

# Product data sheet

Specifications



## Unika interlocked socket - 63 A - 3P + E - 200...250 V AC - IP65 - wall

PKB63P524

### Main

Range	PratiKa
Product or component type	Interlocked socket
Device short name	Unika socket
Plug, socket category	Low voltage
Poles description	3P + E
Network type	AC
Outlet standard	Industrial

### Complementary

Mounting mode	Wall-mounted
[In] rated current	63 A
[Ue] rated operational voltage	200...250 V
Network frequency	50/60 Hz
Ground lug clockwise position	9 h
Protection type	Without protection
Plug, socket material	Housing: self-extinguishing polymer
Contacts material	Pins: stainless steel Screws: stainless steel
Connections - terminals	Captive screws
Maximum cable cross section	35 mm <sup>2</sup>
Maximum cable outer diameter	25 mm
Cable entry	Cable gland
Thread type	Pg 21
Net weight	3 kg
Base dimension	140 x 430 mm
Height	430 mm
Width	140 mm
Depth	190 mm
Colour	Grey (RAL 7035)

---

Voltage colour	Blue
----------------	------

---

## Environment

---

Standards	IEC 60309-2 IEC 60309-1
IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK09 conforming to EN 62262
Fire resistance	750 °C conforming to IEC 60695-2-11
Relative humidity	50 % at 40 °C 70 % at 30 °C 90 % at 20 °C
Ambient air temperature for operation	35 °C ( 86400 s ) -25...40 °C

---

## Packing Units

---

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	3.06 kg
Package 1 Height	19.5 cm
Package 1 width	14 cm
Package 1 Length	43 cm

---

## Offer Sustainability

---

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

---

## Contractual warranty

---

Warranty	18 months
----------	-----------

---