

Product data sheet

Specifications



Unika interlocked socket - 63 A - 3P + N + E - 200...250 V AC - IP65 - wall

PKB63P525

Main

Range	PratiKa
Product or component type	Interlocked socket
Device short name	Unika socket
Plug, socket category	Low voltage
Poles description	3P + N + E
Network type	AC
Outlet standard	Industrial

Complementary

Mounting mode	Wall-mounted
[In] rated current	63 A
[Ue] rated operational voltage	200...250 V
Network frequency	50/60 Hz
Ground lug clockwise position	9 h
Protection type	Without protection
Plug, socket material	Housing: self-extinguishing polymer
Contacts material	Pins: stainless steel Screws: stainless steel
Connections - terminals	Captive screws
Maximum cable cross section	35 mm ²
Maximum cable outer diameter	25 mm
Cable entry	Cable gland
Thread type	Pg 21
Net weight	3 kg
Base dimension	140 x 430 mm
Height	430 mm
Width	140 mm
Depth	190 mm
Colour	Grey (RAL 7035)

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Voltage colour	Blue
----------------	------

Environment

Standards	IEC 60309-2 IEC 60309-1
IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK09 conforming to EN 62262
Fire resistance	750 °C conforming to IEC 60695-2-11
Relative humidity	50 % at 40 °C 70 % at 30 °C 90 % at 20 °C
Ambient air temperature for operation	35 °C (86400 s) -25...40 °C

Packing Units

Unit Type of Package 1	PCE
Package 1 Length	43.0 cm
Number of Units in Package 1	1
Package 1 Width	14.0 cm
Package 1 Height	19.5 cm
Package 1 Weight	3.24 kg

Contractual warranty

Warranty	18 months
----------	-----------

Recommended replacement(s)