

Product data sheet

Specifications



PratiKa wander plug - straight - 32 A - 3P + E - 380...415 V AC - IP67

PKE32M734

Main

| | |
|---------------------------|--------------|
| Range | PratiKa |
| Product or component type | Wander plug |
| Device short name | PratiKa plug |
| Plug, socket category | Low voltage |
| Poles description | 3P + E |
| Network type | AC |
| Outlet standard | Industrial |

Complementary

| | |
|-------------------------------------|---|
| Plug, socket, control station shape | Straight |
| [In] rated current | 32 A |
| [Ue] rated operational voltage | 380...415 V |
| Network frequency | 50/60 Hz |
| Ground lug clockwise position | 6 h |
| Plug, socket material | Housing: self-extinguishing engineering polymer |
| Contacts material | Sleeves: brass |
| Connections - terminals | Captive screws |
| Cable cross section | 2.5...10 mm ² |
| Cable outer diameter | 11.5...21 mm |
| Cable entry | Fair lead Cable gland |
| Thread type | Pg 21 |
| Net weight | 0.22 kg |
| Height | 152 mm |
| Width | 95 mm |
| Depth | 95 mm |
| Colour | Grey (RAL 7035) |
| Voltage colour | Red |

Environment

| | |
|---------------------------------------|---|
| Standards | IEC 60309-2 IEC 60309-1 |
| IP degree of protection | IP67 conforming to IEC 60529 |
| IK degree of protection | IK08 conforming to EN 62262 |
| Fire resistance | 850 °C conforming to IEC 60695-2-11 |
| Relative humidity | 50 % at 40 °C 70 % at 30 °C 90 % at 20 °C |
| Operating altitude | 2000 m |
| Ambient air temperature for operation | 35 °C (86400 s) -25...40 °C |

Packing Units

| | |
|------------------------------|----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 264.0 g |
| Package 1 Height | 9.3 cm |
| Package 1 width | 9.4 cm |
| Package 1 Length | 16.9 cm |
| Unit Type of Package 2 | S03 |
| Number of Units in Package 2 | 12 |
| Package 2 Weight | 4.027 kg |
| Package 2 Height | 30 cm |
| Package 2 width | 30 cm |
| Package 2 Length | 40 cm |
| Unit Type of Package 3 | BB1 |
| Number of Units in Package 3 | 6 |
| Package 3 Weight | 1.77 kg |
| Package 3 Height | 17.8 cm |
| Package 3 width | 26.6 cm |
| Package 3 Length | 26.8 cm |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | Product Environmental Profile |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|