

PKF16G445

Discontinued on: 30 June 2022

(!) To be discontinued

Main

Range	PratiKa
Product or component type	Socket
Device short name	PratiKa socket
Plug, socket category	Low voltage
Poles description	3P + N + E
Network type	AC
Outlet standard	Industrial

Complementary

Complementary	
Mounting mode	Panel-mounted
Plug, socket, control station shape	Straight
[In] rated current	16 A
[Ue] rated operational voltage	480500 V
Network frequency	50/60 Hz
Ground lug clockwise position	7 h
Plug, socket material	Housing: self-extinguishing engineering polymer
Contacts material	Sleeves: brass
Connections - terminals	Captive screws
Cable cross section	14 mm²
Net weight	0.195 kg
Base dimension	90 x 100 mm
Height	100 mm
Width	90 mm
Depth	94 mm
Colour	Grey (RAL 7035)
Voltage colour	Black

Environment

Standards	IEC 60309-1 IEC 60309-2	
IP degree of protection	IP44 conforming to IEC 60529	
IK degree of protection	IK08 conforming to EN 62262	
Fire resistance	850 °C conforming to IEC 60695-2-1	
Relative humidity	50 % at 40 °C 70 % at 30 °C 90 % at 20 °C	
Ambient air temperature for operation	35 °C (86400 s)	

Packing Units

PCE
1
538.0 g
9 cm
10 cm
9.4 cm

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information	
Environmental Disclosure	Product Environmental Profile	
	Product out of China RoHS scope. Substance declaration for your information	

Contractual warranty

Warranty 18 months	
--------------------	--

Recommended replacement(s)

PKF16G445 is replaced by:



PratiKa socket - screw - angled - 16A - 3P + N + E - 480...500 V AC - panel PKF16F445