

PratiKa wander socket - straight - 16 A - 2P + E - 200...250 V AC - IP44

PKF16M423

V	a	ır

Range	PratiKa
Product or component type	Wander socket
Device short name	PratiKa socket
Plug, socket category	Low voltage
Poles description	2P + E
Network type	AC
Outlet standard	Industrial

Complementary

Complementary	
Plug, socket, control station shape	Straight
[In] rated current	16 A
[Ue] rated operational voltage	200250 V
Network frequency	50/60 Hz
Ground lug clockwise position	6 h
Plug, socket material	Housing: self-extinguishing engineering polymer
Contacts material	Sleeves: brass
Connections - terminals	Captive screws
Cable cross section	14 mm²
Cable outer diameter	815 mm
Cable entry	Fair lead Cable gland
Thread type	Pg 21
Net weight	0.16 kg
Height	78 mm
Width	78 mm
Depth	140 mm
Colour	Grey (RAL 7035)
Voltage colour	Blue
·	

Environment

Standards	IEC 60309-1 IEC 60309-2
IP degree of protection	IP44 conforming to IEC 60529
IK degree of protection	IK08 conforming to EN 62262
Fire resistance	850 °C conforming to IEC 60695-2-1
Relative humidity	50 % at 40 °C 70 % at 30 °C 90 % at 20 °C
Ambient air temperature for operation	35 °C (86400 s) -2540 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	148.0 g
Package 1 Height	5 cm
Package 1 width	7.5 cm
Package 1 Length	14.7 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	1.588 kg
Package 2 Height	12.2 cm
Package 2 width	26.4 cm
Package 2 Length	27.2 cm
Unit Type of Package 3	P12
Number of Units in Package 3	240
Package 3 Weight	54.008 kg
Package 3 Height	80 cm
Package 3 width	80 cm
Package 3 Length	120 cm

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information	
Environmental Disclosure	Product Environmental Profile	

Contractual warranty

Warranty	18 months
vvairanty	