# PratiKa wander socket - straight - 16 A - 2P + E - 380...415 V AC - IP67

PKF16M733

|--|

Range	PratiKa
Product or component type	Wander socket
Device short name	PratiKa screw
Plug, socket category	Low voltage
Poles description	2P + E
Network type	AC
Outlet standard	Industrial

#### Complementary

Complementary	
Plug, socket, control station shape	Straight
[In] rated current	16 A
[Ue] rated operational voltage	380415 V
Network frequency	50/60 Hz
Ground lug clockwise position	9 h
Plug, socket material	Housing: self-extinguishing engineering polymer
Contacts material	Sleeves: brass
Connections - terminals	Captive screws
Cable cross section	14 mm²
Cable outer diameter	815 mm
Cable entry	Cable gland
Thread type	Pg 21
Net weight	0.17 kg
Height	84 mm
Width	84 mm
Depth	142 mm
Colour	Grey (RAL 7035)
Voltage colour	Red

#### **Environment**

Standards	IEC 60309-2 IEC 60309-1
IP degree of protection	IP67 conforming to IEC 60529
IK degree of protection	IK08 conforming to EN 62262
Fire resistance	850 °C conforming to IEC 60695-2-1
Relative humidity	50 % at 40 °C 70 % at 30 °C 90 % at 20 °C
Ambient air temperature for operation	35 °C ( 86400 s ) -2540 °C

#### **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.5 cm
Package 1 Width	8.5 cm
Package 1 Length	15.0 cm
Package 1 Weight	171.0 g
Unit Type of Package 2	S03
Number of Units in Package 2	30
Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	5.923 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile

## **Contractual warranty**

Warranty 18 months

### Recommended replacement(s)