



## Main

Range of product	Mobiya Front
Product or component type	Headlight

## Complementary

Safety function	SOS (safe operating stop)
[Us] rated supply voltage	Battery charging: 5 V DC
Luminous flux	60 lm
Battery capacity	0.5 Ah at 3.7 V, Li-Poly (Lithium-Polymer)
Integrated connection type	USB port 5 V DC

## Environment

IP degree of protection	IP54
Product certifications	CE SONCAP SABS LM-79

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.