

14.5 cm

40 cm

19.6 kg

Rack-mounted with kit

Conformance

Width

Depth

Net weight

Mounting mode

Product certifications	CE EAC EN/IEC 62040-1
------------------------	-----------------------------

Environmental

Liviioiiiai	
Ambient air temperature for operation	040 °C
Relative humidity	095 % non-condensing
Operating altitude	03000 m
Ambient air temperature for storage	-1540 °C
Storage Relative Humidity	095 % Non-condensing
Storage altitude	015000 m

Batteries & Runtime

Number of battery blocks per	3
string	

^{*} Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Device mounting	Floor mounted
Number of battery filled slots	0
Number of battery free slots	0
Battery voltage	36 V

Packing Units

_	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	20.8 kg
Package 1 Height	35.5 cm
Package 1 width	23.5 cm
Package 1 Length	52.5 cm
Unit Type of Package 2	P12
Number of Units in Package 2	7
Package 2 Weight	147 kg
Package 2 Height	50 cm
Package 2 width	80 cm
Package 2 Length	120 cm

Offer Sustainability

REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	2 years repair or replace
Warranty	2 years repair or replace