

BLACK 35

AUTOMOTIVE NON METALLISED

BLACK 35

The Black 35 tinted automotive window film confers a touch of aesthetic embellishment to any vehicle, whilst ensuring moderate privacy from prying eyes

Warranty
2 YEARS

Storage From -5C TO +40C
3 YEARS

REACH RoHS Compliant
RESPECTED

WIDTHS AVAILABLE

↔ 51 CM
↔ 76 CM
↔ 101 CM
↔ 152 CM

TECHNICAL DATA SHEET

Data calculated based on film applied to clear glass 3mm thick (*on double glazing 4-16-4)


Ultraviolet Transmission	5 %
Visible Light Transmission	35 %
Reflection Of Ext Visible Light	5 %
Reflection Of Int Visible Light	6 %
Total Solar Energy Rejected	36 %
Total Solar Energy Rejected 2	26 %
Solar Ratio :	
Solar Energy Reflection	-
Solar Energy Absorption	-
Solar Energy Transmission	-
Reduction In Solar Glare	64 %
G-Value	-
U-Value	-
Shading Coefficient	NC
Installation Type	INTERNAL
Roll Length	30.5 M
PET/PVC Composition	PET
Thickness	23 µ
Colour	BLACK

INSTALLATION ADVICE

Vertical installation and on standard glass surface*

Clear Single Pane	✓
Tinted Single Pane	!
Reflective Tinted Single Pane	✓
Clear Double Pane	✓
Tinted Double Pane	x
Reflective Tinted Double Pane	x
Gas Filled Double Pane - Low E	!
STADIP EXT. Clear Double Pane	!
STADIP INT. Clear Double Pane	x

Yes ✓ Caution ! No x



MAINTENANCE INSTRUCTIONS

Soapy water solution, do not clean for at least a month & do not apply any type of sticker or adhesive on the film

CONSTRUCTION

1. "Hard" scratch resistant layer, for durability and ease of maintenance during window cleaning
2. Dyed polyester without optical distortion
3. PS adhesive, glass polymerization within 15 days
4. Protection release liner, disposable after installation