

STEEDA FUSION STRUT TOWER BRACE

Installation Instructions for Part #:555-5720 and #555-5727

- 1) Remove the two nuts on each strut tower which are closest to the firewall. It is not necessary to remove the third nut.
- 2) Set the strut tower brace on the car with the holes in the end brackets over the studs on the strut tower. Jack up one side of the car with a floor jack if the bolt holes do not line up properly upon assembly.
- 3) Reinstall the nuts on the strut tower, over the strut tower brace brackets. Torque nuts to 18 ft-lb. (25 Nm).
- 4) Screw the cap back onto the brake fluid reservoir if removed.

Steeda Autosports Inc. All Rights Reserved 2006 *STBFusion.doc 8/06*

STEEDA FUSION STRUT TOWER BRACE

Installation Instructions for Part #:555-5720 and #555-5727

- 1) Remove the two nuts on each strut tower which are closest to the firewall. It is not necessary to remove the third nut.
- 2) Set the strut tower brace on the car with the holes in the end brackets over the studs on the strut tower. Jack up one side of the car with a floor jack if the bolt holes do not line up properly upon assembly.
- 3) Reinstall the nuts on the strut tower, over the strut tower brace brackets. Torque nuts to 18 ft-lb. (25 Nm).
- 4) Screw the cap back onto the brake fluid reservoir if removed.

Steeda Autosports Inc. All Rights Reserved 2006 *STBFusion.doc 8/06*

STEEDA FUSION STRUT TOWER BRACE

Installation Instructions for Part #:555-5720 and #555-5727

- 1) Remove the two nuts on each strut tower which are closest to the firewall. It is not necessary to remove the third nut.
- 2) Set the strut tower brace on the car with the holes in the end brackets over the studs on the strut tower. Jack up one side of the car with a floor jack if the bolt holes do not line up properly upon assembly.
- 3) Reinstall the nuts on the strut tower, over the strut tower brace brackets. Torque nuts to 18 ft-lb. (25 Nm).
- 4) Screw the cap back onto the brake fluid reservoir if removed.

Steeda Autosports Inc. All Rights Reserved 2006 *STBFusion.doc 8/06*

STEEDA FUSION STRUT TOWER BRACE

Installation Instructions for Part #:555-5720 and #555-5727

- 1) Remove the two nuts on each strut tower which are closest to the firewall. It is not necessary to remove the third nut.
- 2) Set the strut tower brace on the car with the holes in the end brackets over the studs on the strut tower. Jack up one side of the car with a floor jack if the bolt holes do not line up properly upon assembly.
- 3) Reinstall the nuts on the strut tower, over the strut tower brace brackets. Torque nuts to 18 ft-lb. (25 Nm).
- 4) Screw the cap back onto the brake fluid reservoir if removed.

Steeda Autosports Inc. All Rights Reserved 2006 *STBFusion.doc 8/06*

STEEDA FUSION STRUT TOWER BRACE

Installation Instructions for Part #:555-5720 and #555-5727

- 1) Remove the two nuts on each strut tower which are closest to the firewall. It is not necessary to remove the third nut.
- 2) Set the strut tower brace on the car with the holes in the end brackets over the studs on the strut tower. Jack up one side of the car with a floor jack if the bolt holes do not line up properly upon assembly.
- 3) Reinstall the nuts on the strut tower, over the strut tower brace brackets. Torque nuts to 18 ft-lb. (25 Nm).
- 4) Screw the cap back onto the brake fluid reservoir if removed.

Steeda Autosports Inc. All Rights Reserved 2006 *STBFusion.doc 8/06*