

TOOL-A-THON°



Come Visit Us At Our Booth 134360!



Volume 24.2 Valid May 1st - Aug. 31st

www.fowlerprecision.com

Fowler Trimos THV Horizontal Calibration Packages





Specifications:	
Overall Application Range	Using standard probe
External measurement	0 - 4" /0 - 100mm
Internal measurement	0.4 - 4" /10 - 100mm
Scale Range (travel)	Absolute display up to 2"/50mm
Max. Measuring Band Error	0.000016"/0.4µm reference
Temperature 20°C	
Resolution on Heidenhain ND 287	0.00001", 0.000001"
Repeatability	0.000005" ±2s (0.1µm)
Adjustable Measuring Force	0 to 12N (0 - 40 oz.)

THV Package 1 includes...

For checking pins, plugs and plain rings up to 4"

Includes	Description
54-198-558-0	THV with Floating Table
54-198-100-0	Block Support for H-Plate
54-198-101-0	H - Plate, provides clearance for plugs
54-198-261-0	Reverse Attachment American style
*THV Readout Required	

Order No. 54-198-777-P1

Special Package Price \$26,054.00

List Price \$30,652.31

THV Package 2 includes...

For checking thread plugs and plain rings up to 4"

Includes	Description
54-198-508-0	THV with Standard Table
54-198-100-0	Block Support for H-Plate
54-198-101-0	H - Plate, provides clearance for plugs
54-197-007-0	Thread Wire Set
*THV Readout Required	

Order No. 54-198-777-P2

Special Package Price \$21,652.00

List Price \$25.473.64

THV Readouts - sold separately

Order No.	Description	List Price	Sale Price
54-198-400-0	USB Signal Converter w/ WIN DHI Software (Laptop required)	\$4,597.70	\$4,460.00
54-198-111-0	THV Digital Display	\$3,808.53	\$3,460.00

Fowler Trimos Mini Horizontal Calibration Package

This economically priced set allows you to easily calibrate internal and external setting standards as well as measure parts up to 4" OD and as small as 0.24" ID.

The Fowler Trimos Mini Horizontal Special includes the Trimos Mini Horizontal and the Sylvac Nano Indicator with Bluetooth. Includes everything to get started! Additional accessories available, contact our technical department 1-800-788-2353.



Mini-Horizontal Features:

- · Internal range: 0.24" 4"/6 100mm
- External range: 0 4"/0 100mm
- Resolution: 0.00001"/0.0001mm
- · Accuracy: 0.00008"/0.0022mm
- Monoblock construction with probe guide track
- · Adjustable end-stop with anvil location
- Adjustable measuring pressure
- · Adjustable measuring table



Mark VI NANO Electronic Indicator Features:

- Range: 1"/25mm
- Resolution: 0.00001"/0.0001mm
- Accuracy: 0.00008"/0.0022mm
- Repeatability: 0.00002"/0.0005mm
- Lifetime warranty
- Large display
- Bluetooth
- IP54 protected against fluid and dust











Order No. 53-190-012-TP

Special Package Price

List Price \$9.995.00

Fulcrum Revolutionary Manual CMM



Features

- Small footprint allowing measurements right next to your machine
- Intuitive software, allows quick and easy measurement
- Minimal setup
- · Programmable magnetic soft buttons allow you to quickly change between software features without using a mouse
- · Magnetic fixture templates allow you to quickly fix your part
- · Volumetric accuracy of 0.0002"/0.005mm
- · Uses a single USB cable to connect and requires no air



Calibration Artifact



Kit Includes:

NEW Star Styli Probe Kit optional

The Fulcrum can be supplied with our optional star styli kit. The star styli ensures excellent metrology performance and accessibility to side-face features measured in the X-Z or Y-Z projection planes.



Order No. 54-960-403-0

3mm Star Stylus



Extol CMM (Mark 1)

- · Shop floor hardened for use at the machine center
- · Easy to use FUSION Software
- · Robust enough to use around the clock
- 5 temp. sensors allow for use in uncontrolled environments





Order No.	Description
MK1-EXT-370	(XY) 370mm x (Z) 270mm
MK1-EXT-520	(XY) 520mm x (Z) 300mm
MK1-EX1-520	(XY) 520mm x (Z) 300mm





Horizontal Setting and Calibration

Setting of measuring equipment with variable dimensions.

HC5



Features:

- Designed for the calibration of fixed and variable measuring equipment
 Available in sizes up to 120"
- · Adjustable measuring force

Order No. 54-197-370-0

HS6

Features:

- For setting equipment with variable dimensions quickly and accurately
- Available in sizes up to 120"
- Large selection of accessories to handle any job

Order No. 54-196-900-5



NEW Rapid Measuring Systems





Measures multiple parts simultaneously



One touch measuring

Features:


- · Simultaneous measuring up to 100 parts
- · Simple place and press measurement finish in 3 seconds
- · No more operator errors
- · Powerful yet easy to use measuring software
- Up to 12" x 8" field of view
- High resolution: 0.00004"/0.0001mm

Model No.	Measuring Range
54-830-310-0	100mm x 200mm
54-830-320-0	200mm x 200mm
54-830-830-0	300mm x 200mm

Call for more information, 1-800-788-2353!

Venture 3030 XT Multi-Sensor Vision System





baty





The BEST Solution for Shaft Scanning!

Increase productivity while reducing scrap and inspection cycle times by a factor of 10.

















SCAN S25T

Fast, Accurate, Reliable & Repeatable!

Features:

- · Ideal for small cylindrical parts
- · Measuring range: 1.02"/26mm Diameter, 7.87"/200mm Length
- · High resolution and high accuracy
- One-click rapid measuring
- 30° tilting optics for complete thread measurements

Order No. 54-902-025-5





SCAN F60T

For Larger Parts!

Features:

- · Complete 2D part scan in less than 3 seconds
- · Measuring range: 2.3"/60mm diameter, 12"/300mm length
- · Reduce inspection time & scrap, Increase productivity
- · High resolution and high accuracy
- One-click rapid measuring
- · 30° tilting optics for complete thread measurements

Order No. 54-902-406-5

SCAN S145's

Our Largest Machines!

Features:

- · Full part measurement in just a few seconds
- · Measuring range: 5.7"/145mm diameter, 50.3"/1280mm length
- · Reduce inspection time & scrap, increase productivity
- · High resolution and high accuracy
- One-click rapid measuring
- Optional measuring probe for measuring keyways, holes and hole locations

Order No. 54-902-145-5





Fowler Trimos V Series Electronic Height Gages

The Fowler Trimos V series vertical measuring instruments have been developed for the most difficult shop floor environments. Manufactured in Switzerland, they guarantee precise and repeatable measurements with superior ease of use.

Features:

- Electronically adjustable measuring force 0.75/1.5 (N)
- Lithium-ion rechargeable batteries last up to 40 hours
- · Bluetooth transmitter available

All models include:

- · Charging unit
- Measuring probe with ruby ball Ø4mm
- · Probe holder elbow Ø 8mm
- · Setting gage
- Test certificate











V-Series Electronic Height Gages Comparison Chart

	V9	V8	V7	V6	V5	V4	V3
Accuracy							
1.2 + L(mm)/1000 μm	\checkmark	\					
2 + L(mm)/400 μm			\checkmark	\checkmark			
2.5 + L(mm)/300 μm					/		
4.5 - 6 μm						\checkmark	
7 - 8 μm							V
Range							
400/700mm	\checkmark	/	/	\	\checkmark	\	I
1100mm	\checkmark	√	\checkmark	√	\checkmark		
Smart Reverse for Ø	\checkmark	/	/	\	/	/	I
Air Cushion	\checkmark	✓	/	\	\checkmark	I	
Wireless Option	\checkmark	/	/	\	/	/	
Manual/Motorized	\checkmark		\checkmark	√	\checkmark		
Manual ONLY		V				V	V
Fine Adjustment		\checkmark					
Color Display	\checkmark		\				
2D Measuring	\checkmark		/				

Certify Any Height Gage Below For Only \$199.00 Valid only for Tool-A-Thon 24.2

Order No.	Range F	Range with Probe Inverted	List Price	Sale Prie
V3				
54-192-340-0	16"/407mm 2	20"/508mm	\$5,419.97	\$5,149.0
54-192-370-0	28"/711mm 3	31.9"/812mm	\$5,511.60	\$5,237.0
/4				
54-191-440-0	16"/407mm 2	28.3"/719mm	\$6,584.83	\$6,256.0
54-191-470-0	28"/711mm 4	0.2"/1023mm	\$8,305.31	\$7,891.0
V5				
54-199-540-0	16"/407mm 2	28.3"/719mm	\$7,257.34	\$6,895.0
54-199-570-0	28"/711mm 4	0.2"/1023mm	\$8,600.23	\$8,171.0
54-199-590-0	43.7"/1110mm 5	66"/1422mm	\$13,583.85	\$12,905.0
V6				
54-199-640-0	16"/407mm 2	28.3"/719mm	\$9,014.34	\$8,564.0
54-199-670-0	28"/711mm 4	0.2"/1023mm	\$10,458.85	\$9,936.0
54-199-690-0	43.7"/1110mm 5	66"/1422mm	\$15,163.41	\$14,406.0
V7				
54-199-740-0	16"/407mm 2	28"/719mm	\$11,963.78	\$11,366.0
54-199-770-0	28"/711mm 4	0"/1023mm	\$12,781.27	\$12,143.0
54-199-790-0	44"/1100mm 5	66"/1422mm	\$18,311.10	\$17,396.0
V8 - Fine Adjustment				
54-199-840-0	16"/407mm 2	28"/724mm	\$13,157.00	\$12,500.0
54-199-870-0	28"/710mm 4	0"/1028mm	\$14,508.73	\$13,784.0
54-199-890-0	43"/1109mm 5	6"1427mm	\$21,389.93	\$20,321.0
V9				
54-199-940-0	16"/407mm 2	28"/724mm	\$13,871.20	\$13,178.0
54-199-970-0	28"/710mm 4	0"/1028mm	\$14,254.65	\$13,542.0
54-199-990-0	43"/1109mm 5	6"/1427mm	\$21,462.33	\$20,390.0
Probe Sets				
54-199-105-0	4mm Probe Set, 21 piece		\$1,923.23	\$1,828.0
54-199-106-0	8mm Probe Set, 16 piece		\$1,556.00	\$1,479.0
54-199-107-0	8mm Basic Probe Set, 7 pie	ece	\$509.53	\$485.0
Accessories	, , , ,			
45-300-002-0	ISO Certification		\$379.00	\$199.0
54-199-400-0	12"/300mm Holder - for 8mi	m probes	\$1,167.27	\$1,109.0
54-199-022-BT	Bluetooth transmitter (Not a		\$675.78	\$642.0
54-777-120-0		ting multiple units to one PC	\$538.54	\$485.0



Features:

- · Bluetooth for quick, easy recorded measurements
- · Extra low measuring force, from 0.2N

54-931-150-BT

- Measure internal and external diameters, centerlines, heights, widths, depths and MIN/MAX/TIR capability
- · Excellent repeatability thanks to the motorized carriage
- · High reliability
- · Bluetooth, USB and RS232 data outputs
- Battery life: 40 hours rechargeable during operation
- · Touch sensitive probe speed for easy operation
- Base with small footprint
- Includes: protective cover, charging set, ruby ball probe Ø3mm, setting gage and calibration certificate

Full Probe Set



54-930-215-0

FREE Basic Probe Set

with 54-931-450-BT Hi_Cal Purchase \$951.03 Value!



54-930-217-0

ISO Certification available for \$199.00 extra!

Order No.	Range	Accuracy	List Price	Sale Price
54-931-150-BT	6"/150mm	0.00013"/0.0034mm	\$6,080.26	\$5,473.00
54-931-150-BT-C	6"/150mm with ISO/A2LA Certification	1		\$5,672.00
54-931-300-BT	12"/300mm	0.00016"/0.0042mm	\$6,636.83	\$5,974.00
54-931-300-BT-C	12"/300mm with ISO/A2LA Certification	12"/300mm with ISO/A2LA Certification		
54-931-450-BT	17.5"/450mm	0.00020"/0.005mm	\$7,554.76	\$6,442.00
54-931-450-BT-C	17.5"/450mm with ISO/A2LA Certificat	tion		\$6,641.00
Accessories				
54-930-215-0	Full Probe Set		\$1,771.05	\$1,594.00
54-930-217-0	Basic Probe Set		\$951.03	\$856.00

NEW V1 & V1+

Electronic Height Gages

Introducing the next generation of Trimos entry-level height gages for the workshop.



Features:

- V1 features a fine adjust hand-wheel for scribing (optional scriber)
- · V1+ features bi-directional measuring force hand-wheel for measuring bores, centerlines, heights, min/max/delta
- · Accuracy: 0.0012"/0.03mm
- · Supplied with 0.236"/6mm ball probe
- · Bluetooth/RS232 data output
- Steel base and extra large display with simplified keypad









Order No.	Range	Range	Resolution	List Price	Sale Price
54-180-424-0	V1	24"/611mm	0.0005"/0.01mm	\$3,299.99	\$2,999.99
54-180-524-0	V1+	24"/611mm	0.0005"/0.01mm 0.00005"/0.001mm	\$4,399.99	\$3,999.99



Z-HEIGHT.{

Electronic Height Gages

With handwheel and fine adjust.

- Base design has a more comfortable grip and is finely ground and lapped for smooth movement on surface plates
- Fine adjust feature allows precise adjustment to required settings
- Preset feature allows setting pre-determined or reference measurements
- · Indicator holding bar included
- Resolution 0.0005"/0.01mm
- Large, high contrast LCD display
- Coarse adjustment hand wheel
- · Carriage locking lever
- · Carbide tipped scriber

54-175-024-0 shown

Calibration certificates available for all sizes.

Order No.	Range	Accuracy	List Price	Sale Price
54-175-012-0	12"/300mm	± 0.0015"/0.04mm	\$584.91	\$510.00
54-175-018-0	18"/450mm	± 0.002"/0.05mm	\$696.17	\$627.00

Fowler Bowers BLUET001



XTH3 Bluetooth Holematic Pistol Grips

Features:

- · Coolant proof, dust proof IP67
- Resolution: 0.00005"/0.001mm
- · Bluetooth connectivity to your phone or tablet
- · Self centering 3 point heads above 0.250"
- · Tungsten carbide measuring faces on all 3-point heads from 0.5"/12.5mm and up
- · Sizes over 0.500"/12.5mm feature blind bore capability
- · Includes UKAS certificates for all pistol grip, heads and rings



54-567-100-BT

For special application heads, contact the Fowler Technical Department 1-800-788-2353















	Order No.	naliye	includes	LIST PITCE	Sale Price			
Pistol Grip Individual Sets								
	54-567-720-BT	0.750" - 1"/20 - 25mm	1 head, 1 handle, 1 ring	\$2,774.23	\$2,372.00			
	54-567-725-BT	1" - 1.375"/25 - 35mm	1 head, 1 handle, 1 ring	\$2,995.57	\$2,697.00			
	54-567-735-BT	1.375" - 2"/35 - 50mm	1 head, 1 handle, 1 ring	\$3,075.38	\$2,768.00			
	Pistol Grip Complete	e Sets						
	54-567-009-BT	0.080" - 0.250"/2 - 6mm (2 pt.)	5 heads, 1 handle, 3 rings	\$7,033.38	\$6,014.00			
	54-567-010-BT	0.250" - 0.375"/6- 10mm	2 heads, 1 handle, 1 ring	\$2,757.87	\$2,358.00			
	54-567-020-BT	0.375" - 0.750"/10 - 20mm	3 heads, 1 handle, 2 rings	\$3,226.40	\$3,049.00			
	54-567-050-BT	0.750" - 2"/20 - 50mm	3 heads, 1 handle, 2 rings	\$4,165.94	\$3,937.00			
	54-567-100-BT	2" - 4"/50 - 100mm	3 heads, 1 handle, 2 rings	\$4,636.93	\$4,174.00			
	54-567-105-BT	4" - 6"/100 - 150mm	2 heads, 1 handle, 1 ring	\$4,165.94	\$3,937.00			
	54-567-110-BT	6" - 8"/150 - 200mm	2 heads, 1 handle, 1 ring	\$5,498.92	\$4,702.00			
	54-567-200-BT	4" - 8"/100 - 200mm	4 heads, 1 handle, 2 rings	\$8,703.75	\$8,226.00			
	54-567-210-BT	0.750" - 4"/20 - 100mm	6 heads, 1 handle, 4 rings	\$5,091.00	\$4,836.00			
	54-567-620-BT	0.250" - 0.750"/6 - 20mm	5 heads, 1 handle, 3 rings	\$3,722.00	\$3,434.00			
	Connectivity Cables	/Accessory						
	54-115-526-0	Proximity cable with USB conne	ction	\$223.37	\$202.00			
	54-115-527-0	Proximity cable with serial conne	ection	\$216.29	\$195.00			
	54-115-246-RT	USB bluetooth receiver		\$49.45	\$43.00			

Bore Gaging Systems



XTD3 Bluetooth Electronic Holemikes



- Coolant proof, dust proof IP67
- Resolution: 0.00005"/0.001mm
- Bluetooth connectivity to your phone or tablet
- Self centering 3 point heads above 0.250"
- Tungsten carbide measuring faces on all 3-point heads from 0.5"/12.5mm and up
- · Sizes over 0.500"/12.5mm feature blind bore capability
- · Includes UKAS certificates for all pistol grip, heads and rings













- · 3-pt contact with tungsten carbide measuring anvils above 0.5"
- · Blind bore measuring heads featured above 0.5"
- · Ratchet stop for consistent measuring
- Extensions available for deep measuring
- Includes UKAS certificates for all Holemikes and setting rings

			Meas.	Ring	Ring	List	Sale
Order No.	Range	Grads.	Accuracy	Depth	Included	Price	Price
52-255-310-0	0.250" - 0.312"	0.00025"	0.00015"	2.28"	0.312"	\$829.07	\$622.00
52-255-311-0	0.312" - 0.375"	0.00025"	0.00015"	2.28"	0.312"	\$767.67	\$576.00
52-255-312-0	0.375" - 0.500"	0.00025"	0.00015"	2.28"	0.5"	\$767.67	\$576.00
52-255-313-0	0.500" - 0.625"	0.00025"	0.00015"	2.44"	0.5"	\$767.67	\$576.00
52-255-314-0	0.625" - 0.750"	0.00025"	0.00015"	2.44"	0.75"	\$787.25	\$591.00
52-255-315-0	0.750" - 1"	0.00025"	0.00015"	2.60"	0.75"	\$864.56	\$649.00
52-255-316-0	1" - 1.375"	0.00025"	0.00015"	2.60"	1.375"	\$1,231.87	\$924.00
52-255-317-0	1.375" - 2"	0.00025"	0.00015"	3.15"	1.375"	\$1,261.24	\$946.00
52-255-318-0	2" - 2.625"	0.00025"	0.0002"	3.15"	2.625"	\$1,504.52	\$1,129.00
52-255-319-0	2.625" - 3.250"	0.00025"	0.0002"	3.15"	2.625"	\$1,517.98	\$1,139.00
52-255-320-0	3.250" - 4"	0.00025"	0.0002"	3.94"	3.25"	\$1,893.75	\$1,421.00
Sets							
52-255-565-0	0.250" - 0.375"	2 heads, 2 l	handles, 1 ring			\$1,686.00	\$1,265.00
52-255-665-0	0.375" - 0.750"	3 heads, 3 l	nandles, 2 ring	s		\$2,096.32	\$1,573.00
52-255-775-0	0.750" - 2"	3 heads, 3 l	nandles, 2 ring	S		\$3,293.82	\$2,471.00
52-255-885-0	2" - 4"	3 heads, 3 l	handles, 2 ring	S		\$4,465.29	\$3,349.00

52-255-312-0

MicroGage

Pocket sized 2-point bore gaging system.



- System range: 0.040" 0.250"/1 6mm
- Switchable resolution 0.0005", 0.00005"/0.01, 0.001, 0.0005mm
- · Repeatability: 0.00005"/0.001mm
- · Sets include setting rings with UKAS certificates
- Depth stops available, call our technical department 1-800-788-2353

0	
BOWERS GROUP	



Order No.	Description	List Price	Sale Price
54-551-010-0	0.037" - 0.096"/0.95 - 2.45mm	\$3,950.93	\$3,556.00
54-551-011-0	0.060" - 0.167"/1.5 - 4.25mm	\$3,866.75	\$3,481.00
54-551-012-0	0.089" - 0.250"/2.25 - 6.35mm	\$4,162.44	\$3,747.00
Connectivity Cables			
54-115-526-0	Proximity cable with USB connection	\$223.37	\$202.00
54-115-527-0	Proximity cable with serial connection	\$216.29	\$195.00

Ultima Bore Gaging Systems



Features:

- Accuracies of 0.00004" up to 1.97"
- Ceramic anvils with blind bore capabilities above 0.472"
- · Uses compact, multi function Sylvac display





Order No.	Description	Set Includes	List Price	Sale Price
54-565-006-1	0.078" - 0.236"/2 - 6mm	Includes: handle, rings & heads	\$7,642.60	\$6,497.00
54-565-010-1	0.236" - 0.393"/6 - 10mm	Includes: handle, rings & heads	\$4,150.90	\$3,529.00
54-565-020-1	0.393" - 0.787"/10 - 20mm	Includes: handle, rings & heads	\$6,175.54	\$5,250.00
54-565-070-1	0.236" - 0.787"/6 - 20mm	Includes: handle, rings & heads	\$9,658.72	\$7,727.00
54-565-080-1	0.787" - 1.97"/20 - 50mm	Includes: handle, rings & heads	\$10,589.24	\$8,472.00
54-565-090-1	1.97" - 3.94"/50 - 100mm	Includes: handle, rings & heads	\$11,758.98	\$9,408.00
54-565-100-1	0.787" - 3.94"/20 - 100mm	Includes: handle, rings & heads	\$18,007.01	\$16,207.00
Digital Displays				
54-618-106-2	Sylvac D62S Digital Display		\$1,535.33	\$1,382.00
54-618-106-3	Sylvac D62S Advanced Digit	tal Display	\$1,982.16	\$1,884.00

Deluxe Universal Gage

Internal & External Measurements up to 118" (with optional extensions)






Features:

- Used for Internal and external measurement
- ID range 1.18" 10", OD range 0 8.4"
- Large range of accessories with constant measuring pressure and digital readout
- Stackable extensions for increasing range available
- · Anvil travel of 0.78"

Available on special order

Pair of ball inserts for gear/spline measurements. Thread inserts for internal/external threads. Special anvils such as cones, balls, pins, etc. Contact our Technical Department for price quotes.



	Accessories	included
Α	. 54-265-045-0	Pair of Flat Shoulder Anvils
В	. 54-265-048-0	Pair of Internal Disc Anvils (large)
C	. 54-265-049-0	Pair of Internal/External Disc Anvils (small)
D	. 54-265-055-0	Pair of Clamping adaptors
E	. 54-265-047-0	Pair of Cylindrical Shoulder Anvils
F.	54-265-015-0	Pair of Spherical Tip Contact Points
G	. 54-265-030-0	Pair of Measuring Arms 3"(75mm) long
H	. 54-265-040-0	Pair of Measuring Arms 4"(100mm) long
I.	54-265-043-0	Pair of Depth Stops
J.	54-265-020-0	Pair of Measuring Arms 2"(50mm) long
K	. 54-265-010-0	Pair of Flat Contact Points
L	. 54-265-041-0	Pair of Mounting attachments

Order No. 54-265-777-0



XTENDER: Electronic Bore Gage Set

with Carbide Anvils

Industry's two most popular bore gage ranges combined in one easy-to-use electronic set!

Preset size of master for absolute reading and use minimum hold feature to lock on the bore size as the gage is rocked in the part to be measured.

Off 1865

Bore Gage features:

- Range: 1.4"-6"/35mm-150mm
- · Carbide anvils
- Self-centering

Indicator features:

- · Bar graph for reversal point indication
- Preset with recall
- ABS/INC measurement
- · Min/Max/TIR



Use with Bore Gage Setting Master Kits, page 17.

Order No.	Range	Resolution	List Price	Sale Price
54-646-401-0	1.4 - 6"/35 - 150mm	0.00005"/0.001mm	\$420.79	\$358.00
Extensions				
52-646-450-0	20" depth extension		\$108.40	\$98.00
52-646-475-0	40" depth extension		\$121.82	\$110.00

Dial Cylinder Bore Gages

2-point bore measuring



52-646-300-0

Features:

- Carbide Anvils
- Easy-to-read
- Great value
- Graduation: 0.0005", 0.0001" or 0.01mm
- Insulated grip
- 9.5" depth above 1.5"
- Chrome plated handle



52-646-400-0

Use with Bore Gage Setting Master Kits, page 17.

Order No.	Range	Graduation	List Price	Sale Price
52-646-100-0	0.7" - 1.5"	0.0005"	\$169.38	\$128.00
52-646-300-0	2" - 6"	0.0005"	\$160.27	\$137.00
52-646-400-0	1.4" - 6"	0.0005"	\$212.85	\$160.00
52-646-500-0	1.4" - 6"	0.0001"	\$276.34	\$235.00
52-646-220-0	35 - 60mm	0.01mm	\$277.40	\$236.00
Extensions				
52-646-450-0	20" depth extension	*Not for use with 52-646-100-0	\$108.40	\$98.00
52-646-475-0	40" depth extension	*Not for use with 52-646-100-0	\$121.82	\$110.00

Internal & External Electronic Caliper Gages

For grooves and recesses.




Features:

- Accuracy: ± 0.0008"/± 0.02mm
- Resolution: 0.0002"/0.005mm
- · Analog scale for reversal point indication
- · Large, LCD display



- Preset capability
- · Absolute and incremental measurements modes
- · High-impact, aircraft aluminum case
- Rugged housing



Metric	Inch	L	S	Н	Tip Radius
5-15mm	0.2-0.6"	20mm	1.0mm	1.5mm	0.3mm
5-25mm	0.2-1.0"	35mm	1mm	1.5mm	0.3mm
10-30mm	0.4-1.2"	55mm	2mm	3.5mm	0.5mm
20-40mm	0.8-1.6"	80mm	3mm	6.5mm	0.5mm
30-50mm	1.2-2.0"	80mm	3mm	8.5mm	0.5mm

Metric	Inch	L	S	Н	Tip Radius
0-10mm	0-0.4"	40mm	3mm	8mm	0.5mm
0-20mm	0-0.8"	80mm	6.5mm	25mm	0.75mm
10-30mm	0.4-1.2"	80mm	6.5mm	25mm	0.75mm
20-40mm	0.8-1.6"	80mm	6.5mm	25mm	0.75mm
30-50mm	1.2-2.0"	80mm	6.5mm	25mm	0.75mm

_	30-30mm 1.2-2.0°	80mm	mmcs mmc.o	U./5mm
Order No.	Range		List Price	Sale Price
Internal Caliper Gages				
54-554-611-0	0.200" - 0.590"/5 - 15mm		\$207.51	\$177.00
54-554-622-0	0.200" - 1"/5 - 25mm		\$222.49	\$190.00
54-554-623-0	0.400" - 1.2"/10 - 30mm		\$232.88	\$198.00
54-554-624-0	0.790" - 1.6"/20 - 40mm		\$266.52	\$227.00
54-554-625-0	1.2" - 2"/30 - 50mm		\$266.52	\$227.00
External Caliper Gages				
54-554-711-0	0 - 0.400"/0 - 10mm		\$237.48	\$202.00
54-554-722-0	0 - 0.790"/0 - 20mm		\$254.63	\$217.00
54-554-723-0	0.4" - 1.2"/10 - 30mm		\$266.52	\$227.00
54-554-724-0	0.790" - 1.6"/20 - 40mm		\$266.52	\$227.00
54-554-725-0	1.2" - 2"/30 - 50mm		\$232.88	\$198.00

Bore Gage Setting Master Kits - Inch & Metric

Fowler's Bore Gage Setting Master Kit is used for accurately setting any 2 point cylinder bore gage up to 6"/150mm in diameter to an accuracy of 0.0001"/0.003mm

Each Set includes: Setting Device Base anvil: 3.950" x 1.050" Adjustable anvil 2.375" x .375" (two each)

- Internal capacity: 6"/150mm
- · Centralizer capacity width: 2.750"
- · Quick-release holder for fast adjustment

Economy Gage Block Sets Inch model:

- 36 piece
- Tolerances to .00005"
- · Certificate of Calibration to NIST

Metric model:

- 33 piece
- AS-2 grade
- · Certificate of Calibration to NIST

Bore gage shown not included

Bore gage setting master and gage block set! All in a custom-fitted case!

Order No.	Description	List Price	Sale Price
53-646-000-1	Inch Bore Gage Setting Master Kit	\$400.72	\$341.00
53-646-010-0	Metric Bore Gage Setting Master Kit	\$407.18	\$347.00
53-646-005-0	Bore Gage Setting Master Kit - without Gage Blocks	\$247.69	\$211.00

Electronic Calipers Comparison Chart


	Data Output	Wireless	IP Rating	IN/MM/Frac.	Sizes
Ultra-Cal VI Calipers	\checkmark	/	IP67	_	6", 8", 12"
Ultralight IV Calipers	J	√	IP67	_	15", 24", 40", 60", 80", 100"
IP67 Calipers	\checkmark	√	IP67	_	6", 12"
Digital Calipers	\checkmark	\checkmark	IP40	_	4", 6", 8", 12"
Carbon Fiber Calipers	√	_	IP65	_	24", 40", 60"
Xtra-Range Calipers	✓	_	IP54	_	12", 24"
Xtra-Value PLUS Calipers	-	_	IP54	√	6", 12"
Xtra-Value Calipers	_	_	_	_	6", 8", 12"

Swiss Ultralight IV Electronic Calipers

When you have **HUGE** parts to measure, this is the caliper you need!



Alternative jaws available, contact the Fowler Technical Department for more information 1-800-788-2353





Swiss Ultra-Cal VI Electronic Calipers

3 styles to suit your needs.





Features:

- · IP67 protected against fluid and dust
- · Available with Bluetooth, proximity cable or no SPC output
- · Heavy duty frame
- Extra large display
- · Available with ISO Cert
- 12"/300mm is supplied without depth rod









Calibration certificates available for all sizes.

Order No.	Range	Accuracy	Resolution	List Price	Sale Price
Bluetooth Commi	unication				
54-100-167-0	6"/150mm	0.0008"/20µm	0.0005"/0.01mm	\$425.08	\$383.00
54-100-168-0	8"/200mm	0.0012"/30µm	0.0005"/0.01mm	\$725.47	\$653.00
54-100-169-0	12"/300mm	0.0012"/30µm	0.0005"/0.01mm	\$886.25	\$754.00
Proximity Cable (Communication				
54-100-444-1	6"/150mm	0.0008"/20µm	0.0005"/0.01mm	\$196.06	\$177.00
54-100-448-1	8"/200mm	0.0012"/30µm	0.0005"/0.01mm	\$439.69	\$396.00
54-100-412-1	12"/300mm	0.0012"/30µm	0.0005"/0.01mm	\$593.06	\$534.00
Without Data Out	put				
54-100-177-0	6"/150mm	0.0008"/20µm	0.0005"/0.01mm	\$169.18	\$153.00
54-100-178-0	8"/200mm	0.0012"/30µm	0.0005"/0.01mm	\$398.79	\$359.00
54-100-179-0	12"/300mm	0.0012"/30µm	0.0005"/0.01mm	\$460.06	\$415.00
Connectivity Cab	les/Accessories				
54-981-713-2	Sylcom Basic Da	ata Processing Softwar	е	\$810.69	\$771.00
54-115-526-0	Proximity cable	Proximity cable with USB Connection			\$202.00
54-115-527-0	Proximity cable	Proximity cable with Serial Connection			\$195.00
54-115-246-BT	USB Bluetooth F	Receiver		\$49.45	\$43.00



IP67 Electronic Calipers

Smart Wireless Communication to most phones or tablets.





Features:

- · IP67 protected against fluid and dust
- · Wireless connectivity for quick error free data collection
- · Supplied with NIST certification
- · Heavy duty frame with 4-way measuring, inside, outside, depth and step
- · Super large display
- Includes fitted case, extra battery tray and a 1" setting standard

Order No.	Range	Accuracy	List Price	Sale Price
54-100-556-BT	0 - 6"/150mm	0.001"/0.02mm	\$211.24	\$191.00
54-100-512-BT	0 - 12"/300mm	0.0015"/0.04mm	\$259.54	\$234.00

TRA-VALUE Plus Electronic Calipers

IP54 protected with inch/metric/fractions.





- Range: 6"/150mm
- Accuracy: ± 0.001"/0.02mm
- · Inch/Metric/Fraction reading: 0.0005"/0.01mm/ 1/128"
- · Heavy Duty frame for extra rigidity and wear resistance
- · Super large, easy to read display
- · Includes fitted case

Order No.	Range	Accuracy	List Price	Sale Price
54-103-006-0	0 - 6"/150mm	0.001"/0.02mm	\$98.98	\$80.00
54-103-012-0	0 - 12"/300mm	0.0015"/0.03mm	\$149.79	\$128.00



Electronic Calipers

Absolute location retention after shut off.



- Absolute/Incremental Measurement
- · Stainless steel frame
- · Direct Inch/Metric conversion
- 4-way measuring, inside, outside, depth and step
- · Wireless SPC data option
- · Includes fitted case

Order No.	Range	Accuracy	List Price	Sale Price
54-100-004-2	4"/100mm	0.001"/0.02mm	\$143.24	\$122.00
54-100-000-2	6"/150mm	0.001"/0.02mm	\$161.96	\$146.00
54-100-008-2	8"/200mm	0.0015"/0.04mm	\$164.57	\$140.00
54-100-112-2	12"/300mm	0.0015"/0.04mm	\$226.48	\$193.00
Accessories				
54-115-100-0	Wireless transmitte	r	\$119.81	\$114.00



- · Large easy-to-read display
- Resolution: 0.0005"/0.01mm
- · Absolute/Incremental measurement
- · 4-way measuring, inside, outside, depth and step
- 6" and 12" regular display models include NIST Cert.
- · Includes fitted case

Order No.	Range	Accuracy	List Price	Sale Price
54-101-150-2	6"/150mm - Regular Display	0.001"/0.02mm	\$54.93	\$47.00
54-101-600-1	6"/150mm - Large Display with Hold feature	0.0015"/0.04mm	\$75.62	\$65.00
54-101-200-1	8"/200mm - Regular Display	0.0015"/0.04mm	\$102.31	\$87.00
54-101-300-1	12"/300mm - Regular Display	0.0015"/0.04mm	\$125.48	\$107.00
54-101-900-1	12"/300mm - Large Display with Hold feature	0.0015"/0.04mm	\$165.55	\$141.00



XTRA-RANGE Carbon Fiber Electronic Calipers



54-100-140-0

Features:

- · IP65 protected against fluid and dust
- · Lightweight carbon fiber frame
- · Stainless steel jaws with ID nibs
- ID/OD pressure device for repeatability
- USB data output (works with 54-520-399-0)
- · Preset, ABS/INC, Floating zero, IN/MM, Hold function
- Super large display
- · Fitted wooden case



Order No.	Range	Accuracy	Jaw Depth	Weight	List Price	Sale Price
54-100-124-0	0 - 24"/600mm	0.0020"/0.05mm	5.4"/138mm	2.85 lbs.	\$825.00	\$743.00
54-100-140-0	0 - 40"/1000mm	0.0025"/0.06mm	5.4"/138mm	3.45 lbs.	\$1,495.00	\$1,346.00
54-100-160-0	0 - 60"/1500mm	0.0055"/0.13mm	5.9"/150mm	4.4 lbs.	\$1,995.00	\$1,796.00

XTRA-RANGE Electronic Calipers

For large measurements

54-100-312-0

52-008-018-0



Features:

- · IP54 protected against fluid and dust Resolution: 0.0005"/0.01mm
- · Hold feature
- · Absolute/Incremental measurement
- · Preset mode includes offset size for ID measurements
- · Both sizes feature fine adjustment


Order No.	Range	Accuracy	Jaw Depth	List Price	Sale Price
54-100-312-0	0 - 12"/300mm	± 0.002"/0.05mm	3.5"	\$266.68	\$241.00
54-100-024-1	0 - 24"/600mm	± 0.003"/0.075mm	4"	\$412.94	\$372.00

XTRA-RANGE Dial Calipers

With full length depth rod



- Graduations: 0.001"
- Jaw depth: 3.125"
- · Stainless steel construction
- · Satin chrome finish
- · Full length depth rod
- · 0.50" internal measuring nibs on jaws









Features:

- · Tough shockproof gearing with ultra smooth movement
- · 4-way measuring, inside, outside, depth and step
- · Inverted/covered rack
- · Solid stainless steel construction with lapped measuring faces
- 0.100" range per revolution
- 0.001" reading dial

Order No.	Range	Dial Color	Accuracy	List Price	Sale Price
52-008-704-1	0 - 0"	White	± 0.001"	\$90.00	\$77.00
52-008-714-1	0 - 0"	Black	± 0.001"	\$90.00	\$77.00
52-008-706-0	0 - 6"	White	± 0.001"	\$102.74	\$88.00
52-008-707-0	0 - 6"	Black	± 0.001"	\$102.74	\$88.00
52-008-708-0	0 - 8"	White	± 0.0015"	\$123.37	\$105.00
52-008-712-0	0 - 12"	White	± 0.002"	\$165.88	\$141.00
Metric					
52-008-709-0	0 - 150mm	Yellow	± 0.02mm	\$105.93	\$91.00

Dial Calipers



- · 4-way measuring for outside, inside, depths and steps
- · Graduation: 0.001"
- · Hardened stainless steel throughout
- · Covered rack
- · Shockproof gearing

Order No.	Range	Dial Color	Accuracy	List Price	Sale Price
52-008-005-1	0 - 6"	Black	± 0.001"	\$85.00	\$73.00
52-008-007-1	0 - 6"	White	± 0.001"	\$85.00	\$73.00
52-008-008-1	0 - 8"	White	± 0.0015"	\$100.00	\$85.00
52-008-012-1	0 - 12"	White	± 0.002"	\$150.00	\$128.00



Electronic Micrometers Comparison Chart

	Data Output	Wireless	IP Rating	Sizes
RAPID-MIC Micrometers	\checkmark	/	IP67	0 - 4"
DIGI-MIC Micrometers		J	IP67	0 - 1"
Xtra-MIC PLUS Mics.	\checkmark	_	IP54	0 - 4"
Coolant Resistant Mics.	_	_	IP54	0 - 4"
Xtra-Value II Micrometers	_	-	IP40	0 - 4"
			11 40	0 4

Rapid-Mic Quick-Displacement Electronic Micrometers

Fastest micrometer on the market!













Features:

- · IP67 protected against fluid and dust
- Non-rotating spindle with 0.39"/10mm travel per thimble rotation
- Adjustable measuring force, 5N/10N (54-815-030-0 and 54-815-130-0 only)
- · Menu customizable with free software
- Larger sizes and specialty anvil micrometers also available

Calibration certificates available for all sizes.

Order No.	Range	Accuracy	List Price	Sale Price
54-815-030-0	0 - 1.18"/0 - 30mm	0.00012"/0.003mm	\$625.88	\$532.00
54-815-060-0	1.18" - 2.6"/30 - 66mm	0.00016"/0.004mm	\$1,134.49	\$1,022.00
54-815-100-0	2.6" - 4.0"/66 - 102mm	0.00020"/0.005mm	\$1,237.69	\$1,114.00
Set				
54-815-111-0	0 - 4"/0 - 102mm		\$2,851.16	\$2,424.00
Bluetooth Models				
54-815-130-0	0 - 1.18"/0 - 30mm	0.00012"/0.003mm	\$986.19	\$888.00
54-815-160-0	1.18" - 2.6"/30 - 66mm	0.00016"/0.004mm	\$1,311.38	\$1,216.00
54-815-110-0	2.6" - 4.0"/66 - 102mm	0.00020"/0.005mm	\$1,553.60	\$1,259.00
Bluetooth Set				
54-815-112-0	0 - 4"/0 - 102mm		\$3,706.17	\$3,218.00
Connectivity Cables	s/Accessories			
54-981-713-2	Sylcom Basic Data Process	ing Software	\$810.68	\$771.00
54-981-724-5	Sylcom Pro Data Processing	Sylcom Pro Data Processing Software		\$1,843.00
54-115-526-0	Proximity cable with USB connection		\$223.37	\$202.00
54-115-527-0	Proximity cable with serial connection		\$216.29	\$195.00
54-115-246-BT	USB Bluetooth receiver		\$49.45	\$43.00











Calibration certificate available.

· Carbide measuring surfaces, sleep and absolute

List Price \$886.83

XTRA-MIC PLUS Electronic Micrometers

modes



Limited quantities

Features:

- · IP54 protected against fluid and dust
- · Super large LCD display, 14mm height
- Resolution: 0.00005"/0.001mm
- · Carbide tipped anvil and spindle

Order No.	Range	Accuracy	List Price	Sale Price
54-880-001-0	0 - 1"/0 - 25mm	0.00016"/0.004mm	\$152.25	\$115.00
54-880-002-0	1 - 2"/25 - 50mm	0.00016"/0.004mm	\$194.98	\$153.00
54-880-003-0	2 - 3"/50 - 75mm	0.0002"/0.005mm	\$208.44	\$163.00
54-880-004-0	3 - 4"/75 - 100mm	0.0002"/0.005mm	\$239.01	\$162.00
Set				
54-880-103-0	0 - 3"/0 - 75mm		\$538.08	\$384.00

Electronic IP54 Blade Micrometers



- IP54 protected against fluid and dust
- Blades are 0.030" thick x 0.255" long
- Accuracy: 0.00016"
- Resolution: 0.00005"/0.001mm
- Friction thimble

Order No.	Range	List Price	Sale Price
54-860-241-0	0 - 1" Blade Anvil	\$300.90	\$241.00
54-860-242-0	1" - 2" Blade Anvil with standard	\$374.04	\$300.00



Electronic Coolant Resistant Micrometers

For basic outside measurements with higher protection.





- · Carbide measuring faces
- Absolute & incremental modes
- · Ratchet thimble
- · Automatic switch off
- · Free ball attachment included
- · Sizes over 1"/25mm include a calibration standard

Range	Accuracy	List Price	Sale Price
0 - 1"/0 - 25mm	± 0.00016"/0.004mm	\$157.14	\$126.00
1 - 2"/25 - 50mm w/standard	± 0.00016"/0.004mm	\$181.88	\$146.00
2 - 3"/50 - 75mm w/standard	± 0.0002"/0.005mm	\$190.70	\$138.00
3 - 4"/75 - 100mm w/standard	± 0.0002"/0.005mm	\$221.40	\$169.00
0 - 3"/0 - 75mm w/standard		\$516.67	\$414.00
	0 - 1"/0 - 25mm 1 - 2"/25 - 50mm w/standard 2 - 3"/50 - 75mm w/standard 3 - 4"/75 - 100mm w/standard	0 - 1"/0 - 25mm ± 0.00016"/0.004mm 1 - 2"/25 - 50mm w/standard ± 0.00016"/0.004mm 2 - 3"/50 - 75mm w/standard ± 0.0002"/0.005mm 3 - 4"/75 - 100mm w/standard ± 0.0002"/0.005mm	0 - 1"/0 - 25mm

XTRA-VALUE | Electronic Micrometers





- Oarbide measuring races
- · Absolute and incremental modes
- · Ratchet thimble
- · Free ball attachment included
- · Sizes over 1"/25mm include a calibration standard

Order No.	Range	Accuracy	List Price	Sale Price
54-870-001-0	0 - 1"/0 - 25mm	± 0.00016"/0.004mm	\$107.28	\$86.00
54-870-002-0	1" - 2"/25 - 50mm	± 0.00016"/0.004mm	\$115.85	\$93.00
54-870-003-0	2" - 3"/50 - 75mm	± 0.0002"/0.005mm	\$138.56	\$111.00
54-870-004-0	3" - 4"/75 - 100mm	± 0.0002"/0.005mm	\$169.62	\$136.00
Set				
54-870-103-0	0 - 3"/0 - 75mm		\$346.42	\$278.00

Digit Counter Micrometers

0.001" digit counter.



52-224-001-1

Features:

- · Digital counter reads to 0.001"
- Graduations: 0.0001" (using vernier)
- · Microfine graduations on satin chrome
- · Carbide tipped measuring faces
- · Sizes over 1"/25mm include a standard
- Includes case

Order No.	Range	Accuracy	List Price	Sale Price
52-224-001-1	0 - 1"	0.00016"	\$125.49	\$95.00
52-224-002-1	1" - 2"	0.00016"	\$131.81	\$93.00
52-224-003-1	2" - 3"	0.0002"	\$150.12	\$106.00
52-224-004-1	3" - 4"	0.0002"	\$189.08	\$133.00
52-224-005-1	4" - 5"	0.00024"	\$194.27	\$123.00
52-224-006-1	5" - 6"	0.00024"	\$203.08	\$128.00
Sets				
52-224-103-0	0 - 3" set (set fi	nished in grey enamel)	\$396.05	\$278.00
52-224-104-0	0 - 4" set (set fi	nished in grey enamel)	\$561.69	\$394.00
52-224-220-0	0 - 75mm set (s	set finished in grey enamel)	\$463.37	\$292.00

Digit Counter Ball Anvil Micrometers



Features:

- · Microfine graduations on satin chrome
- Digital counter reads to 0.001", sleeve reads to 0.0001"
- · Spindle hardened and precision ground with a carbide tipped measuring face
 - · Ratchet stop thimble
- · Accuracy: 0.00016", Graduation: 0.0001"

Order No.	Range	List Price	Sale Price
52-244-201-1	0 - 1" Ball Anvil	\$135.89	\$96.00
52-244-301-1	1" - 2" Ball Anvil/Ball Spindle	\$164.99	\$116.00

Digit Counter Disc Micrometers



- · Anvil and spindle are hardened and precision ground
- Flatness: 0.00004"
- · Accuracy: 0.00016", Graduation: 0.0001"
- · Disc edge thickness: 0.035", disc dia.: 0.708"
- Ratchet thimble
- The disc type anvil and spindle simplifies measuring the thickness of difficult, closely spaced sections

Order No. 52-250-301-1



List Price \$178.70

Outside Vernier Micrometers

0.0001" graduations for higher accuracy.



52-215-003-1

- · Graduation: 0.0001"
- · Microfine graduations on satin chrome finish and carbide tipped measuring faces
- · Diameter of measuring faces: 0.256"
- Flatness: 0.00003"
- · Spindle thread hardened, ground and lapped for ultimate accuracy
- · Includes a wrench and case
- · Sizes over 1"/25mm include a standard

Order No.	капде	Accuracy	Inimbie	LIST Price	Sale Price
52-240-001-1	0 - 1"	± 0.00016"	Friction	\$45.94	\$40.00
52-240-101-1	0 - 1"	± 0.00016"	Ratchet	\$45.94	\$40.00
52-240-002-1	1" - 2"	± 0.00016"	Friction	\$53.43	\$46.00
52-240-102-1	1" - 2"	± 0.00016"	Ratchet	\$61.14	\$52.00
52-240-003-1	2" - 3"	± 0.0002"	Ratchet	\$62.43	\$54.00
52-240-004-1	3" - 4"	± 0.0002"	Ratchet	\$79.78	\$68.00
52-240-005-1	4" - 5"	± 0.00024"	Ratchet	\$88.36	\$76.00
52-240-006-1	5" - 6"	± 0.00024"	Ratchet	\$96.81	\$83.00
52-240-007-1	6" - 7"	± 0.00028"	Ratchet	\$105.26	\$90.00
52-240-008-1	7" - 8"	± 0.00028"	Ratchet	\$108.25	\$93.00
52-240-009-1	8" - 9"	± 0.00032"	Ratchet	\$123.03	\$105.00
52-240-010-1	9" - 10"	± 0.00032"	Ratchet	\$139.52	\$119.00
52-240-011-1	10" - 11"	± 0.00036"	Ratchet	\$154.30	\$132.00
52-240-012-1	11" - 12"	± 0.00036"	Ratchet	\$193.48	\$165.00
Sets					
52-215-003-1	0 - 3" with st	andards and fitted sh	op hardened case	\$183.19	\$147.00
52-215-004-1	0 - 4" with st	andards and fitted sh	op hardened case	\$262.46	\$224.00
52-215-006-1	0 - 6" with st	andards and fitted sh	op hardened case	\$445.54	\$379.00
52-215-012-1	0 - 12" with s	standards and fitted o	ase	\$1,350.70	\$1,130.00
52-215-612-1	6 - 12" with s	standards and fitted o	ase	\$891.07	\$758.00

Outside Vernier Micrometers


0.001" readings.



· Sizes over 1"/25mm include a standard

Order No.	Range	Accuracy	Thimble	List Price	Sale Price
52-253-001-1	0 - 1"	± 0.001"	Friction	\$38.66	\$33.00
52-253-101-1	0 - 1"	± 0.001"	Ratchet	\$38.66	\$33.00
52-253-002-1	1" - 2"	± 0.001"	Friction	\$52.58	\$45.00
52-253-102-1	1" - 2"	± 0.001"	Ratchet	\$45.94	\$40.00
52-253-003-1	2" - 3"	± 0.001"	Ratchet	\$61.15	\$52.00
52-253-004-1	3" - 4"	± 0.001"	Ratchet	\$62.43	\$54.00
52-253-005-1	4" - 5"	± 0.001"	Ratchet	\$69.71	\$60.00
52-253-006-1	5" - 6"	± 0.001"	Ratchet	\$77.21	\$66.00

Outside Vernier Micrometer Set





- Range: 0 6"
- · Carbide tipped measuring faces
- · Graduation: 0.001"
- · Diameter of measuring faces: 0.256"
- · Anvil & spindle hardened and precision ground with microlap finish on tips
- Sizes over 1" include a standard

Order No. 52-253-600-1



List Price \$354.41

Micrometers

Electronic IP65 Thread Micrometers

For accurate pitch diameter measurements



IP65 protected against fluid and dust

- Thread range: 64 3.5 TPI/0.4 7mm
- Accuracy: ± 0.00008"/0.002mm
- 60° measuring anvils
- · Absolute and incremental measuring mode
- Resolution: 0.00005"/0.001mm
- · Friction thimble

Order No.	Range	Thread Range	Accuracy	List Price	Sale Price
54-219-001-0	0 - 1"/0 - 25mm	64 - 5 TPI/0.4 - 5mm	± 0.00008"/0.002mm	\$289.94	\$261.00
54-219-002-0	1" - 2"/25 - 50mm	44 - 3.5 TPI/0.6 - 7mm	± 0.00008"/0.002mm	\$349.06	\$315.00

Vernier Thread Micrometers



Features:

- 60° measuring anvils
- Graduation: 0.001"
- Ratchet thimble
- · Sizes over 1" include standard

Order No.	Range	Thread Range	Accuracy	List Price	Sale Price
52-219-001-1	0 - 1"	64 - 5 TPI/0.4 - 5mm	0.00016"	\$132.54	\$120.00
52-219-002-1	1" - 2"	44 - 3.5 TPI/0.6 - 7mm	0.00016"	\$127.49	\$115.00

Micrometer Stands



Features:

- Unique locking system adjusts micrometer stand to any position for perfect use and viewing
- Stand folds for storage

XTRA MAG

Features

- Holds standard 0-12" micrometers firmly to metal surfaces
- Use at machine centers, assembly and inspection stations, steel tables and shelves
- V-bottom for mounting on cylindrical surfaces
- · On/Off magnet switch
- Base is 2.30" L x 1.20" W x 3.50" H



Micrometer not included

Order No.	Description	List Price	Sale Price
52-247-005-0	Folding Micrometer Stand	\$48.66	\$40.00
52-247-010-0	Magnetic Micrometer Stand	\$77.48	\$70.00
52-247-010-0	Magnetic Micrometer Stand	φ11.40	\$70.00

Features:

- · IP54 protected against fluid and dust
- Range: 0 6"/150 mm
- Resolution: 0.00005"/0.001mm
- · Base surface hardened and microlapped to 0.00008"
- · Rod diameter: 0.176"
- · Includes fitted case



IP54 Electronic Depth Micrometer

Order No. 54-225-456-0



List Price \$250.55

Digit Counter Depth Micrometers

Features:

- · Easy-to-read digit counter
- Microfine 0.001" graduations
- · Base surface hardened and microlapped to 0.00008" flatness
- · Ratchet thimble
- · Rod diameter: 0.176"
- · Includes wrench and fitted case





Order No.	Range	Graduation	Accuracy	Base Size	List Price	Sale Price
52-225-176-0	0 - 6"	0.001"	0.0002"	2.5"	\$219.24	\$198.00
52-225-226-0	0 - 6"	0.001"	0.0002"	4"	\$243.57	\$208.00

Vernier Depth Micrometers

- · Base surface hardened and microlapped to 0.00008" flatness
- · Ratchet thimble
- Locking clamp
- · Rod diameter: 0.176"
- · Includes fitted case





52-225-110-0

Order No.	Range	Graduation	Accuracy	Base Size	List Price	Sale Price
52-225-110-0	0 - 4"	0.001"	0.0002"	2.5"	\$157.44	\$142.00
52-225-112-0	0 - 6"	0.001"	0.0002"	2.5"	\$201.58	\$182.00
52-225-114-0	0 - 4"	0.001"	0.0002"	4"	\$161.14	\$146.00
52-225-116-0	0 - 6"	0.001"	0.0002"	4"	\$188.55	\$170.00

Electronic Indicators Comparison Chart

	Data Output	Wireless Option	IP Rating	IN/MM/Frac.
MARK VI Indicators	J	√	IP54	_
Mini-S Indicators	\checkmark	✓	IP67	_
Quadra-TEST Indicators	\checkmark	✓	IP65	_
Indi-X BT Indicators	_	√	IP65	_
Indi-X Indicators	_	_	_	√

Mark VI Electronic Indicators

Our BEST electronic indicators!



Features:

- · IP54 protected against fluid and dust
- Output: Proximity/Power USB/RS232/digimatic/Wireless
 Functions (ANN/MAX/PDITA TOLL Footer Procest Auto Company)
- Functions (MIN/MAX/DELTA, TOL, Factor, Preset, Auto Off)
- · Large display with LED tolerance indicators







Calibration certificates available for all sizes.

Order No.	Range	Accuracy	Resolution	List Price	Sale Price
Low Resolution					
54-530-125-0	0 - 0.500"/12.5mm	0.0004"/0.01mm	0.0005"/0.01mm	\$576.32	\$519.00
54-530-145-0 High Resolution	0 - 1"/25mm	0.0004"/0.01mm	0.0005"/0.01mm	\$657.81	\$593.00
54-530-135-0	0 - 0.500"/12.5mm	0.00012"/0.003mm	0.00005"/0.001mm	\$713.10	\$614.00
54-530-155-0	0 - 1"/25mm	0.00016"/0.004mm	0.00005"/0.001mm	\$681.61	\$642.00
54-530-175-0	0 - 2"/50mm	0.00019"/0.005mm	0.00005"/0.001mm	\$1,368.02	\$1,232.00
Bluetooth					
54-530-335-0	0 - 0.500"/12.5mm	0.00012"/0.003mm	0.00005"/0.001mm	\$902.32	\$813.00
54-530-355-0	0 - 1"/25mm	0.00016"/0.004mm	0.00005"/0.001mm	\$841.84	\$758.00
Accessories					
54-981-713-2	Sylcom Basic Data I	\$810.69	\$771.00		
54-981-724-5	Sylcom Pro Digital License \$1.939.95 \$1,843.00				
54-115-246-BT	USB Bluetooth Rece	eiver		\$49.45	\$43.00

NDI-X BT Electronic Indicators

Smart Wireless Communication to most phones and tablets



Features:

- · Bluetooth compatible to most
- phones and tablets
- Resolution 0.00005"/0.001mm
- · Economical bluetooth option
- Includes lifting hook, ceramic ball contact point, 2 specialty contact points (spline and point), NIST cert., lug and flat backs

54-520-285-0

54-520-280-0

Calibration certificates available for all sizes.







54-520-250-0

Features:

- Accuracy: ± 0.001"/0.03mm
- Resolution 0.0005"/0.01mm
- 54-520-260-0 also reads 1/64ths
- 2-1/4" dial face
- · Lugback and 3/8" stem mountings
- Tolerance function
- · Absolute/incremental reading

54-520-692-0

· Floating zero

Calibration certificates available for all sizes.

Order No.	Range	List Price	Sale Price
54-520-255-0	0.50"/12.5mm	\$117.77	\$95.00
54-520-250-0	1"/25mm	\$133.36	\$107.00
54-520-260-0	1"/25mm	\$135.38	\$109.00

Mini S_Dial Indicators

Small in size BIG in features!

Features:

- · Bluetooth connectivity to your phone or tablet
- · IP67 protected against fluid and dust
- · All indicators feature 0.50"/12.5mm range
- Analog scale for reversal point indication, Min/Max, multiplication factor (Bluetooth® models only)
- 3/8" mounting diameter with 4-48 contact thread
- · Auto power off feature

54-520-255-0

· Optional cable connectivity output









Calibration certificates available for all sizes.

Order No.	Accuracy	Resolution	List Price	Sale Price
Bluetooth Models				
54-520-687-BT	0.0004"/0.01mm	0.0005"/0.01mm	\$592.58	\$534.00
54-520-690-BT	0.0002"/0.005mm	0.00005"/0.001mm	\$860.27	\$775.00
Basic Models (Zero	set, preset, in/mm, measu	uring direction)		
54-520-691-0*	0.0004"/0.01mm	0.0005"/0.01mm	\$498.06	\$449.00
54-520-692-0*	0.0002"/0.005mm	0.00005"/0.001mm	\$687.64	\$619.00
Accessories				
54-981-713-2	Sylcom Basic Data Prod	cessing Software	\$810.69	\$771.00
54-115-528-0	USB Power Cable	_	\$323.34	\$292.00

^{*}Bluetooth models feature zero, data, preset, direction, min/max/delta, resolution, multiplication factor

Premium Dial Indicators

Smooth, accurate and built tough.

Features:

- · AGD Group 2 specifications
- Shockproof gearing
- · Jeweled movement
- Tolerance markers
- Solid steel housingCarbide contact point
- Includes NIST Certification









52-520- 1	105-0
------------------	-------

Order No.	Range	Graduation	Reading	Balanced Reading	Dial Color	List Price	Sale Price
52-520-135-0	0.05"	0.0001"	0 - 10	0 - 5 - 0	White	\$205.54	\$155.00
52-520-105-0	0.50"	0.001"	0 - 100	0 - 50 - 0	White	\$105.64	\$72.00
52-520-110-1	1"	0.001"	0 - 100	_	Black	\$100.53	\$76.00
52-520-110-2	1"	0.001"	0 - 100	-	White	\$100.53	\$76.00
52-520-120-0	2"	0.001"	0 - 100	_	White	\$160.28	\$121.00
52-520-125-0	0.250"	0.0005"	0 - 100	-	White	\$147.39	\$100.00
52-520-129-0	1"	0.0005"	0 - 50	0 - 25 - 0	White	\$121.52	\$92.00
52-520-300-0	10mm	0.01mm	0 - 100	0 - 50 - 0	White	\$127.54	\$87.00
52-520-500-0	25mm	0.01mm	0 - 100	0 - 50 - 0	White	\$153.00	\$115.00



Vertical Long Reach Test Indicator

Features:

- 3.077" extra long contact point
- Graduations: 0.001"
- · Jeweled movement
- · Automatic reversal
- · Dovetails on top and bottom of main body
- Includes fitted case





3.077"

Order No. 52-555-022-0





List Price \$374.85

Electronic Test Indicators

Features:

- · Bluetooth connectivity to your phone or tablet
- · IP65 protected against fluid and dust
- · 4 measuring modes: Min, Max, TIR and Direct
- 4 measuring resolutions 0.00005"/0.001mm or 0.0005"/0.01mm
- 1-1/2" diameter dial face rotates a full 360°
- · Analog scale for reversal point indication
- · Meets or exceeds DIN/ISO Standards (Maximum error on 0.00005" scale at full range: 0.0004")
- 54-562-890-BT is capable of interchanging contact point lengths













54-562-777-BT

Calibration certificates available for all sizes.

Order No.	Range	Contact Point Length	List Price	Sale Price
54-562-777-BT	0.030"/0.80mm	1/2"	\$582.41	\$486.00
54-562-888-BT	0.080"/2.0mm	1-7/16"	\$658.71	\$560.00
54-562-890-BT	0.030"/0.80mm 0.080"/2.0mm	1/2" 1-7/16"	\$820.82	\$698.00
Accessories				
54-981-713-2	Sylcom Basic Data Pr	ocessing Software	\$810.68	\$771.00
54-115-528-0	USB Power Cable		\$323.33	\$292.00

X-TEST[®]

Horizontal & Vertical Test Indicators

- · Super smooth jeweled movement
- · Smooth bezel adjustment for easy zero setting
- · Solid brass anti-magnetic housing
- 0.080" and 0.120" carbide ball contact points (0.040" steel ball)
- · 0.060" range with auto reverse and rev. counter











52-562-005-0

52-562-001-0

52-562-002-BD

Order No.	Graduation	Dial Size	Dial Reading	List Price	Sale Price
Horizontal					
52-562-001-0	0.0005"	1-1/2"	0 - 15 - 0	\$143.15	\$122.00
52-562-001-BD	0.0005"	1-1/2"	0 - 15 - 0	\$143.15	\$122.00
52-562-002-BD	0.0005"	1-1/2"	0 - 15 - 0	\$159.05	\$122.00
52-562-003-0	0.001"	1"	0 - 15 - 0	\$163.82	\$140.00
52-562-008-0	0.01mm	38mm	0 - 40 - 0	\$159.41	\$140.00
Vertical					
52-562-004-0	0.0005"	1-1/2"	0 - 15 - 0	\$156.75	\$118.00
52-562-005-0	0.0005"	1"	0 - 15 - 0	\$174.16	\$135.00

S_Depth Gages

Perfect for measuring depths, groove widths, slot widths, recess heights, step heights and through holes.

Features:

- · IP67 protected against fluid and dust
- Bluetooth connectivity to your phone or tablet
- · 3 measuring styles available
- 4"/100mm measuring base as standard

S SV Vac SWISS

- Optional probes available for 54-139-160-0 series
- Extra large display
- Absolute measuring system



Rotary Pin Series 54-139-162-3





Order No.	Description	List Price	Sale Price
54-139-160-1	8"/200mm Interchangeable Anvil Bluetooth Depth Gage	\$1,349.30	\$1,215.00
54-139-160-3	12"/300mm Interchangeable Anvil Bluetooth Depth Gage	\$1,555.30	\$1,400.00
54-139-160-5	19"/500mm Interchangeable Anvil Bluetooth Depth Gage	\$2,080.60	\$1,873.00
54-139-161-1	8"/200mm Standard Style Bluetooth Depth Gage	\$1,240.00	\$1,150.00
54-139-161-3	12"/300mm Standard Style Bluetooth Depth Gage	\$1,410.00	\$1,269.00
54-139-161-5	19"/500mm Standard Style Bluetooth Depth Gage	\$1,780.00	\$1,651.00
54-139-162-1	8"/200mm Rotary Pin Bluetooth Depth Gage	\$1,340.00	\$1,243.00
54-139-162-3	12"/300mm Rotary Pin Bluetooth Depth Gage	\$1,510.00	\$1,400.00
54-139-162-5	19"/500mm Rotary Pin Bluetooth Depth Gage	\$2,111.50	\$1,901.00

X-Dερτη 22°0 - 22" Dial Depth Gage



Features

- 0 1" travel indicator with 4" base
- 0.001" Graduations
- · Rods connect together for full 22" capacity
- · Satin chrome finish
- Includes 2 extra points for small hole applications; one 0.078" dia. x 1" long and one needle point x 1" long

54-139-161-1

54-139-160-5

Order No. 52-125-006-1



List Price \$224.29

X-DEPTH 22 $\{$ 0 - 22" Electronic Depth Gage

Provides rapid electronic measurement of hole depths.



Features:

- 0-1" AGD Group 2
- Resolution: 0.0005"/0.01mm
- 4" base ground and lapped for flatness
- · Rods connect for 22" capacity
- · Includes 2 extra points (spline & needle)
- Tolerance function

Order No. 54-125-777-0



List Price \$349.23

Granite Dial Gage Stand

Sturdy with 0.00005" flatness

Features:

- 6" x 6" x 2" granite base
- Positive lock screw
- · Fine adjustment knob for zero setting
- · Column height is 8"
- · Accepts all lug-back indicators
- · This stand is maintenance free

Order No. 52-580-030-0





Magnetic Bases

Features:

- 9.5" Height and 85 lb. pull
- · Base dimensions are 2" x 2-11/32" x 1-13/16"(50mm x 58.7mm x 46mm)
- · Accepts all AGD dial indicators
- · V-bottom base allows mounting on cylindrical surfaces
- · Mounts test indicators with 1/4" post mount



	52-585-010	
n	List Price	Sale Priee
Base	\$66.08	\$50.00

Order No. Descriptio 52-585-005-0 Magnetic B 52-585-010-0 Magnetic Base wit fine adjustment \$70.98 \$54.00

Hydraulic Arm Magnetic Base

Heavy duty holding power

Features:

- · Adjusts to virtually any position
- · All purpose magnetic base with 180 lbs. of pulling power
- · Fine adjustment
- · Base can be mounted vertically as well as horizontally,
- · V-bottom base allows mounting on cylindrical surfaces



Order No. 52-585-095-0



List Price \$267.42

Clinotronic-S

The Clinotronic-S is a portable precision instrument for measuring inclinations up to ±45°.

The large, backlit, high contrast color display provides excellent readability even under adverse conditions in the workshop or under a machine.

The Clinotronic-S can be connected to an Android™ device, which can then be used as a remote display. This new feature makes the instrument much more versatile and suitable for many applications. It is built on the success of the Clinotronic PLUS, while retaining the features that made it famous, like its reliability and versatility, plus it adds the latest technology:



Features:

- Wireless functionality (APP wylerUNIVERSAL for Android™)
- · Data transmission via USB cable as well
- · User friendly
- · Adjustable to local gravity
- · Improved mechanical accuracy
- Excellent color display with low power consumption



Order No. 54-635-605-0



Clinotronic Plus

The Fowler Wyler Clinotronic Plus is an electronic level with unsurpassed versatility. It is economically priced, uses a specially designed microprocessor and the well-proven Wyler inclination sensor.



Features:

- Range of ± 45°, capacity of 0-360°
- Resolution of 0.01° (selectable)
- Absolute or relative measuring mode selectable by push button
- Seal-tec technology for excellent performance even in difficult environmental conditions
- Interface connection RS-232 is integrated.
 Special purpose cables available
- · No loss of calibration data by power failure
- Response time: value available within 5 seconds
- Repeatability: <.01°
- · Linearity: 3 min. of arc + 1
- · Housing: aluminum hard anodized.
- Dimensions: 4 x 3 x 1"(100 x 75 x 30mm)

Order No. 54-635-601-0



Protractor

The mini-MAG Protractor provides instant 360° digital inclination display of any angle.

Features:

- Accuracy: ± 0.2°
- Resolution: 0.05°
- · Embedded magnets
- · Display automatically inverts
- Dimensions: 2.375" x 1.375" x 2.375"
- Hold feature
- · Battery Life: up to 250 hrs.

for easy reading!





Order No. 54-422-450-1



List Price \$108.05

The mini-MAG II Protractor provides instant 360° digital inclination display of any angle.

Features:

- · On/off, tilt %, light, zero functions
- · Display is backlit for low light areas
- · Embedded magnets with 3.5lb. pull
- · Display automatically inverts
- Measuring range: 360° (4 x 90°)
- Accuracy: ± 0.2°
- Resolution: 0.05°
- Dimensions: 2.375" x 1.375" x 2.375"
- Hold feature

Order No. 54-422-460-0



List Price \$133.60

Digi Level with smart wireless data







Features:

- IP65 protected against fluid and dust
- Large auto inverting display
- Includes a 6" straight edge with beveled edge and 1/32nds graduations
- · Smart wireless available to connect to phone or tablet
- V's on top and bottom for measuring on cylindrical surfaces
- Embedded magnets on bottom base for vertical and horizontal hold
- Accuracy: ± 0.2°
- Resolution: 0.050°

Order No.	Description	List Price	Sale Price
54-422-550-0	Digi-Level PLUS	\$156.88	\$133.00
54-422-550-BT	Digi-Level PLUS with smart wireless	\$177.30	\$151.00





Rules 52-297-006-0

EZ-Read Black Face Rules

- · Hardened stainless steel
- White easy-to-read microfine graduations against a black, non-glare finish

Satin Chrome Rules

- · Tempered steel
- Non-glare
- · Sharp, easy-to-read microfine graduations







4R: 8ths, 16ths, 32nds, 64ths 16R: 32nds, 64ths, 50ths, 100ths

52-330-006-0

Rigid Steel Rules

Order No.	Finish	Size	Reading	List Price	Sale Price
52-330-006-0	Satin Chrome	6"	4R	\$15.58	\$14.00
52-337-006-0	Black	6"	4R	\$12.39	\$11.00
52-330-012-0	Satin Chrome	12"	4R	\$26.60	\$24.00
52-337-012-0	Black	12"	4R	\$23.84	\$22.00
52-350-006-0	Satin Chrome	6"	16R	\$14.34	\$13.00
52-338-006-0	Black	6"	16R	\$15.23	\$14.00
52-350-012-0	Satin Chrome	12"	16R	\$32.70	\$28.00

Flexible Steel Rules

Order No.	Finish	Size	Reading	List Price	Sale Price
52-295-006-0	Satin Chrome	6"	4R	\$12.93	\$12.00
52-297-006-0	Black	6"	4R	\$12.77	\$11.00
52-295-012-0	Satin Chrome	12"	4R	\$26.84	\$25.00
52-297-012-0	Black	12"	4R	\$18.75	\$17.00
52-308-006-0	Black	6"	16R	\$12.41	\$11.00
52-310-006-0	Satin Chrome	6"	16R	\$13.35	\$12.00
52-308-012-0	Black	12"	16R	\$18.75	\$17.00

Metal Etching Pen



A "must" for any tool room and machine shop for general marking purposes, Fowler's metal etching pen is used on copper, copper alloy, stainless steel, hardened steel tools and castings, etc. Use it to initial personal tools. Its low-cost, disposable design offers limitless applications. Overall length is 6-1/4".

Order No. 52-730-005-0



Carbide Super Scriber



· Lightweight · Retractable carbide tip · Knurled grip · Machined aluminum body · Pocket clip

Order No.	Description	Overall Length	List Price	Sale Price
52-500-050-0	Carbide Super Scriber	6.5"	\$37.00	\$34.00
52-500-055-0	Carbide Refill		\$11.76	\$11.00

Combination Squares



Features:

- Blades are chrome plated, fully hardened and tempered
- 4 piece includes: square, protractor and center heads with 12" blade
- · 2 piece includes: square head and 12" blade
- · Square head has level and scriber point
- Double indexed protractor is graduated 180° in both directions
- · Graduated in 8ths, 16ths, 32nds and 64ths

Order No.	Description	List Price	Sale Price
52-370-012-0	4 pc.	\$263.46	\$198.00
52-370-012-0 52-373-012-0	2 pc.	\$169.55	\$198.00 \$136.00




Features:

- Used for checking squares, height gages and other instruments
- Hardened and the ends are lapped to 90° angular accuracy
- 6" cylindrical squares: ± 0.0001"
- 12" cylindrical square: ± 0.00015"

Order No.	Description	List Price	Sale Price
52-750-006-0	6"	\$256.44	\$231.00
52-750-012-0	12"	\$366.22	\$330.00
52-750-000-0		*	

Steel Squares and Sets



Features:

- Made of carbon tool steel, these economy squares have true right angles both inside and outside
- Beams and blades ground and lapped for straightness and parallelism
- Hardened blade
- Beam grooved at inner corner for clearance of burrs and dirt
 - Squareness of blade edge to the working face: $2" \& 3" = \pm 0.0006"$, $4" \& 6" = \pm 0.0008"$, $9" \& 12" = \pm 0.0012"$



Order No.	Description/Size	List Price	Sale Price
52-432-006-0	6" Square ONLY	\$33.36	\$31.00
52-432-009-0	9" Square ONLY	\$67.12	\$61.00
Sets			
52-432-246-0	4 piece Square Set, 2", 3", 4" & 6"	\$105.88	\$96.00
52-432-469-0	4 piece Square Set, 4", 6", 9" & 12"	\$182.18	\$164.00



2 each @:

- Dimensions: 1-1/2" L x 1-1/4" W x 1-1/4" H
- · Work capacity: Approximately 1"

2 each @:

- Dimensions: 2" L x 1-1/2" W x 1-1/2" H
- · Work capacity: 1-1/2"

All feature:

- Surfaces are square and parallel within 0.0005"
- · V-grooves are square and parallel with all surfaces within 0.0005"
- Corresponding dimensions for each pair are alike within 0.0005"

Order No. 52-475-500-0



V-Block Set



Features

- Hardened steel. All sides of V-Blocks precision ground parallel and square within 0.0004"
- Height: 2", Length:, 2-3/4", Width: 2"
- Two clamps, with screw hole at 90 degrees for positive clamping of work, are included
- Clamping capacity= 2"/50m
- V-Blocks are constructed with stepped grooves which allow the clamps to be inserted without protrusion, thus allowing V-Blocks to be used on base, ends or sides
- Matched pair of V-Blocks are perfectly aligned with 90 degree V-grooves ground central and parallel to the sides and bases

Order No. 52-475-555-0



List Price \$317.46

Toolmaker's Vise

Toolmaker's Vise makes precision holding possible for inspection, precision jig boring, milling and grinding



Features:

- Maximum opening: 2.48"
- Dimensions: 6.1" x 1.9" x 2.0"
- Features solid base and front jaw construction
- Parallelism and squareness accuracy: 0.0004"
- Clamping slots on the bottom of the base allow for easily affixing to angle plates, vises, etc.

Order No. 52-466-000-1



List Price \$245.07

1-2-3 & 2-4-6 Blocks

Useful in layout, inspection and grinding work

Features:

- · 23 holes for easy clamping
- Sold in pairs
- · Hardened 56 60 HRC
- · Both styles include 5 threaded holes, 3/8" 16



52-439-246-0

Order No.	Description	Accuracy	List Price	Sale Price
52-439-031-0	1-2-3 Blocks	± 0.0001"/1"	\$46.34	\$38.00
52-439-032-0	1-2-3 Blocks	± 0.0002"/1"	\$96.48	\$80.00
52-439-246-0	2-4-6 Blocks	± 0.0003"/1"	\$176.40	\$142.00

Parallel Sets

2 thicknesses to choose from!

Features:

- 2 each of 1/2", 5/8", 3/4", 7/8", 1", 1-1/8", 1-1/4", 1-3/8", 1-1/2" & 1-5/8" heights
- · Absolute heights are nominal
- Hardness: 50 HRC, 6" length
- 52-437-000-0 paired in height: 0.001"
- 52-437-031-0 paired in height: 0.0001"



escription	Parallelism L	ist Price	Balle Prilee
/8" Parallel Set	± 0.0008"	\$270.99	\$231.00
/32" Parallel Set	± 0.0001"	\$291.81	\$249.00
/	'8" Parallel Set	8" Parallel Set ± 0.0008"	8" Parallel Set ± 0.0008" \$270.99

Angle Blocks



Features:

- Each 12 block set includes 1 thru 5° blocks in 1° increments and 5° through 30° blocks in 5° increments as well as 1/4° & 1/2° blocks
- · Accuracy: ± 2.5 arc minutes
- · Use of the Solid Angle Block simplifies the setting and checking of angles during tooling, production or inspection. This fast, accurate method eliminates time consuming calculations, sine bar and any setup
- · All blocks precision ground
- · All blocks are 3" long and 1/4" thick

Order No. 53-666-000-0



Use the 2D Coaxial Set for accurate component centering and positioning in most machining applications. The dial remains stationary during the rotation of the machine spindle.

Features:

- · Graduations and revolution counter 0.0005"/0.01mm)
- · 3 internal and 3 external feelers; ball dia.: 1/8" (3mm)
- Includes center point feeler and staining arm
 Restraining arm
- Shank: 3/8" dia. x 7/8" long (10mm x 20mm)
- · Measuring range: 0.250" (6mm) axis offset
- · Speed recommended 800 RPM max.
- · Repeatability to within 0.0002" (0.005mm) of true center
- Capacity, depending on feeler is 5/32-12"/4-300mm) internal diameter;
 0-12"/0-300mm external diameter



02 7 10 020 0

Order No.	Description	List Price	Salle Prilee
52-710-025-0	2D Coaxial Set - Inch	\$289.56	\$232.00
52-710-030-0	2D Coaxial Set - Metric	\$279.67	\$238.00

Electronic Edge Finders



- · Six equally spaced light ports provide visibility at any angle
- · Edge finder lights instantly when stylus touches work edge
- Repeatability: 0.0002"
- · Works on any conductive metal

Along with light indication, model #54-575-650-0 emits an audible "beep" at time of contact

Order No.	Stylus	Shank	Audible	List Price	Sale Price
54-575-600-0	0.200"	1/2"	NO	\$45.42	\$41.00
54-575-625-0	0.200"	1/2"	NO	\$141.14	\$128.00
54-575-650-0	0.400"	3/4"	YES	\$163.10	\$147.00

Quill Kit

Digital display for drill presses and milling machines

Features:

- · IP54 protected against fluid and dust
- · Includes quill installation tool kit
- Range: 0 6"/150mm
- Accuracy: ± 0.001"/0.03mm
- Resolution: 0.0005"/0.01mm/1/64"
- · Preset, zero, in/mm, absolute/incremental, on/off functions
- · Stainless steel construction
- · Interchangeable mounting brackets with hardware

Order No. 54-050-100-0



List Price \$189.81



Z-Axis Tool Setter

Features:

- · Supplied with zero reference setting block
- · IP65 protected against fluid and dust
- · Back light turns on when zero reference is achieved
- · 4 magnets embedded into base
- · 2" default setting height
- Steel contact surface with 0.0002" flatness
- Resolution: 0.00005"/0.001mm
- · Repeatability: 0.00015"/0.004mm
- Accuracy: 0.0001"/0.003mm
- Includes a rugged, aluminum fitted case





Order No. 54-188-200-0




List Price \$125.06

HIGH Accuracy Z-Axis Detectors



Features:

- · IP67 protected against fluid and dust
- High accuracy and repeatability, ± 0.000039"/0.001mm
- Carbide touch surface (0.196"/5mm)
 High precision bearing guide system for
- · High precision bearing guide system for long life
- · Interchangeable magnetic base
- High visibility LED indicator
- Movement stroke 0.078"/2mm
- · Battery life approximately 250 hours (on time)



Order No.	Model	Dimensions	List Price	Sale Price
54-188-150-0	Inch	Height: 2"/50.8mm, Dia. 0.97"/24.638mm	\$268.63	\$242.00
54-188-140-0	Metric	Height: 1.57"/40mm, Dia. 0.78"/20mm	\$307.43	\$277.00

QUICK CHECK Multi-Function Check Standard



Check

- **Height Gages**
- **Micrometers** √ Depth Gages
- √ Bore Gages
- √ Test & Dial Indicators
- **Caliper Gages**
- Protractors & more
- · All sizes marked are actual
- Accuracy of indicated values ± 0.00012"
- · One compact, multi-function, precise standard
- · Can be used to check and verify a multitude of measuring instruments
- · Supplied with a manufacturer's test certificate and fitted wood case

Order No. 53-813-015-0



List Price \$1,827.00

SHOP-BLOX[®] **Rectangular Gage Block Sets**



Features:

- Manufactured to meet Federal Specification ASME B89. 1.9 - 2002 tolerances on length for inch gage blocks
- Certificate of Calibration traceable to NIST
- Tolerances to ± 0.00005"
- · In high-quality fitted wood case

Order No.	Description	List Price	Salle Prilee
53-672-036-0	36 pc.	\$358.63	\$269.00
53-672-081-0	81 pc.	\$613.39	\$461.00

Grade Ø Rectangular Steel Gage Block Set



53-670-038-0

Features:

- · Grade Ø, 36 piece
- · Certificate of Calibration traceable to N.I.S.T.
- · Each block is individually serialized
- Sizes clearly marked on each block
- · Complete with fitted wooden case

Order No. 53-670-038-0



List \$529.13

Tool Set 300 Presetter

Used for the quick checking of heights and diameters (radii) of various types of machine tools. Accuracy is guaranteed by a precise steel measuring column and displacement devices in X and Z coordinates utilizing constant measuring force.

Tool Holding Spindle

Tool presetter is supplied with high precision tool pot (Grade 0)

- · ISO 50 taper
- · Less than 0.00008"/0.002mm concentricity error

Features:

- Measuring range: (X)11.8"/300mm, (Z)15.7"/400mm
- · Min/Max functions for TIR readings
- · 2 reference indications
- · Preset and Tolerance value inputs
- · Radius or diameter indication on X-axis display
- Resolution: 0.00005"/0.001mm
- · Floating zero function anywhere within axis range
- · Carbide measuring insert for durability · Counter balanced measuring carriage
- · Constant measuring force in both axes
- · High precision Swiss measuring system



Order No.	Description	List Price	Sale Price
54-188-300-0	Tool Presetter	\$10,800.87	\$9,721.00
54-121-005-0	ISO 50/40 Tool Pot Adapter	\$751.82	\$715.00



Portable Roughness Tester II

Quick, easy roughness testing

The X-Pro Portable Roughness Tester II can be used for various applications by selecting from a variety of accessories including special application probes and a swivel stand.

RS232 data output is available on additional models (contact the Fowler technical department for more information 1-800-788-2353)



(X-Pro shown with optional stand with swivel)

X-Pro Portable Roughness Tester II

Features:

- Small, compact size
- 2 selectable parameters: Ra and Rz
- Large LCD display
- · Meets ISO and DIN standards
- NIST traceable specimen included
- · Uses 9 volt battery (approx. 3000 measurements)

Includes fitted case

Order No.	Description	List Price	Salle Prilee
54-410-500-0	Portable Surface Roughness Tester 0.0004" probe (NIST specifications)	\$2,039.35	\$1,836.00
54-410-600-0	Portable Surface Roughness Tester 0.0002" probe (DIN specifications)	\$2,039.35	\$1,836.00

X-Pro Portable Roughness Tester II Stand with Swivel

Order No.	Description	List Price	Sale Price
54-400-896-0	Stand with Swivel Attachment	\$491.18	\$443.00



Headquarters

sales@fowlerprecision.com • www.fowlerprecision.com 780 Dedham Street • Canton • Massachusetts 02021 (800) 788-2353 · (617) 332-4137 fax

Distribution Center & Showroom

Valencia, California 91355 28010 Industry Drive (415) 633-5354

Find us on social media





