

Poly Guard Liquid®

Scale & Rust Preventer



Prevents Scale, Corrosion and Rust Staining.

Pro Poly Guard Scale & Rust Preventer (Liquid) is specifically formulated to prevent hard water scale and iron staining in commercial, industrial and residential potable water applications. Poly Guard forms a protective coating on metal and plastic surfaces preventing scale, corrosion and copper leaching. The Poly Guard formula has the unique ability to sequester iron and manganese to reduce or eliminate iron staining in potable water, irrigation systems and other areas where unsightly iron staining is to be prevented.

Applications

Inject Poly Guard by chemical feed pump into the raw water system as close to the source as possible. Poly Guard is normally fed at a rate of 1 GAL per 200,000 gallons of water (2.5 ppm of phosphate). In case of above-normal iron and corrosion, increase feed rate to 1 GAL per 100,000 gallons of water (5 ppm). Contact your local Poly Guard distributor or visit www.proproducts.com for more details and dosage information.



Benefits to the User	Technical Information	Part #	Size	Qty.
<ul style="list-style-type: none"> Cleans & Maintains Water Using Appliances Restores Pressure in Scale Clogged Pipes Prevents Iron and Manganese stains on appliances and plumbing fixtures 	<ul style="list-style-type: none"> This product is NSF Certified to meet NSF/ANSI Standard 60 for drinking water additives Maximum use level for potable water: 30mg/L Compatible with most chemical feed pumps, follow manufacturer's procedures for injection 	GL41N	1 Gal.	4
		GL05N	5 Gal.	1
		GL55N	55 Gal.	1



Certified to
NSF/ANSI 60