

RELAY GEO

GEO	XS XS PNW	SM SM PNW	MD MD PNW	L L PNW	XL XL PNW	XXL XXLPNW
A. Reach	410 405	430 422	460 452	485 477	510 502	535 527
B. Stack (Carbon)	590 588	615 615	628 634	637 643	646 652	655 661
Stack (Alloy)	595 593	620 620	628 634	637 643	646 652	655 661
C. Effective TT Length	523 532	553 564	586 597	614 631	642 665	671 696
D. Seat Tube Length (Carbon)	380	390	410	430	460	490
Seat Tube Length (Alloy)	410	410	410	430	460	490
E. Effective ST Angle	79.7 79.3	79.1 78.4	78.4 77.7	77.8 77.1	77.3 76.6	77.0 76.3
F. Reference Seat Height	560	600	660	720	780	820
G. Actual ST Angle	71 70.6	71 70.3	71 70.3	71 70.3	71 70.3	71 70.4
ST Offset At BB	90	90	90	90	90	90
H. Head Tube Length (Carbon)	100	100	115	125	135	145
Head Tube Length (Alloy)	105	105	115	125	135	145
I. Head Tube Angle	64.0 63.6	64.0 63.3	64.0 63.3	64.0 63.3	64.0 63.4	64.0 63.4
J. Chainstay Length	436	442 440	442 440	448 446	448 446	448 446
K. Wheelbase	1167 1172	1208 1211	1244 1247	1280 1282	1309 1312	1338 1341
L. Bottom Bracket Drop	15 11	25	25	25	25	25
M. Estimated BB Height	340 343	350	350	350	350	350

