



MAXAM MS406

E4/L4

Deep E4/L4 lug pattern combines excellent traction and high resistance to wear and cutting. Specifically designed to maximize traction in loader applications and provide the lowest cost-per-hour.

- Excellent traction in all off-road conditions
- Deep undertread for improved puncture resistance
- High quality casing allows for excellent retreadability
- Wear and cut resistant tread compound
- Wide, flat footprint profile for maximum stability and wear

Applications:



| Size | Rating | Type | Rim | O.D. | S.W. | T.D. | Infl. P. | L.C.C. (lbs/kg) | Infl. P. | L.C.C. (lbs/kg) | L.I. |
|----------|--------|------|-----------|----------|----------|-------------|------------|--------------------|------------|--------------------|------------|
| | | | | in mm | in mm | 32nds mm | psi KPa | 5 mph 10 kph | psi KPa | 30 mph 50 kph | |
| 23.5R25 | ★★ | TL | 19.50/2.5 | 65.0 | 24.1 | 66 | 94 | 32000 | 76 | 20400 | 201A2/185B |
| | | | | 1651 | 610 | 52 | 650 | 14500 | 525 | 9250 | |
| 26.5R25 | ★★ | TL | 22.00/3.0 | 69.2 | 26.8 | 71 | 94 | 40800 | 76 | 25400 | 209A2/193B |
| | | | | 1757 | 680 | 56 | 650 | 18500 | 525 | 11500 | |
| 29.5R25 | ★★ | TL | 25.00/3.5 | 74.8 | 30.3 | 76 | 94 | 49400 | 76 | 30900 | 216A2/200B |
| | | | | 1900 | 770 | 60 | 650 | 22400 | 525 | 14000 | |
| 29.5R29 | ★★ | TL | 25.00/3.5 | 78.9 | 30.2 | 76 | 94 | 52000 | 76 | 33100 | 218A2/202B |
| | | | | 2005 | 766 | 60 | 650 | 23600 | 525 | 15000 | |
| 35/65R33 | ★★ | TL | 28.00/3.5 | 81.3 | 34.5 | 83 | 94 | 61500 | 76 | 38600 | 224A2/207B |
| | | | | 2066 | 877 | 66 | 650 | 28000 | 525 | 17500 | |
| 35/65R33 | ★★★★ | TL | 28.00/3.5 | 81.3 | 34.5 | 83 | 116 | 64000 | | | 225A8 |
| | | | | 2066 | 877 | 66 | 800 | 29000 | | | |

