SOLIDEAL AIR 561 by camso



GROUND SUPPORT EQUIPMENT




PERFECT SOLUTION FOR GROUND SUPPORT EQUIPMENT

Especially designed for ground support equipment, this tire delivers great life on high temperature apron surfaces while ensuring low rolling resistance and increased traction.

BoltzEquipmentParts.com Jacksonville, Florida USA Phone: +1 904-232-4448 Email: sales@boltzequipmentparts.com

PERFORMANCE





Solideal Air 561 **BY CAMSO**

TIRE SIZE	PR	TUBE* & VALVE**	FLAP	RIM SIZE ⁽¹⁾	
				Recommended	Alternative
6.00 - 9	10	JS2	125 - 9	4.00 E	-
6.50 - 10	10	JS2	140 - 10	5.00 F	5.50 F
7.00 - 12	14	TR75A	135 - 12	5.00 S	-
7.00 - 15	14	TR75A	180 - 15	5.50	5.00
8.00 - 16.5	10	TBLS	-	6.75	-
8.75 - 16.5	10	TBLS	-	6.75	6.00



- tire/rim combination particularly with regard to rim profile and wheel strength.
- (2) The speeds quoted in the table are the maximum speeds of the unloaded vehicle. An increase in load capacity for lower speeds is not permitted. Loads apply to cyclic service applications. Cyclic service means applications where tire are not used continuously at the load indicated by its Load Index and Speed Symbol. It does not refer to the length of time a vehicle is in use. but rather that there is a variation in load and/or speed.
- * Tube size is identical to tire size
- ** Table shows standard valves. Other valves on request.

NHS - Not for Highway Service: Tires primarily designed for use outside of public roads, but suitable for temporary/incidental use on public roads.

All tires come with tube and flap.

It is possible that certain items are not sold in your region.

Please contact your local sales contact to check tire availability in your region.

