

QUALITY ATTACHMENTS!

STRAIGHT BLADE SPECIFICATIONS

The Loegering Trip-Edge Plow features all the tough, reliable characteristics you need. Reinforced diagonal braces make it stronger, quick and reliable hydraulics make it productive!



Plowing Width (At full 30 degree angle)	83"	93-1/2"
Moldboard Width	96"	108"
Moldboard Heights	30-1/4"	30-1/4"
Moldboard Thickness	11 gauge	11 gauge
Reinforcements	6 Vertical 2 Diagonal	8 Vertical 2 Diagonal
Number of Trip Springs	4	4
Angle Cylinders	1-1/2" rod 10" Stroke	1-1/2" rod 10" Stroke
Plow Weights	790 lbs.	830 lbs.
Powder Coat Paint	x	x
2 Cast Iron Shoes	x	x
All Hydraulic Operation	x	x

- ✿ **Universal mounting system.**
- ✿ **The push frame is twice as thick as competitors.**
- ✿ **Mechanical positive-stop cylinders prevent bottoming out.**

ELIMINATOR®

RUGGED DESIGN FOR ANY JOBSITE.

The Eliminator rake is simple to operate and eliminates hours of manual labor. Go from an uncleared lot to a finished seed bed with one attachment. Increased visibility allows you to place soil within inches of sidewalks, buildings and landscaping.

- ✿ **Universal mounting system.**
- ✿ **Scarifying teeth break up hard soils.**
- ✿ **Grading teeth level soil in both forward and reverse.**
- ✿ **Perfect for leveling in tight areas.**
- ✿ **Remove shrubs and heavy vegetation in record time.**

Now available in three sizes: 42" (1,066.8mm)
72" (1,828.8mm)
84" (2,133.6mm)



MAKE TRACKS



www.loegering.com

QUALITY ATTACHMENTS!

MUD BUCKET®



The Mud Bucket saves time by hauling a full 1/2 yard of concrete, 0.3823 m³ based on loader capacity, quickly and effortlessly to where you need it. It saves money by decreasing the number of costly labor hours spent using a wheelbarrow. Work in tight areas efficiently and more cost effectively with the Mud Bucket.

- ✿ **Universal mounting system.**
- ✿ **Perfect for hauling and placing materials in tight areas.**
- ✿ **Haul concrete or any easily flowable material with confidence.**
- ✿ **Hydraulically operated gate allows easy operation from the cab.**
- ✿ **Extension chute increases reach 32" and reduces to 9" wide for accurate placement.**

PALLET FORK

In your busy day you need a reliable extension of your compact loader to make you more productive. Designed with the operator in mind, these pallet forks feature recessed forks to prevent damage and maintain load stability, as well as a rugged guard plate with increased visibility. In addition to safety, Loegering's pallet forks feature an easily accessible entry step engineered to clear most standard pick-up boxes decreasing the opportunity for damage.



SPECIFICATIONS

Part Number

	PF42	PF42HD	PF48	PF48HD
Frame Width	46.5in.	54.5in.	46.5in.	54.5in.
Overall Width	57in.	65in.	57in.	65in.
Frame Height	36in.	36in.	36in.	36in.
Overall Height	39.5in.	39.5in.	39.5in.	39.5in.
Tine Length	42in.	42in.	48in.	48in.
Tine Thickness	1.375in.	1.75in.	1.375in.	1.75in.
Tine Width	4in.	4in.	4in.	4in.
Frame Weight	205lbs.	254lbs.	205lbs.	254lbs.
Total Weight	400lbs.	485lbs.	420lbs.	500lbs.
Load Rating Capacity	3,900lbs. at 24in.	6,200lbs. at 24in.	3,900lbs. at 24in.	6,200lbs. at 24in.

INCREASE PRODUCTIVITY



FACTORY AUTHORIZED DISTRIBUTOR:

BOLTZ EQUIPMENT, INC.
 JACKSONVILLE, FLORIDA USA
 TOLL FREE USA/CANADA: +1 (888) 955-9779
 INTERNATIONAL DIRECT: +1 (904) 232-4448
 EMAIL: SALES@BOLTZEQUIPMENT.COM
 WEB: BOLTZEQUIPMENTPARTS.COM