

All-steel radial industrial tires designed for heavy loads and long cycle times in port and marina applications. Belt-stabilized tread provides better traction, longer tread life and lower heat buildup than bias construction tires.

- ▶ Belt-stabilized tread provides better traction and wear performance
- ▶ Extra-wide profile and reinforced sidewall for improved stability
- ▶ Tread pattern designed to maximize tread life
- ▶ Cut and wear-resistant compound
- ▶ High-quality casing allows for excellent retreadability



TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS



SIZE	RATING	TYPE	RIM	O.D.		S.W.		T.D.		INFLATION PRESSURE psi/KPa	L.C.C. (LBS/KG) 15 mph/25 kph	L.I.
				in	mm	in	mm	32nds	mm			
10.00R20	★★★	TT	7.50	41.9	1064	11.2	285	44	35	145/1000	15210/6890	166A5
12.00R20	★★★	TT	8.50	44.8	1138	12.0	305	52	41	145/1000	20410/9230	176A5
12.00R24	★★★	TT	8.50	49.4	1255	12.5	317	52	41	145/1000	21450/9750	178A5
14.00R24	★★★	TT	10.00W	55.6	1411	15.0	382	79	63	145/1000	33020/14950	193A5
14.00R24	★★★	TL	10.00W	55.6	1411	15.0	382	79	63	145/1000	33020/14950	193A5
14.00R25	★★★	TL	10.00/1.5	55.6	1411	15.0	382	79	63	145/1000	33020/14950	193A5
18.00R25	★★★	TL	13.00/2.5	64.8	1645	19.7	500	81	64	145/1000	50180/22750	207A5

* Load ratings for counterbalanced industrial cyclic application. Please contact a MAXAM representative for other applications.