



**MAXAM**  
NORTH AMERICA

# MS401

**E4**

Designed for rigid haul trucks operating in low traction applications with high work cycles.

- Excellent traction in all off-road conditions
- Deep tread grooves provide cooler running tread for high site TKPH
- Wide square footprint distributes load to minimize haul road disturbance
- Reinforced bead, shoulder, and sidewall for increased cut resistance
- Heat resistant undertread reduces tire temperature
- Multiple tread compound options target specific site requirements

Applications:



Size	Rating	Type	Rim	O.D.	S.W	T.D.	Infl. P.	Tread Compound	TMPH	L.C.C. (lbs)	L.I.
				in	in	32nds	psi			30 mph	
12.00R24	***	TT / TL	8.50V	49.3	12.0	40	102	Standard	---	9350	158B
14.00R24	***	TT	10.00W	55.1	15.6	46	102	Standard	82	12800	169B
								Cut Resistant	62		
14.00R25	***	TT / TL	10.00/1.5	55.1	15.6	46	102	Standard	82	12800	169B
								Cut Resistant	62		
18.00R33	**	TL	13.00/2.5	73.6	20.3	66	94	Standard	169	24000	191B
								Cut Resistant	136		
21.00R33	**	TL	15.00/3.0	78.0	21.8	77	94	Standard	---	30900	200B
								Cut Resistant	---		
21.00R35	**	TL	15.00/3.0	80.7	23.2	74	94	Standard	225	32000	201B
								Cut Resistant	182		
24.00R35	**	TL	17.00/3.5	85.4	26.2	83	94	Standard	286	40800	209B
								Cut Resistant	232		
27.00R49	**	TL	19.50/4.0	106.7	28.9	88	94	Standard	319	60000	223B
								Cut Resistant	257		
								Heat Resistant	429		

