



High performance three-stage solid resilient tire featuring a full-size tread profile for excellent traction, stability, and tire life. Produced with EcoPoint³ rubber compounding technology, providing exceptional resistance to wear and chunking, as well as minimal rolling resistance.

- ▶ Unique tread for an optimal combination of traction and tread life
- ▶ Smooth centerline design provides smooth ride, enhanced steering, and prevents chunking in aggressive applications
- ▶ Incorporates a superior center compound with unmatched heat resistance and shock absorption for the most demanding industrial applications
- ▶ Widest footprint in its class for maximum lifting capabilities



TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS



| SIZE | RIM | TYPE | | | | O.D. | | S.W. | | L.C.C. (LBS/KG) 15 MPH/25 KPH | |
|------------|--------|------|----|------|------|------|-----|------|-----|-------------------------------|--------------|
| | | ST | SW | STNM | SWNM | in | mm | in | mm | LOAD WHEELS | STEER WHEELS |
| 15x4.5-8 | 3.00D | * | * | * | * | 15.0 | 381 | 4.5 | 114 | 2295/1040 | 1765/800 |
| | 3.25I | * | * | * | * | 15.0 | 381 | 4.5 | 114 | 2295/1040 | 1765/800 |
| 16x6-8 | 4.33R | * | * | * | * | 16.3 | 415 | 6.0 | 154 | 3210/1455 | 2470/1120 |
| 18x7-8 | 4.33R | * | * | * | * | 18.1 | 461 | 6.1 | 156 | 4730/2145 | 3640/1650 |
| 5.00-8 | 3.00D | * | * | * | * | 18.1 | 461 | 4.8 | 122 | 3120/1415 | 2405/1090 |
| 140/55-9 | 4.00E | * | * | * | * | 15.0 | 381 | 5.1 | 129 | 2580/1170 | 1985/900 |
| 6.00-9 | 4.00E | * | * | * | * | 20.9 | 531 | 5.5 | 141 | 4155/1885 | 3200/1450 |
| 21x8-9 | 6.00E | * | * | * | * | 20.5 | 520 | 7.4 | 187 | 6075/2755 | 4675/2120 |
| 6.50-10 | 5.00F | * | * | * | * | 22.7 | 576 | 6.6 | 166 | 5160/2340 | 3970/1800 |
| 23x9-10 | 6.50F | * | * | * | * | 23.2 | 589 | 8.0 | 202 | 7595/3445 | 5840/2650 |
| 200/50-10 | 6.50F | * | * | * | * | 18.1 | 461 | 7.7 | 195 | 5445/2470 | 4190/1900 |
| 7.00-12 | 5.00S | * | * | * | * | 25.8 | 655 | 6.8 | 172 | 6440/2920 | 4940/2240 |
| 23x10-12 | 8.00G | * | * | * | * | 23.2 | 589 | 9.3 | 236 | 8310/3770 | 6395/2900 |
| 27x10-12 | 8.00G | * | * | * | * | 26.8 | 681 | 9.7 | 247 | 8600/3900 | 6610/3000 |
| 315/45-12 | 10.00G | * | * | * | * | 23.0 | 584 | 11.2 | 284 | 9890/4485 | 7605/3450 |
| 7.00-15 | 5.50 | * | * | * | * | 29.0 | 737 | 7.2 | 182 | 7815/3545 | 6010/2725 |
| | 6.00 | * | * | * | * | 29.0 | 737 | 7.2 | 182 | 7815/3545 | 6010/2725 |
| 8.25-15 | 6.50 | * | * | * | * | 32.2 | 819 | 8.4 | 212 | 10470/4750 | 8050/3650 |
| 28x9-15 | 7.00 | * | * | * | * | 27.4 | 696 | 8.6 | 218 | 8600/3900 | 6615/3000 |
| 28x12.5-15 | 9.75 | * | * | * | * | 28.2 | 717 | 11.3 | 287 | 12180/5525 | 9370/4250 |



TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS



| SIZE | RIM | TYPE | | | | O.D. | | S.W. | | L.C.C. (LBS/KG) 15 MPH / 25 KPH | |
|-----------|-------|------|----|------|------|------|-------|------|-------|---------------------------------|--------------|
| | | ST | SW | STNM | SWNM | in | mm | in | mm | LOAD WHEELS | STEER WHEELS |
| 250-15 | 7.00 | * | * | * | * | 28.3 | 719 | 8.8 | 223 | 10470/4750 | 8045/3650 |
| | 7.50 | * | * | * | * | 28.3 | 719 | 8.8 | 223 | 10470/4750 | 8045/3650 |
| 300-15 | 8.00 | * | * | * | * | 32.2 | 819 | 10.1 | 256 | 12895/5850 | 9920/4500 |
| 355/65-15 | 9.75 | * | * | * | * | 32.2 | 819 | 12.3 | 313 | 17195/7800 | 13230/6000 |
| 400/60-15 | 11.00 | * | * | * | * | 32.4 | 822.3 | 13.0 | 331.4 | 19775/8970 | 15210/6900 |
| 10.00-20 | 7.00 | * | | * | | 40.7 | 1034 | 9.8 | 250 | 13230/6000 | 11025/5000 |
| | 7.50 | * | | * | | 40.7 | 1034 | 9.8 | 250 | 13230/6000 | 11025/5000 |
| | 8.00 | * | | * | | 40.7 | 1034 | 9.8 | 250 | 13230/6000 | 11025/5000 |
| 12.00-20 | 8.00 | * | | * | | 43.2 | 1098 | 11.1 | 282 | 16660/7560 | 13890/6300 |
| | 8.50 | * | | * | | 43.2 | 1098 | 11.1 | 282 | 16660/7560 | 13890/6300 |
| | 10.00 | * | | * | | 43.2 | 1098 | 11.1 | 282 | 16660/7560 | 13890/6300 |
| 12.00-24 | 8.50 | * | | | | 47.4 | 1203 | 11.8 | 299 | 17720/8040 | 14770/6700 |
| | 10.00 | * | | | | 47.4 | 1203 | 11.8 | 299 | 17720/8040 | 14770/6700 |
| 14.00-24 | 10.00 | * | | | | 52.4 | 1331 | 12.9 | 328 | 24470/11100 | 20390/9250 |
| 14.00-25 | 10.00 | * | | | | 52.4 | 1331 | 12.9 | 328 | 24470/11100 | 20390/9250 |
| | 11.25 | * | | | | 52.4 | 1331 | 12.9 | 328 | 24470/11100 | 20390/9250 |
| 16.00-25 | 11.25 | * | | | | 57.3 | 1456 | 16.1 | 408 | 35880/16250 | 27600/12500 |
| 18.00-25 | 13.00 | * | | | | 64.0 | 1625 | 18.5 | 471 | 50180/22750 | 38600/17500 |

