



MAXAM
NORTH AMERICA

MS701

INDUSTRIAL PRO

Applications:



Premium 3-stage solid resilient tire

- Premium natural rubber compounds:
 - Compounds do not contain crumb rubber or other fill materials
 - Cut and Tear resistant tread
 - Chunk Resistant, Non-Marking (NM)
 - Soft, heat resistant cushion center
 - Pure rubber base compound
- Premium 3-Stage compound construction
 - Evenly layered compound uniformity
 - Internal steel ring reinforcement eliminates wheel slip
- Product conforms to TRA and ETRTO global design standards
- Wide footprint for maximum lifting stability
- Full tread profile for uniform load distribution
- Deep tread configuration for superior traction
- Available in both Standard, and Swift (Clip/Halo/LOC) bead set configuration

Size	R.I.M	Type		O.D. in	S.W. in	T.D. in	L.C.C. (lbs)	
		Std.	Swift				6 mph	10 mph
15x4.1/2-8	3.00D	*	*	14.8	4.5	1.1	1975	1430
	3.25I	*	*	14.8	4.5	1.1	2170	1570
4.00-8	3.00D	*	*	16.1	4.1	1.4	2320	1685
5.00-8	3.00D	*	*	17.7	4.8	1.4	2670	1935
16x6-8	4.33R	*	*	16.2	5.9	1.2	3170	2300
18x7-8	4.33R	*	*	17.9	6.2	1.5	4010	2905
18x9-8 SM	7.00	*	*	18.1	8.4	1.6	6030	3900
140/55-9	4.00E	*	*	14.9	5.1	1.1	2330	1685
6.00-9	4.00E	*	*	20.6	5.4	1.7	4230	3065
21x8-9	6.00E	*	*	20.4	7.4	2.0	6190	4480
200/50-10	6.50F	*	*	18.1	7.5	1.6	5220	3780
6.50-10	5.00F	*	*	22.3	6.4	2.0	5810	4210
23x9-10	6.50F	*	*	23.0	8.0	2.2	7525	5450
23x10-12	8.00G	*	*	23.0	9.2	2.2	8820	6385
7.00-12	5.00S	*	*	25.7	6.8	2.2	6640	4810
27x10-12	8.00G	*	*	26.8	9.8	2.2	10680	7735
315/45-12	10.00G	*	*	22.5	11.1	2.2	9200	6665
28x9-15 (8.15-15)	7.00	*	*	27.0	8.6	2.0	9000	6520
28x12.5-15	9.75	*	*	28.1	11.3	2.2	13320	9650
7.00-15	5.50	*	*	28.7	7.0	2.2	7905	5705
7.50-15	6.50	*	*	29.6	7.8	2.3	9600	6900
250-15	7.00	*	*	28.2	8.9	2.1	9615	6960
	7.50	*	*	28.2	8.9	2.1	10300	7460
8.25-15	6.50	*	*	32.0	8.3	2.8	10875	7875
300-15	8.00	*	*	32.1	10.1	2.6	13190	9550
355/65-15 (350-15)	9.75	*	*	32.2	12.3	3.5	15745	11405
400/60-15	11.00	*	*	32.4	13.1	3.3	19735	15180
355/50-20	10.00	*	*	33.3	12.7	2.6	19835	14360
9.00-20	6.50	*	*	38.7	9.3	2.9	13200	9560
	7.00	*	*	38.7	9.3	2.9	13385	9700
7.50	*	*	38.7	9.3	2.9	15235	11030	
	7.00	*	*	40.7	10.0	3.2	14890	10780
10.00-20	7.50	*	*	40.7	10.0	3.2	15755	11410
	8.00	*	*	40.7	10.0	3.2	17015	12320
10.00-20 SM	7.50	*	*	40.7	10.0	3.2	15755	11405
	8.00	*	*	40.7	10.0	3.2	17015	12320
12.00-20	8.00	*	*	42.8	11.3	3.4	18605	13475
	8.50	*	*	42.8	11.3	3.4	19765	14320
10.00	*	*	42.8	11.3	3.4	23255	16840	

