



**MAXAM**  
NORTH AMERICA

# MS702

## INDUSTRIAL STR

Premium 2-stage solid resilient tire.

- Premium natural rubber compounds: Compounds do not contain crumb rubber or other fill materials
- Cut and Tear resistant tread
- Chunk Resistant, Non-Marking (NM)
- Premium nylon reinforced base compound
- 2-Stage compound construction with steel torque rings
- Excellent stability
- Deep tread configuration for superior traction
- Available in both Standard, and Swift (Clip/Halo/LOC) bead set configuration



Size	Rim	Type		O.D. in	S.W. in	T.D. in	L.C.C. (lbs)	
		Std.	Swift				6 mph	10 mph
100/80-8 SM	2.50C	*		14.3	4.3	0.9	1560	1200
15x4.5-8	3.00D	*	*	14.7	4.2	1.1	1975	1430
	3.25I	*		14.7	4.2	1.1	1975	1430
15x4.5-8 RIB	2.50C	*		14.7	4.2	1.1	1975	1430
	3.00D	*	*	14.7	4.2	1.1	1975	1430
400-8	3.00D	*	*	15.8	3.8	1.4	2320	1685
400-8 RIB	3.00D	*	*	15.8	3.8	1.4	2320	1685
5.00-8	3.00D	*	*	17.7	4.5	1.4	2670	1935
16x6-8	4.33R	*	*	16.1	5.5	1.2	3170	2300
18x7-8	4.33R	*	*	17.6	5.7	1.5	4010	2905
140/55-9	4.00E	*	*	14.6	4.8	1.1	2330	1685
6.00-9	4.00E	*	*	20.5	5.2	1.6	4230	3065
6.00-9 RIB	4.00E	*	*	20.5	5.2	1.6	4230	3065
21x8-9	6.00E	*	*	20.2	7.0	2.0	6190	4480
200/50-10	6.50F	*	*	17.8	7.2	1.6	7510	5445
6.50-10	5.00F	*	*	22.3	6.0	2.0	5810	4210
23x9-10	6.50F	*	*	22.7	7.4	2.2	7525	5450
7.00-12	5.00S	*	*	25.4	6.4	2.1	6640	4810
27x10-12	8.00G	*	*	26.4	9.3	2.2	10680	7735
28x9-15 (8.15-15)	7.00	*	*	26.9	8.0	2.0	9000	6520
7.00-15	5.50	*	*	28.3	6.6	2.2	7905	5725
	5.50	*	*	29.4	7.4	2.3	8125	5660
7.50-15	6.50	*	*	29.4	7.4	2.3	9600	6900
	5.50	*	*	31.7	7.6	2.8	9200	6665
8.25-15	6.50	*	*	31.7	7.6	2.8	10875	7875
	7.00	*	*	28.0	8.2	2.1	9615	6960
250-15	7.50	*	*	28.0	8.2	2.1	10300	7460
	8.00	*	*	31.8	9.5	2.5	13190	9550
355/65-15	9.75	*	*	32.0	11.5	3.5	15745	11405
10.00-20	7.00	*		40.4	9.8	3.1	14890	10780
	7.50	*		40.4	9.8	3.1	15755	11410
	8.00	*		40.4	9.8	3.1	17015	12320
12.00-20	8.00	*		42.7	10.9	3.4	18605	13475
	8.50	*		42.7	10.9	3.4	19770	14320
	10.00	*		42.7	10.9	3.4	23255	16840

