



# MS801

## INDUSTRIAL PNEUMATICS

Designed for use in multiple applications, the MS801 offers excellent traction and protection from punctures, as well as improved stability.

- Extra wide profile and reinforced sidewall for improved stability
- Thick undertread for maximum puncture resistance
- Self-cleaning industrial tread design provides excellent traction
- Cut and wear resistant compound

Applications:



Size	PR	Type	Rim	O.D.	S.W.	T.D.	Infl. P.	L.C.C. (lbs)		L.I.
				in	in	32nds		psi	15 mph	
18x7-8	14	TT	4.33R	18.3	6.8	21	130	4160	2690	121A5
	16	TT	4.33R	18.3	6.8	21	145	4730	3060	125A5
5.00-8	10	TT	3.00D	18.4	5.4	18	145	3120	2015	111A5
6.00-9	10	TT	4.00	21.5	6.5	20	125	3785	2445	118A5
	12	TT	4.00	21.5	6.5	20	150	4160	2690	121A5
23x9-10	18	TT	6.50F	23.0	9.0	24	130	6970	4500	139A5
	20	TT	6.50F	23.0	9.0	24	145	7590	4905	142A5
6.50-10	10	TT	5.00	23.4	7.0	21	115	4290	2770	122A5
	12	TT	5.00	23.4	7.0	21	140	4730	3060	125A5
23x10-12	16	TT	8.00G	23.5	9.6	25	115	6970	4500	139A5
	20	TT	8.00G	23.5	9.6	25	145	8320	5375	145A5
7.00-12	12	TT	5.00	26.7	7.7	22	125	5900	3815	133A5
	14	TT	5.00	26.7	7.7	22	145	6085	3930	134A5
27x10-12	16	TT	8.00G	26.9	10.0	29	115	8580	5545	146A5
	18	TT	8.00G	26.9	10.0	29	130	9295	6010	149A5
	20	TT	8.00G	26.9	10.0	29	145	10205	6595	152A5
8.15-15 (28x9-15)	14	TT	7.00	27.9	8.7	23	140	8580	5545	146A5
250-15	18	TT	7.50BD	28.9	9.8	25	138	10465	6760	153A5
	20	TT	7.50BD	28.9	9.8	25	145	11115	7180	155A5
7.00-15	14	TT	5.50BD	30.0	8.4	25	135	7385	4770	141A5
7.50-15	14	TT	6.00BD	32.0	8.7	25	135	7995	5165	144A5
8.25-15	14	TT	6.50	33.4	9.6	24	115	9295	6010	149A5
300-15	20	TT	8.00	33.2	11.7	30	135	14300	9240	164A5
	22	TT	8.00	33.2	11.7	30	145	14820	9580	165A5
9.00-20	14	TT	7.00	40.9	10.3	38	130	12870	8315	160A5
10.00-20	16	TT	7.50	42.4	11.2	43	130	14300	9240	164A5
11.00-20	18	TT	8.00	43.6	11.7	45	145	17160	11090	170A5
12.00-20	20	TT	8.50	45.3	12.5	48	145	20410	13190	176A5
	24	TT	8.50	45.3	12.5	48	145	21490	13890	178A5
12.00-24	20	TT	8.50	49.2	12.5	48	145	21450	13860	178A5
14.00-24	28	TT	10.00W	53.9	14.8	52	145	28600	18480	188A5

