



MAXAM
NORTH AMERICA

MS802 GSE

GROUND SUPPORT EQUIPMENT

Designed for use in ground support, industrial and manufacturing applications, the MS802 GSE offers improved operating costs and reduced down time.

- Extra wide profile and reinforced sidewall for improved stability
- Thick undertread for maximum puncture resistance
- Extra deep rib tread provides exceptional wet grip
- Low rolling resistance

Applications:



Size	PR	Type	Rim	O.D.	S.W.	T.D.	Infl. P.	L.C.C. (lbs)		L.I.
				in	in	32nds	psi	15 mph	30 mph	
18x7-8	16	TT	4.33R	18.1	6.6	20	145	3640	3060	125A5
6.00-9 (6.90-9)	10	TT	4.00E	21.4	6.4	21	125	2910	2445	118A5
	12	TT	4.00E	21.4	6.4	21	150	3200	2690	121A5
6.50-10	14	TT	5.00	23.5	7.5	20	145	3960	3330	128A5
23x9-10	20	TT	6.50F	23.1	9.0	20	145	5840	4910	142A5
7.00-12	16	TT	5.00	26.9	7.7	22	145	4940	4150	136A5
165-13	8	TL	4.50	23.2	6.3	21	65	1760	1480	100A5
7.00-15	14	TT	5.50BD	29.8	8.2	23	135	5680	4770	141A5
7.50-15	16	TT	6.00BD	31.8	9.1	23	145	6600	5540	146A5
8.25-15	14	TT	6.50	33.1	9.8	24	115	7150	6010	149A5
8.00-16.5	8	TL	6.00	29.0	8.0	20	65	3740	3140	126A5

