

For use in ground support, industrial and manufacturing applications, the MS802 GSE offers improved operating costs and reduced down time.

- ▶ Extra-wide profile and reinforced sidewall for improved stability
- ▶ Thick undertread for maximum puncture resistance
- ▶ Extra-deep rib tread provides exceptional wet grip
- ▶ Low rolling resistance (LRR) tread compound



TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS



SIZE	P.R.	TYPE	RIM	O.D.		S.W.		T.D.		INFLATION PRESSURE psi/KPa	L.C.C. (LBS/KG)	
				in	mm	in	mm	32nds	mm		15 mph/25 kph	30 mph/50 kph
MS802 GSE												
18 x 7-8	16	TT	4.33R	18.1	460	6.6	168	20	16	145/1000	3640/1650	3060/1385
6.00-9 (6.90-9)	10	TT	4.00E	21.4	543	6.4	163	21	17	125/850	2910/1320	2445/1110
	12	TT	4.00E	21.4	543	6.4	163	21	17	145/1000	3200/1450	2690/1220
6.50-10	14	TT	5.00	23.5	597	7.5	190	20	16	145/1000	3960/1800	3325/1510
23 x 9-10	20	TT	6.50F	23	584	8.8	223	20	16	145/1000	5840/2650	4905/2225
7.00-12	16	TT	5.00	26.9	683	7.7	196	22	17	145/1000	4940/2240	4150/1880
165-13	8	TL	4.50	23.2	589	6.3	160	21	17	65/450	1760/800	1480/670
	10	TL	4.50	23.2	589	6.3	160	21	17	94/650	2150/975	1840/840
185-14	10	TL	6J	25.0	635	7.3	185	25	20	95/655	2470/1120	2070/940
7.00-15	14	TT	5.50BD	29.8	757	8.2	208	23	18	135/930	5680/2575	4770/2165
7.50-15	16	TT	6.00BD	31.8	808	9.1	231	23	18	145/1000	6600/3000	5545/2520
8.25-15	14	TT	6.50	33.1	841	9.8	248	24	19	115/790	7150/3250	6005/2730
8.00-16.5	8	TL	6.00	29	736	8	203	20	16	65/450	3740/1700	3140/1430
8.75-16.5	10	TL	6.75	30.3	769	9.1	231	24	19	75/520	4800/2180	4030/1830
	12	TL	6.75	30.3	769	9.1	231	24	19	95/650	5520/2500	4635/2100
MS802W												
8.75-16.5	10	TL	6.75	30.3	770	9.1	230	30	24	75/520	4800/2180	4030/1830
	12	TL	6.75	30.3	770	9.1	230	30	24	95/650	5520/2500	4635/2100

