

MAXAM

MS803/ MS804

BIAS PORT IND3 / IND4

Designed for heavy loads and long cycle times typical of demanding port applications.

- Extra wide profile and reinforced sidewall for improved stability
- Multi-bead design to withstand extreme impact and shock loads
- Tread patterns designed to maximize tread life
- Cut and wear resistant compound
- High quality casing allows for excellent retreadability

Applications:



Size	P.R.	Type	Rim	O.D.		S.W.		T.D.		Infl. P.	L.C.C. (lbs/kg)	
				in	mm	in.	mm	32nds	mm		psi/KPa	15 mph/25 kph
12.00-20 TR	20	TT	8.50	46.2	1173	12.3	312	25	20	145/1000	20410/9230	15700/7100
14.00-24 TR	28	TT	10.00W	53.5	1359	14.4	366	58	46	145/1000	28600/13000	22000/10000
16.00-25 SM	32	TL	11.25/2.0	60.9	1547	16.9	429	64	51	145/1000	35880/16250	27600/12500
18.00-25 SM	40	TL	13.00/2.5	65.9	1674	19.9	505	68	54	145/1000	50180/22750	38600/17500
18.00-33 SM	40	TL	13.00/2.5	73.7	1872	19.5	495	69	55	145/1000	60710/27560	46700/21200

* Load ratings for counterbalanced industrial cyclic application. Please contact a MAXAM representative for other applications.

