



MAXAM
NORTH AMERICA

MS902

BACKHOE - INDUSTRIAL SERVICE

Modified R1 tread pattern for excellent traction and flotation in soft underfoot conditions.

- Tread design optimized with self-cleaning mud breakers
- Center tie bar reduces vibration during over-the-road driving
- Deep undertread for improved puncture resistance
- Wear and cut resistant compound

Applications:



Size	PR	Type	Rim	O.D.	S.W.	T.D.	Infl. P.	Position	L.C.C. (lbs)		L.I.
									5 mph	25 mph	
				in	in	32nds	psi				
12.5/80-18	12	TL	9.00	38.8	13.4	26	58	-	7500	6000	143A8
	14	TL	9.00	38.8	13.4	26	62	-	8000	6400	145A8
15.5/80-24 (400/80-24)	12	TL	13.00	50.0	15.5	35	44	-	11550	8250	154A8
	14	TL	13.00	50.0	15.5	35	51	-	12320	8800	156A8
	16	TL	13.00	50.0	15.5	35	58	-	13510	9650	159A8
16.5/85-24	12	TL	13.00	52.0	16.4	35	40	FREE	14700	10500	162A8
								DRIVE	10360	7400	150A8
	14	TL	13.00	52.0	16.4	35	48	FREE	15960	11400	165A8
								DRIVE	11270	8050	153A8
	16	TL	13.00	52.0	16.4	35	55	FREE	17220	12300	168A8
								DRIVE	12320	8800	156A8
16.5/85-28	10	TL	W13	54.9	15.2	35	33	FREE	12320	8800	156A8
								DRIVE	8610	6150	144A8

