



MAXAM
NORTH AMERICA

MS903

BACKHOE - INDUSTRIAL SERVICE

Modified R4 tread pattern for excellent traction and flotation in soft underfoot conditions.

- Tread design optimized with self-cleaning mud breakers
- Deep undertread for improved puncture resistance
- Wear and cut resistant compound

Applications:



Size	PR	Type	Rim	O.D.	S.W.	T.D.	Infl. P.	L.C.C. (lbs)		L.I.
				in	in	32nds	psi	5 mph	25 mph	
18.4-26 (480/80-26)	12	TL	W16L	56.3	18.8	36	36	11000	8800	156A8
	16	TL	W16L	56.3	18.8	36	45	13125	10500	162A8
16.9-28 (440/80-28)	12	TL	W15L	55.5	17.2	34	38	9815	7850	152A8
	14	TL	W15L	55.5	17.2	34	44	10690	8550	155A8
16.9-30 (420/85-30)	12	TL	W15L	57.5	17.1	34	34	10060	8050	153A8
	14	TL	W15L	57.5	17.1	34	45	11000	8800	156A8
18.4-30 (460/85-30)	12	TL	W16L	60.2	18.5	36	36	11690	9350	158A8
	14	TL	W16L	60.2	18.5	36	42	12375	9900	160A8

