



# MS906

## SKID STEER

Deep R4 tread pattern designed for skid steer, backhoe and telehandler applications.

- Full flat profile with self-cleaning stepped tread improves performance
- Deep undertread for improved puncture resistance
- Special cut resistant compound improves wear and reduces chunking

Applications:



Size	PR	Type	Rim	O.D.	S.W.	T.D.	Infl. P.	L.C.C. (lbs)	L.I.	
				in	in	32nds	psi	5 mph	30 mph	
5.70-12	6	TL	4.50	22.4	5.7	18	60	1430	900	93A2
23x8.50-12	6	TL	7JA	22.9	8.5	17	50	1820	1145	101A2
	8	TL	7JA	22.9	8.5	17	65	2150	1355	107A2
	12	TL	7JA	22.9	8.5	17	75	2680	1690	115A2
27x8.50-15	8	TL	7JA	26.9	8.7	18	60	2910	1820	118A2
27x10-12	14	TL	8.00G	27.6	10.4	24	100	7800	5040	143A5
7.00-15	6	TL	5.50	29.9	7.8	21	60	3200	2015	121A2
	8	TL	5.50	29.9	7.8	21	70	3640	2290	125A2
31x15.50-15	8	TL	13LB	31.0	15.1	30	45	4400	2760	132A2
10-16.5	10	TL	8.25	30.2	10.7	21	75	4680	2950	134A2
12-16.5	12	TL	9.75	32.8	13.0	25	80	6400	4030	145A2
14-17.5	14	TL	10.50	36.2	14.2	33	80	8550	5360	155A2
15-19.5	14	TL	11.75	40.2	15.3	33	70	10200	6425	161A2
	16	TL	11.75	40.2	15.3	33	80	11000	6930	164A2

