

MAXAM
NORTH AMERICA

MS907

L5 SKID STEER AND BACKHOE

Extra deep, aggressive L5 tread pattern designed for skid steer, backhoe and telehandler applications.

- Full flat profile with self-cleaning stepped tread improves performance
- Deep undertread for improved puncture resistance
- Special cut resistant compound improves wear and reduces chunking
- Increased net-to-gross for maximum tread life and lowest cost per hour

Applications:



Size	PR	Type	Rim	O.D.	S.W.	T.D.	Infl. P.	L.C.C. (lbs)		L.I.
				in	in	32nds	psi	5 mph	30 mph	
23x8.50-12	8	TL	7JA	22.6	8.4	35	65	2150	1350	107A2
27x8.50-15	10	TL	7JA	27.0	8.7	38	75	3300	2080	122A2
10-16.5	14	TL	8.25	31.3	10.9	44	90	3960	2500	128A2
12-16.5	14	TL	9.75	33.1	13.0	44	90	6800	4285	147A2
14-17.5	16	TL	10.50	36.8	14.1	46	90	9100	5735	157A2
12.5/80-18	14	TL	11.00	38.0	12.0	47	62	8260	5200	145A8
	16	TL	11.00	38.0	12.0	47	70	8940	5630	148A8
16.9-28	14	TL	W15L	55.5	17.7	48	45	10690	6735	155A8

