



MAXAM
NORTH AMERICA

MS909

MULTIPURPOSE

For use on wheeled excavators where traction and stability are required.

- Wide and open tread design for maximum flotation and traction on soft terrain
- Reinforced sidewall for excellent stability and cut resistance
- Center tie bar reduces vibration during over-the-road driving
- Cut and wear resistant tread compound

Applications:



Size	PR	Type	Rim	O.D.	S.W.	T.D.	Infl. P.	L.C.C. (lbs)	L.I.
				in	in	32nds	psi	30 mph	
405/70-20 (16/70-20)	12	TL	13.00	42.4	16.2	42	46	6400	145B
	14	TL	13.00	42.4	16.2	42	51	7150	149B
	16	TL	13.00	42.4	16.2	42	58	7850	152B
405/70-24 (16/70-24)	14	TL	13.00	46.2	15.9	42	58	7850	152B
	16	TL	13.00	46.2	15.9	42	72	8800	156B
445/65-19.5 (18-19.5)	16	TL	14.00	43.1	18.0	34	85	9900	160B
	18	TL	14.00	43.1	18.0	34	100	11000	164B
445/65-22.5 (18-22.5)	16	TL	14.00	46.1	18.0	36	85	10700	163B
	18	TL	14.00	46.1	18.0	36	100	12000	167B

