

Designed for use on demanding forestry equipment. High strength, belt-stabilized tire construction provides excellent traction and flotation in severe logging applications.

- ▶ Heavy-duty shoulder and sidewall
- ▶ Maximum protection from cuts, impacts and punctures
- ▶ Cut-resistant compound specifically engineered for forestry service
- ▶ Steel-reinforced undertread
- ▶ Extra-wide footprint provides exceptional flotation in muddy and wet ground conditions
- ▶ Nylon-wrapped beads prevent unwinding

BoltzEquipmentParts.com Jacksonville, Florida USA
 Phone: +1 904-232-4448 Email: sales@boltzequipmentparts.com



TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS



SIZE	P.R.	TYPE	RIM	O.D.	S.W.	T.D.	INFLATION PRESSURE	L.C.C. (Lbs/Kg)	L.I.
				in mm	in mm	32nds mm	psi KPa	5mph 10kph	
28L-26	16	TL	DW25B	64.7	28.1	72	35	14800	174A2
				1644	714	57	240	6700	
	20	TL	DW25B	64.1	28.0	72	40	16100	177A2
				1628	710	57	275	7300	
	26	TL	DW25B	64.7	28.1	72	55	20400	185A2
				1644	714	57	380	9250	
24.5-32	20	TL	DH21	72.1	24.5	76	45	18700	182A2
				1831	622	60	310	8500	
30.5L-32	20	TL	DH27	72.7	30.5	76	35	18700	182A2
				1847	775	60	240	8500	
	26	TL	DH27	73.0	30.2	76	45	22000	188A2
				1855	768	60	310	10000	
	32	TL	DH27	72.7	30.2	76	55	24700	192A2
				1847	775	60	380	11200	
35.5L-32	26	TL	DH31	79.2	35.2	80	40	26800	195A2
				2011	895	64	275	12150	
	30	TL	DH31	79.2	35.5	79	45	29100	198A2
				2011	902	63	310	13200	

