



MAXAM
NORTH AMERICA

MS951R

AGRIXTRA R1W RADIAL DRIVE TIRE

Premium 45° lug profile provides excellent traction and minimizes vibration while roading. Low pressure and wide footprint lowers soil compaction.

- Self cleaning tread design
- Wide tread for maximized performance in the field
- Low pressure for minimum soil disturbance
- Premium rubber compounds reduce ozone cracking and weathering

Applications



Size	Alt Size	Type	Rim	O.D.	S.W.	T.D.	RC	Infl. P.	LCC (lbs)	LI/SS
				in	in	32nds	in	psi	25/30 mph	
280/85R24	11.2R24	TL	W10.00	42.9	11.4	52.0	128	23	2680	115A8/B
320/85R24	12.4R24	TL	W11.00	45.7	12.6	53.0	136	23	3300	122A8/B
340/85R24	13.6R24	TL	W12.00	46.9	14.0	55.0	140	23	3640	125A8/B
380/85R24	14.9R24	TL	W12.00	49.6	15.4	55.0	148	23	4300	131A8/B
420/85R24	16.9R24	TL	W15.00	51.8	17.1	59.0	156	23	5080	137A8/B
340/85R28	13.6R28	TL	W12.00	51.0	13.9	53.0	152	23	3860	127A8/B
380/85R28	14.9R28	TL	W13.00	53.3	15.1	55.0	160	23	4540	133A8/B
420/85R28	16.9R28	TL	W15.00	56.0	17.6	59.0	168	23	5360	139A8/B
380/85R30	14.9R30	TL	W13.00	55.6	15.1	55.0	166	23	4800	135A8/B
420/85R30	16.9R30	TL	W15.00	58.3	17.3	64.0	174	23	5520	140A8/B
460/85R30	18.4R30	TL	W16.00	60.7	18.5	66.0	182	23	6400	145A8/B
420/85R34	16.9R34	TL	W15.00	62.0	17.4	65.0	186	23	5840	142A8/B
460/85R34	18.4R34	TL	W15.00	64.6	18.3	66.0	194	23	6800	147A8/B
420/85R38	16.9R38	TL	W16.00	65.9	17.9	66.0	198	23	6150	144A8/B
460/85R38	18.4R38	TL	W16.00	69.1	18.8	66.0	206	23	7150	149A8/B
520/85R38	20.8R38	TL	W18.00	73.0	21.4	68.0	218	23	8550	155A8/B
520/85R42	20.8R42	TL	W18.00	77.2	21.1	69.0	230	23	9100	157A8/B
650/65R38		TL	DW20B	71.3	25.5	73.0	213	23	9900	160A8/157D

