heauenly heat saunas

# **Traditional**

Heater Installation

Instruction Manual

Please refer to the heater manual for specific wiring instruction



#### **Overview**

- 1. Install junction box.
- 2. Direct connect junction box to electrical panel.
- 3. Run 3/4 in. metallic conduit from junction box to heater.
- 4. Mount heater.
- 5. Mount thermostat bulb.

#### **Table of Contents**

Requirements	03
Electrician to Provide	03
Heater Connection Picture	03
Exterior	04
Step: 1	04
Step: 2	04
Heater Mounting	05
Step: 1	05
Step: 2	05
Step: 3	06
Step: 4	07
Step: 5	07
Step: 6	08
Step: 7	08
Thermostat Bulb	00




### Requirements

- 1. It needs a 2 pole 30 amp non-GFCI breaker.
- 2. Run (2) #10 copper wires + ground to heater.
- 3. Wires connect to heater terminals 1 and 2.

#### **Electrician to Provide**

- 1. Junction box.
- 2. 3/4 in metallic conduit.
- 3. All wiring external sauna heater.

#### **Heater Connection Picture**



#### **Exterior**

- 1. Install Junction box (provided by electrician) on outside of the back wall of the sauna next to the predrilled hole.
- 2. Use 3/4 in. metallic conduit from the junction box to the sauna heater (provided by electrician). Route metallic conduit through pre-drilled holes on the back wall and sitting baffle.





Junction Box (Provided by Electrician).

Use 3/4 in. metallic conduit from the junction box to the sauna heater (Provided by Electrician). Route conduit through pre drilled holes in the back of the sauna and in the sitting baffle.

Direct Connect to Electrical Panel.



Run metallic conduit through this hole to heater.

## **Heater Mounting**

1. Remove 2 screws to release black mounting plate from silver mounting bracket.



2. Slide black mounting plate away from heater.



3. Remove black hanging bracket from bottom of heater.





4. Mount black hanging bracket to wall with screws included in warning sign bag that was in heater box.





6.75 inches from the bottom of back plate to top of trim on floor.

5. Once mounting plate is attached to the wall, the heater can be placed back on the bracket bars by inserting the bar ends back into the holes in the bottom of the heater.



6. Place the silver mounting bracket back on top of the heater.



7. Screw the mounting bracket back to the black mounting plate.




#### **Thermostat Bulb**

The KV Topclass heater has a temperature sensor bulb attached to a coil of wire. This bulb needs to be run up the face of the sauna wall ideally 12" down from the ceiling. A mounting bracket is included in the heater box, usually attached to the heating elements with a zip tie.

To locate the sensor bulb remove the side cover under the control knobs. The thermostat bulb connected to a coil of wire is tucked between the control consul and the main heater body.

Depending on if you have controls on the left of right side of the heater the coil of wire could be found at the front of the heater or hidden on the back side of the heater against the wall.





Run the thermostat wire up the wall and away from the heater at least 12 inches. The bulb should be mounted 12" - 24" from the ceiling of the sauna. Cover the thermostat wire with the wooden cover provided with the heater.



- Call or Text: 1-888-825-2085
- ™ heavenlyheat@heavenlyheatsaunas.com
- 100 Commons Road STE 7 PMB 410 Dripping Springs, Tx 78620

Since 1988. Heavenly Heat Saunas. All rights reserved.

