SECTION 01: IDENTIFICATION

CARTIER CHEMICALS Ltd. 2610A Boul. J B Deschamps, Lachine, Quebec, H8T 1C8, CANADA

PRODUCT NAME: VYTAC ACX Powder

MANUFACTURER: Same as above PREPARED BY: Production Department

TELEPHONE NO.: (514) 637 4631 or (800) 361 9432

EMERGENCY PHONE NUMBER: As above or call CANUTEC (613) 996 6666

MATERIAL USE: Please refer to technical literature

SECTION 02: HAZARDS IDENTIFICATION

GHS Classification: This product is classified as an eye irritant category 2A, Oral toxicity category 5

LABEL Information:

WARNING

Causes serious eye irritation. May cause skin irritation. May be harmful if swallowed.

Precautions: Wash hands thoroughly after handling. Wear eye protection and protective gloves.

Response: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing. If eye irritation persists get medical advice/attention.

IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs get medical advice/attention.

IF SWALLOWED: Get medical attention if you feel unwell.

SECTION 03: COMPOSITION / INFORMATION on HAZARDOUS INGREDIENTS

HAZARDOUS INGREDIENTS CONC. APPROX.% (WT/WT) C.A.S #

Sodium Carbonate 60 -100 497 - 19 - 8

Any concentration shown as a range is due to batch variation or is to protect confidentiality.

SECTION 04: FIRST AID MEASURES

INSTRUCTIONS: For contact with skin, rinse with water. Remove and wash contaminated clothing before reuse.

For eye contact, flush eyes with large amounts of water for 15 minutes. If irritation persists seek

medical attention.

If ingested, give 2 glasses water; and do not induce vomiting; seek immediate medical attention.

In case of inhalation of dust, remove to fresh air.

PRIMARY SYMPTOMS /ROUTE OF ENTRY:

SKIN CONTACT May cause mild irritation
EYE CONTACT May cause severe irritation

INHALATION Dust may cause irritation of nasal passages INGESTION May cause gastrointestinal discomfort

SECTION 05: FIRE AND EXPLOSION HAZARD AND FIRE FIGHTING MEASURES

FLAMMABILITY: NO
IF YES , UNDER WHICH CONDITIONS:
EXTINGUISHING MEDIA: N.Ap.
SPECIAL PROCEDURES: N.Ap.
HAZARDOUS COMBUSTION PRODUCTS: N.Ap.
UNUSUAL FIRE AND EXPLOSION HAZARDS: NIL
SENSITIVITY TO MECHANICAL IMPACT: NIL

SENSITIVITY TO STATIC DISCHARGE: NIL

VYTAC ACX P PAGE 2/3

SECTION 06: ACCIDENTAL RELEASE MEASURES

LEAK AND SPILL PROCEDURE: Wear gloves and eye protection. Recover as much as possible using any convenient means. Recovered material is usable as long as it is not contaminated with incompatible materials. Flush away residues as per local regulations.

SECTION 07: HANDLING AND STORAGE

HANDLING PROCEDURES AND EQUIPMENT: Avoid contact with skin and eyes. Keep container closed when not in use.

STORAGE REQUIREMENTS: Store in cool location.

PERSONAL PROTECTIVE EQUIPMENT / EXPOSURE CONTROLS **SECTION 08:**

GLOVES / TYPE: Chemical resistant

RESPIRATOR / TYPE: Dust filter mask (if handling large quantities).

EYE / TYPE: Goggles

CLOTHING /TYPE: Appropriate for the use environment Have access to eye bath and safety shower OTHER / TYPE:

ENGINEERING CONTROLS: General ventilation is adequate.

CONTROL PARAMETERS: N/Ap

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE / APPEARANCE: Pink Granular powder ODOUR: None

ODOUR THRESHOLD: Not available SPECIFIC GRAVITY: ~1.2 VAPOUR PRESSURE (mm Hg @ 20C): N.Ap. VAPOUR DENSITY (Air = 1): N.Ap. EVAPORATION RATE (WATER = 1): N.Ap. FREEZING POINT (C): N.Ap. BOILING POINT INIT / RANGE (C): N.Ap. SOLUBILITY IN WATER (% W/W): 100

pH (% SOLUTION): 11.4 (1%) % VOLATILE (WT): < 1% FLASH POINT (C): N.Ap. FLAMMABILITY: Nil

LEL / UEL LIMITS (% by vol): LEL: N.Ap. UEL: N.Ap. DECOMPOSITION TEMP (C): N.Ap.

AUTO IGNITION TEMP(C): N.Ap. VISCOSITY: N.Ap.

PARTITION COEFF. n-octanol/water: N.Av.

SECTION 10: STABILITY AND REACTIVITY

CHEMICALLY STABLE: Yes

IF NO, UNDER WHICH CONDITIONS?: INCOMPATIBILITY WITH OTHER SUBSTANCES: Yes

IF YES, WITH WHICH ONES?: Will react with acidic materials.

SPECIAL REACTIVITY AND UNDER WHAT CONDITIONS: N.Av.

HAZARDOUS DECOMPOSITION PRODUCTS: CO2 is generated as a byproduct of the acid neutralization reaction. When used to neutralize acids in enclosed spaces, make sure that adequate ventilation is provided to maintain CO2 levels below hazard standards. SENSITIVITY TO SHOCK, VIBRATION or STATIC DISCHARGE: None.

SECTION 11: TOXICOLOGICAL INFORMATION

EXPOSURE LIMIT OF MATERIAL: N.Av.

LC 50 OF MATERIAL, SPECIES AND ROUTE N.Ap.

2.8 gr / Kg (rat) LD 50 OF MATERIAL, SPECIES AND ROUTE: CARCINOGENICITY OF MATERIAL:

No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC, OSHA, NTP, ACGIH

REPRODUCTIVE EFFECTS: No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

PRIMARY SYMPTOMS /ROUTE OF ENTRY:

SKIN CONTACT May cause mild irritation **EYE CONTACT** May cause severe irritation

INHALATION Dust may cause irritation of nasal passages **INGESTION** May cause gastrointestinal discomfort

SENSITIZING CAPABILITY OF MATERIAL: N.Av. SYNERGISTIC MATERIALS: N.Av.

SECTION 12: ECOLOGICAL CONSIDERATIONS

AQUATIC TOXICITY: Fingerling Rainbow Trout 96Hr LC50 >100 mg /L

PERSISTANCE & DEGRADABILITY: Readily biodegradable.

BIOACCUMULATIVE POTENTIAL: N.Av.

MOBILITY IN SOIL: N.Av. OTHER ADVERSE EFFECTS: N.Av. VYTAC ACX P PAGE 3/3

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL: In accordance with municipal, provincial and federal regulations

SECTION 14: TRANSPORT INFORMATION

T.D.G. CLASSIFICATION: Not regulated under TDG

UN NUMBER : N.Ap. PACKING GROUP : N.Ap.

SECTION 15: REGULATORY INFORMATION

GHS CLASSIFICATION: See section 2

HPR COMPLIANCE: This product has been classified in accordance with the hazard criteria of the GHS and the SDS contains

all the information required by the HPR.

REACH COMPLIANCE: Conforms to Regulation (EC) No. 1907/2006, including all applicable registrations concerning ingredients.

SECTION 16: OTHER INFORMATION

ABBREVIATIONS USED: N.Av. = Not Available N.Ap. = Not applicable L(U)EL = Lower(Upper) explosion limit

PREPARATION DATE: 16/08/2021