

## INT/EXT READY MIXED MULTISURFACE REPAIR FILLER



### GENERAL INFORMATION

#### Description

Ready mixed  
multisurface repair filler

#### Intended use

Interior/exterior  
• Filling small holes and cracks  
on multiple surfaces



### PRODUCT ADVANTAGES

- + Excellent adhesion to difficult substrates, including ceramic tiles
- + Fine finish
- + Water, humidity & mould resistant
- + Ideal for kitchens and bathrooms
- + White

### USE

#### DILUTION APPLICATION

- *Conditions*

- *Equipment*

- *Operational mode*

- *Equipment cleaning*

Ready mixed

Do not apply at temperatures of below +5°C or above +35°C, or at a relative humidity of above 80% H.R.

Blade, filling knife.

Massage tube before use. Fill the cavity thoroughly, taking care to line the bottom while chasing air and level off with spatula.

With water before completely dry. Do not throw away into drains, dispose of this material and its container to an approved disposal contractor or taken to municipal collection point. Do not dispose into the environment.

#### RECOMMANDATIONS

Allow product to cure 24 hours before introducing damp & humid conditions. Suitable for tile grouting and repairing chips & cracks to ceramic tiles.

Apply two or more layers when filling deeper cavities.

#### APPLICATION THICKNESS

3 mm

#### AVERAGE CONSUMPTION

125 ml/m<sup>2</sup>/mm thickness

#### SUBSTRATES

Concrete, cellular concrete, cement, brick, plaster, plasterboard, gypsum board, primed wood, ceramic tiles, glass tiles, glass ceramic, stone, mortars polystyrene, cork, old painted substrates.

*Substrates must be hard, cohesive, clean, sound and dry according to the local standards.*


#### OVERCOAT

Primer, interior conventional paint, light-weight wall coverings.

# INT/EXT READY MIXED MULTISURFACE REPAIR FILLER



## TECHNICAL DATA

<b>COMPONANTS</b>	Based on acrylic copolymers.
<b>DENSITY</b>	1.6 ± 0.1
<b>pH</b>	8 ± 0.5
<b>COLOUR</b>	White
<b>WORKING TIME AT 20°C</b>	Unlimited
<b>WAITING TIME BEFORE OVERCOATING</b>	Once completely dry
<b>CLASSIFICATION</b>	NFT 36 005 famille IV class 4b
<b>V.O.C</b>	< 20 g/l (Ready mixed)
<b>HEALTH AND SAFETY</b>	 Use in a well-ventilated place. Avoid direct contact with skin and eyes. Do not breathe dust. In case of prolonged contact, it is recommended to wear suitable gloves. Safety data sheet available on <a href="http://www.beissier.eu">www.beissier.eu</a> or <a href="http://www.quickfds.com">www.quickfds.com</a>
<b>PACKAGING</b>	200 ml tube
<b>STORAGE</b>	12 months from date of manufacture, in unopened original packaging, protected from frost, heat (max. +30°C), sun and moisture. Close the packaging after each use.

This data sheet supersedes and replaces any prior sheet relating to the same product.

Date of issue : April 2017

The purpose of this data sheet is to inform our customers about our product's properties. The information presented in the sheet is based on the current state of our knowledge. However, this information is no substitute for a description pertaining specifically to the type and condition of the substrate concerned. Since technical progress is continuously being made, it is our customer's responsibility, prior to use, to check with us that updated edition of this sheet has not been issued.