

## SAFETY DATA SHEET

### Pegakote component A

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Product name : Pegakote component A

Product description : Floorcoating.

Product type : Liquid.

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses				
Industrial uses Professional uses				
Uses advised against Reason				
Consumer use	Product is not intended for consumer use.			

### 1.3 Details of the supplier of the safety data sheet

Martin Mathys NV, Kolenbergstraat 23, B-3545 Zelem, Belgium

Telephone no.: +32 (0) 13 460 200

Fax no.: +32 (0) 13 460 201

e-mail address of person : rpmeurohas@ro-m.com

responsible for this SDS

### 1.4 Emergency telephone number

**Supplier** 

**Telephone number** : +44 (0) 207 858 1228

Hours of operation : 24 / 7

### SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition**: Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317

STOT RE 2, H373 (inhalation)

Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

Date of issue/Date of revision : 29/07/2016 Date of previous issue : No previous validation Version : 2 1/14

## **SECTION 2: Hazards identification**

**Hazard pictograms** 







Signal word : Danger

**Hazard statements** : Causes serious eye damage.

Causes skin irritation.

May cause an allergic skin reaction.

May cause damage to organs through prolonged or repeated exposure if inhaled.

Harmful to aquatic life with long lasting effects.

**Precautionary statements** 

**Prevention**: Wear protective gloves and eye protection: nitrile rubber gloves and Safety glasses

with side shields. Do not breathe vapour or spray. Avoid release to the environment.

Response : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing. Immediately call a doctor. IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get

medical attention.

Storage : Not applicable.

Disposal : Dispose of contents and container in accordance with all local, regional, national

and international regulations.

Hazardous ingredients : polyaminoamide adduct

quartz, respirable fraction 3-aminomethyl-3,5,5-trimethylcyclohexylamine

Supplemental label

elements

: Not applicable.

: Not applicable.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and

articles

Special packaging requirements

Containers to be fitted with child-resistant

fastenings

: Not applicable.

Tactile warning of danger : Not applicable.

2.3 Other hazards

Other hazards which do not result in classification

: None known.

## **SECTION 3: Composition/information on ingredients**

3.2 Mixtures : Mixture

			Classification		
Product/ingredient name	Identifiers	%	67/548/EEC	Regulation (EC) No. 1272/2008 [CLP]	Type

Date of issue/Date of revision : 29/07/2016 Date of previous issue : No previous validation Version : 2

## **SECTION 3: Composition/information on ingredients**

polyaminoamide	CAS: -	≥10 - <25	Xi; R41	Eye Dam. 1, H318	[1]
adduct quartz, respirable fraction	EC: 238-878-4	≥1 - <3	Xn; R48/20	STOT RE 1, H372 (respiratory tract) (inhalation)	[1] [2]
3-aminomethyl-3,5, 5-trimethylcyclohexylamine	CAS: 14808-60-7 EC: 220-666-8	≥1 - <3	Xn; R21/22	Acute Tox. 4, H302	[1]
o announting	CAS: 2855-13-2 Index: 612-067-00-9		C; R34 R43	Acute Tox. 4, H312 Skin Corr. 1B, H314	
			R52/53	Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Chronic 3, H412	
zinc oxide	REACH #: 01-2119463881-32 EC: 215-222-5 CAS: 1314-13-2 Index: 030-013-00-7	≥0.3 - <1	N; R50/53	Aquatic Acute 1, H400 Aquatic Chronic 1, H410	[1]
			See Section 16 for the full text of the R-phrases declared above.	See Section 16 for the full text of the H statements declared above.	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

### <u>Type</u>

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8.

### SECTION 4: First aid measures

### 4.1 Description of first aid measures

**General** 

: In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.

Eye contact

: Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.

Inhalation

: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

Skin contact

: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

Ingestion

: If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.

**Protection of first-aiders** 

No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

Date of issue/Date of revision : 29/07/2016 Date of previous issue : No previous validation Version : 2 3/14

## **SECTION 4: First aid measures**

### 4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in nonallergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains 3-aminomethyl-3,5,5-trimethylcyclohexylamine. May produce an allergic reaction.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician

: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

**Specific treatments** 

: No specific treatment.

See toxicological information (Section 11)

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media

: Recommended: alcohol-resistant foam, CO2, powders, water spray.

Unsuitable extinguishing

media

: Do not use water jet.

### 5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

**Hazardous thermal** decomposition products : Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

#### 5.3 Advice for firefighters

**Special protective actions** for fire-fighters

: Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.

**Special protective** equipment for fire-fighters : Appropriate breathing apparatus may be required.

**Additional information** 

: No unusual hazard if involved in a fire.

### SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: Exclude sources of ignition and ventilate the area. Avoid breathing vapour or mist. Refer to protective measures listed in sections 7 and 8.

For emergency responders: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

Date of issue/Date of revision : 29/07/2016 Date of previous issue : No previous validation Version :2 4/14

### **SECTION 6: Accidental release measures**

### 6.3 Methods and material for containment and cleaning up

### **Small spill**

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

### Large spill

: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

## 6.4 Reference to other sections

: See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

## **SECTION 7: Handling and storage**

The information in this section contains generic advice and guidance.

## 7.1 Precautions for safe handling

: Keep away from heat, sparks and flame. No sparking tools should be used.

Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Avoid inhalation of dust from sanding.

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed.

Put on appropriate personal protective equipment (see Section 8). Never use pressure to empty. Container is not a pressure vessel.

Always keep in containers made from the same material as the original one.

Comply with the health and safety at work laws. Do not allow to enter drains or watercourses.

When spraying and sanding, suitable respiratory protection must be used.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations.

### Notes on joint storage

Keep away from: oxidising agents, strong alkalis, strong acids.

### Additional information on storage conditions

Observe label precautions. Store between the following temperatures: 5 to 35°C (41 to 95°F). Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

### 7.3 Specific end use(s)

Recommendations : Not available.

Industrial sector specific : Not available.

solutions

Date of issue/Date of revision : 29/07/2016 Date of previous issue : No previous validation Version : 2 5/14

## **SECTION 8: Exposure controls/personal protection**

### 8.1 Control parameters

### Occupational exposure limits

Product/ingredient name	Exposure limit values
quartz, respirable fraction	EH40/2005 WELs (United Kingdom (UK), 12/2011). TWA: 0,1 mg/m³ 8 hours. Form: respirable dust

## Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

### **DNELs/DMELs**

Product/ingredient name	Type	Exposure	Value	Population	Effects
3-aminomethyl-3,5,	DNEL	Short term	20.1 mg/m <sup>3</sup>	Workers	Systemic
5-trimethylcyclohexylamine	DNEL	Inhalation Short term Inhalation	20.1 mg/m³	Workers	Local
	DNEL	Long term Oral	0.526 mg/ kg bw/day	Consumers	Systemic
zinc oxide	DNEL	Long term Inhalation	5 mg/m³	Workers	Systemic
	DNEL	Long term Inhalation	2.5 mg/m³	Consumers	Systemic
	DNEL	Long term Dermal	83 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Dermal	83 mg/kg bw/day	Consumers	Systemic
	DNEL	Long term Oral	0.83 mg/ kg bw/day	Consumers	Systemic

### **PNECs**

Product/ingredient name	Compartment Detail	Value	Method Detail
3-aminomethyl-3,5, 5-trimethylcyclohexylamine	Fresh water	0.06 mg/l	Assessment Factors
	Marine	0.006 mg/l	Assessment Factors
	Fresh water sediment	5.784 mg/kg	Assessment Factors
	Marine water sediment	0.578 mg/kg	Assessment Factors
	Sewage Treatment Plant	3.18 mg/l	Assessment Factors
	Soil	1.121 mg/kg	Assessment Factors
zinc oxide	Fresh water	25.6 µg/l	-
	Marine	7.6 µg/l	-
	Sewage Treatment	64.7 µg/l	-
	Plant		
	Fresh water sediment	146 mg/kg dwt	-
	Marine water sediment	70.3 mg/kg dwt	-
	Soil	44.3 mg/kg dwt	-

### 8.2 Exposure controls

Date of issue/Date of revision : 29/07/2016 Date of previous issue : No previous validation Version : 2 6/14

## **SECTION 8: Exposure controls/personal protection**

## Appropriate engineering controls

: Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the OEL, suitable respiratory protection must be worn.

### **Individual protection measures**

### **Hygiene measures**

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

### **Eye/face protection**

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead. Recommended: safety glasses with side-shields (EN 166).

### **Skin protection**

### **Hand protection**

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

#### **Gloves**

: For prolonged or repeated handling, use the following type of gloves:

Recommended: > 8 hours (breakthrough time): nitrile rubber (0.5mm).

The recommendation for the type or types of glove to use when handling this product is based on information from the following source:

EN 374-3: 2003

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

## **Body protection**

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: Wear overalls or long sleeved shirt.

### Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

### Respiratory protection

: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Recommended: organic vapour (Type A) and particulate filter

## **Environmental exposure controls**

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Date of issue/Date of revision : 29/07/2016 Date of previous issue : No previous validation Version : 2

## **SECTION 9: Physical and chemical properties**

### 9.1 Information on basic physical and chemical properties

**Appearance** 

Physical state : Liquid.

Colour : Various

Odour : Not available.

Odour threshold : Not available.

PH : Not available.

Melting point/freezing point : Not available.

Initial boiling point and : Not available.

boiling range

Flash point : Not available.

Evaporation rate : Not available.

Flammability (solid, gas) : Not available.

Upper/lower flammability or : Not available.

**explosive limits** 

Vapour pressure: Not available.Vapour density: Not available.Relative density: 1.55 to 1.6Solubility(ies): Not available.Partition coefficient: n-octanol/: Not available.

water

Auto-ignition temperature : Not available.

Decomposition temperature : Not available.

Viscosity : Dynamic (room temperature): 1500 to 2500 mPa·s

Explosive properties : Not available.

Oxidising properties : Not available.

### 9.2 Other information

No additional information.

## **SECTION 10: Stability and reactivity**

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

**10.2 Chemical stability** : Stable under recommended storage and handling conditions (see Section 7).

10.3 Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : When exposed to high temperatures may produce hazardous decomposition products.

**10.5 Incompatible materials** : Keep away from the following materials to prevent strong exothermic reactions:

oxidising agents, strong alkalis, strong acids.

10.6 Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced. If involved in a fire, toxic gases including CO, CO2 and smoke can be generated.

Date of issue/Date of revision: 29/07/2016Date of previous issue: No previous validationVersion: 2

## **SECTION 11: Toxicological information**

### 11.1 Information on toxicological effects

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains 3-aminomethyl-3,5,5-trimethylcyclohexylamine. May produce an allergic reaction.

### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
3-aminomethyl-3,5, 5-trimethylcyclohexylamine	LD50 Oral	Rat	1030 mg/kg	-
zinc oxide	LC50 Inhalation Dusts and mists	Mouse	2500 mg/m³	4 hours
	LC50 Inhalation Dusts and mists	Rat	>5700 mg/m³	4 hours
	LD50 Oral	Rat	>15 g/kg	-

**Conclusion/Summary** 

: Based on available data, the classification criteria are not met.

### **Acute toxicity estimates**

Not available.

### **Irritation/Corrosion**

Product/ingredient name	Result	Species	Score	Exposure	Observation
3-aminomethyl-3,5, 5-trimethylcyclohexylamine	Eyes - Cornea opacity	Rabbit	2	24 hours	-
zinc oxide	Skin - Severe irritant Eyes - Mild irritant	Rabbit Rabbit	-	4 hours 24 hours 500	-
	Skin - Mild irritant	Rabbit	-	milligrams 24 hours 500 milligrams	-

### **Conclusion/Summary**

Skin : Causes skin irritation.

**Eyes** : Causes serious eye damage.

**Respiratory**: May cause damage to organs through prolonged or repeated exposure if inhaled.

### **Sensitisation**

Product/ingredient name	Route of exposure	Species	Result
3-aminomethyl-3,5, 5-trimethylcyclohexylamine	skin	Guinea pig	Sensitising

### **Conclusion/Summary**

**Skin** : May cause an allergic skin reaction.

**Respiratory**: Based on available data, the classification criteria are not met.

**Mutagenicity** 

**Conclusion/Summary**: Based on available data, the classification criteria are not met.

**Carcinogenicity** 

**Conclusion/Summary**: Based on available data, the classification criteria are not met.

**Reproductive toxicity** 

**Conclusion/Summary**: Based on available data, the classification criteria are not met.

Date of issue/Date of revision : 29/07/2016 Date of previous issue : No previous validation Version : 2 9/14

## **SECTION 11: Toxicological information**

### **Teratogenicity**

Not available.

Product/ingredient name	Result	Species	Dose	Exposure
3-aminomethyl-3,5, 5-trimethylcyclohexylamine	Negative - Unreported	Rat - Female	>250 mg/kg	-

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

### Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
quartz, respirable fraction	Category 1	Inhalation	respiratory tract

### **Aspiration hazard**

Not available.

Other information : Not available.

## **SECTION 12: Ecological information**

#### 12.1 Toxicity

There are no data available on the mixture itself.

Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

Product/ingredient name	Result	Species	Exposure
3-aminomethyl-3,5, 5-trimethylcyclohexylamine	Acute EC50 37 mg/l Acute EC50 23 mg/l Acute LC50 110 mg/l Chronic NOEC 3 mg/l	Algae - Desmodesmus subspicatus Daphnia spec. Fish Daphnia spec.	72 hours 48 hours 96 hours 21 days

**Conclusion/Summary** : Harmful to aquatic life with long lasting effects.

### 12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
3-aminomethyl-3,5, 5-trimethylcyclohexylamine	OECD 303A	42 % - Not readily - 3 days	-	-
	OECD 301A	8 % - Not readily - 28 days	-	-

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
3-aminomethyl-3,5, 5-trimethylcyclohexylamine	-	-	Not readily

### 12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
3-aminomethyl-3,5, 5-trimethylcyclohexylamine	0,99	-	low

### 12.4 Mobility in soil

Date of issue/Date of revision : 29/07/2016 Date of previous issue : No previous validation Version :2 10/14

## **SECTION 12: Ecological information**

Soil/water partition coefficient (Koc)

: Not available.

Mobility : Non-volatile.

#### 12.5 Results of PBT and vPvB assessment

PBT : Not applicable.

vPvB : Not applicable.

**12.6 Other adverse effects**: No known significant effects or critical hazards.

## **SECTION 13: Disposal considerations**

The information in this section contains generic advice and guidance.

#### 13.1 Waste treatment methods

### **Product**

**Methods of disposal** 

The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** 

: Yes.

**Disposal considerations** 

Do not allow to enter drains or watercourses.
 Dispose of according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no

longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

### European waste catalogue (EWC)

The European Waste Catalogue classification of this product, when disposed of as waste, is:

Waste code	Waste designation
08 01 15*	aqueous sludges containing paint or varnish containing organic solvents or other dangerous substances

### **Packaging**

**Methods of disposal** 

: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

**Disposal considerations** 

: Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers.

Empty containers must be scrapped or reconditioned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions.

**Special precautions** 

: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Date of issue/Date of revision : 29/07/2016 Date of previous issue : No previous validation Version : 2

## **SECTION 14: Transport information**

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.
Additional information	-	-	-	-

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

## **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

**Annex XIV** 

None of the components are listed.

Substances of very high concern

None of the components are listed.

**Annex XVII - Restrictions** on the manufacture, placing on the market

and use of certain dangerous substances,

mixtures and articles

Other EU regulations

VOC : The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the

product label and/or technical data sheet for further information.

**VOC for Ready-for-Use** 

**Mixture** 

: 2004/42/EC - IIA/j: 140g/l (2010). <= 10g/l VOC.

**Europe inventory** : All components are listed or exempted.

: Not applicable.

**Seveso Directive** 

This product is not controlled under the Seveso Directive.

**National regulations** 

Industrial use

: The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.

Date of issue/Date of revision : 29/07/2016 Date of previous issue : No previous validation Version :2 12/14

## **SECTION 15: Regulatory information**

References : EH40/2005 Workplace exposure limits

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by

Regulation (EU) No. 2015/830

### **International regulations**

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

### Montreal Protocol (Annexes A, B, C, E)

Not listed.

### **Stockholm Convention on Persistent Organic Pollutants**

Not listed.

### **Rotterdam Convention on Prior Inform Consent (PIC)**

Not listed.

### **UNECE Aarhus Protocol on POPs and Heavy Metals**

Not listed.

**CN code** : 3209 90 00

#### International lists

### **National inventory**

Australia : Not determined.
Canada : Not determined.
China : Not determined.
Japan : Not determined.

Malaysia : At least one component is not listed.

New Zealand : Not determined.

Philippines : Not determined.

Republic of Korea : Not determined.

Taiwan : Not determined.

United States : Not determined.

### 15.2 Chemical Safety

**Assessment** 

: No Chemical Safety Assessment has been carried out.

CLP = Classification, Labelling and Packaging Regulation (Regulation (EC) No.

### **SECTION 16: Other information**

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

: ATE = Acute Toxicity Estimate

1272/2008]

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

vPvB = Very Persistent and Very Bioaccumulative

### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Skin Irrit. 2, H315	Expert judgment
Eye Dam. 1, H318	Expert judgment
Skin Sens. 1, H317	Expert judgment
STOT RE 2, H373 (inhalation)	Expert judgment
Aquatic Chronic 3, H412	Expert judgment

Date of issue/Date of revision : 29/07/2016 Date of previous issue : No previous validation Version : 2 13/14

### **SECTION 16: Other information**

Full	text	of	abl	brev	iated	Н
etat	omo	nte				

H302 H312 H314 H315 H317 H318 H372 (respiratory tract) (inhalation) H373 (inhalation) H400 H410 H412	Harmful if swallowed. Harmful in contact with skin. Causes severe skin burns and eye damage. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. Causes damage to organs through prolonged or repeated exposure if inhaled. (respiratory tract) May cause damage to organs through prolonged or repeated exposure if inhaled. Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects. Harmful to aquatic life with long lasting effects.
--	--

## Full text of classifications [CLP/GHS]

11112	riammar to aquatio ino with long labiting offocio.
	ACUTE TOXICITY (oral) - Category 4 ACUTE TOXICITY (dermal) - Category 4 ACUTE AQUATIC HAZARD - Category 1 LONG-TERM AQUATIC HAZARD - Category 1 LONG-TERM AQUATIC HAZARD - Category 3 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category
Skin Corr. 1B, H314 Skin Irrit. 2, H315 Skin Sens. 1, H317 Skin Sens. 1A, H317 STOT RE 1, H372 (respiratory tract) (inhalation) STOT RE 2, H373 (inhalation)	1 SKIN CORROSION/IRRITATION - Category 1B SKIN CORROSION/IRRITATION - Category 2 SKIN SENSITIZATION - Category 1 SKIN SENSITIZATION - Category 1A SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (respiratory tract) (inhalation) - Category 1 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (inhalation) - Category 2

Date of printing

Date of issue/ Date of revision

: 29/07/2016: 29/07/2016

Date of previous issue

: No previous validation

Version : 2

### **Notice to reader**

The information in this Safety Data Sheet is based on the present state of knowledge and current legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications. The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions. As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with. The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation.

Date of issue/Date of revision : 29/07/2016 Date of previous issue : No previous validation Version : 2 14/14