

PRODUCT DATA

ALKALINE CLEANER/DEGREASER ND 14

DESCRIPTION

RUST-OLEUM® Alkaline Cleaner/Degreaser ND 14 is a concentrated, alkaline, non-flammable, virtually odour-free cleaning/degreasing solution.

RECOMMENDED USES

RUST-OLEUM Alkaline Cleaner/Degreaser ND 14 should be used to remove grease, oil, proteins dirt and many other surface contaminants from coated, mineral and steel substrates. RUST-OLEUM Alkaline Cleaner/Degreaser ND 14 should be applied with an artificial sponge, cloth or stiff nylon brush or broom. RUST-OLEUM Alkaline Cleaner/Degreaser ND 14 can also be used as an additive for high-pressure (steam) cleaning.

TECHNICAL DATA

VOC-content: 92 g/l

Coverage

Theoretical: 6 - 8 m²/l

Practical: Practical usage depends on many factors such as type and amount of contaminants, shape of the substrate and material losses during application. The content of the concentrated 5 litre packaging will allow you to treat a surface of 400 m², based on a dilution of 1:20.

DIRECTION FOR USE

To ensure homogeneity shake well before use.

Scrape or sweep away grease, oil, dirt, mould and all other surface contaminations as much as possible.

RUST-OLEUM Alkaline Cleaner/Degreaser ND 14 can be applied diluted or concentrated with a sponge, cloth, brush or broom. For normal cleaning a 3 - 5% concentration will be sufficient.

The product should be diluted with cold water. After use rinse with plenty of fresh water.

If a concentration of more than 5% is used, hot water rinsing is absolutely necessary.

As a high-pressure(steam) cleaning additive a 2% concentration is recommended.

After cleaning, remove any remaining water and allow the surface to dry, as moisture left on the surface or entrapped into pores may cause premature failure of the coating system.

Large surface areas or poor drying conditions may require longer drying times before a coating system can be applied.

APPLICATION CONDITIONS

Temperature of air, substrate and material between 5 and 35°C.

REMARKS

If used on galvanized steel, zinc, aluminum or anodized aluminum rinse the surface excessively.

SAFETY

Consult Safety Data Sheet and Safety Information printed on the can.

SHELLIFE / STORAGE CONDITIONS

2 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.

Rust-Oleum Netherlands B.V.
Braak 1, 4704 RJ
P.O. Box 138, 4700 AC
Roosendaal, The Netherlands
T +31 (0)165 593 636
F +31 (0)165 593 600
info@rust-oleum.eu
www.rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Halen, Belgium
T +32 (0)13 460 200
F +32 (0)13 460 201
info.be@ro-m.com
www.ro-m.com

Rust-Oleum France S.A.S
11, Rue Jules Verne, B.P. 60039
95322 St-Leu-la-Forêt Cedex
France
T +33 (0)1 30 40 00 44
F +33 (0)1 30 40 99 80
info.fr@ro-m.com
www.ro-m.com

Rust-Oleum UK Ltd.
Rotterdam House
116 Quayside
Newcastle
NE1 3DY
United Kingdom
T +44 (0)2476 717 329
F +44 (0)2476 718 930
info@rust-oleum.eu
www.rust-oleum.eu