

## PRODUCT DATA

## PEGAKOTE

### DESCRIPTION

2-component water dilutable epoxy coating.

### MAIN PROPERTIES

Very hard - exceptional abrasion resistance - resistant to oils and solvents.  
Solvent free, almost odourless and easy to clean.

### RECOMMENDED USES

For garages, warehouses, showrooms, corridors, indoor car parks, workshops, etc.  
Only for indoor works, as well for floors as for walls.

### TECHNICAL DATA

Appearance:	Semi-gloss (gloss 60°: ±50%)
Colour:	Standard colours + Mathymix / ColourShop
Density:	± 1,45 g/cm <sup>3</sup> (mixture)
Solids Content:	In volume: 48 - 50% In weight: 64 - 66%
Recommended film thickness:	Wet film: 200 micron (cons.: 300 g/m <sup>2</sup> ) Dry film: 100 micron (cons.: 300 g/m <sup>2</sup> )
Flashpoint:	Not flammable
Taber Abrasion:	Weight loss after 1000 cycles: ± 60 mg (CS10, load: 1000 g)
VOC-content:	0 g/l max.
Ready-for-use mixture:	10 g/l max.
Category:	A/j
EU Limit values:	140 g/l (2007) / 140 g/l (2010)

<b>Drying times</b>	20°C/60% r.h.
To touch:	9 hours. 18 - 20 hours for saturated and deep colours (base ED, TR, YE)
To recoat:	24 hours. At lower temperatures (8 - 10°C), this product can only be recoated after min. 48 hours.
Full hardness	7 days

### Coverage

Theoretical:	1st coat: 200 - 300 g/m <sup>2</sup> 2nd coat: 300 - 400 g/m <sup>2</sup>
Practical:	Practical coverage depends on many factors such as porosity and roughness of the substrate and material losses during application.

### SURFACE PREPARATION

The substrate should be dry and clean, free from ascending humidity and sufficiently coherent (tensile strength min. 6 kg/cm<sup>2</sup>).

Pegakote can be applied directly on most mineral substrates (f.i. old concrete, tiles, glass etc.). Curing compounds in case of poly-concrete have to be removed by means of sand or grit blasting. On new concrete or non-porous concrete, remove cement grout by sand or grit blasting, treatment with diluted hydrochloric acid at a ratio of 3 l hydrochloric acid to 10 l water or with Surfa-Etch 108. For these two last solutions, there is obligation to rinse abundantly and to allow drying through of the surfaces.

Porous substrates shall be impregnated with Pegakote diluted with 10 to 20% water.

Pegakote may not be applied on an elastic paint coat or a moving substrate.

**Rust-Oleum Netherlands B.V.**  
Braak 1, 4704 RJ  
P.O. Box 138, 4700 AC  
Roosendaal, The Netherlands  
T +31 (0)165 593 636  
F +31 (0)165 593 600  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)  
[www.rust-oleum.eu](http://www.rust-oleum.eu)

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Halen, Belgium  
T +32 (0)13 460 200  
F +32 (0)13 460 201  
[info.be@ro-m.com](mailto:info.be@ro-m.com)  
[www.ro-m.com](http://www.ro-m.com)

**Rust-Oleum France S.A.S**  
11, Rue Jules Verne, B.P. 60039  
95322 St-Leu-la-Forêt Cedex  
France  
T +33 (0)1 30 40 00 44  
F +33 (0)1 30 40 99 80  
[info.fr@ro-m.com](mailto:info.fr@ro-m.com)  
[www.ro-m.com](http://www.ro-m.com)

**Rust-Oleum UK Ltd.**  
Rotterdam House  
116 Quayside  
Newcastle  
NE1 3DY  
United Kingdom  
T +44 (0)2476 717 329  
F +44 (0)2476 718 930  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)  
[www.rust-oleum.eu](http://www.rust-oleum.eu)

## PRODUCT DATA

## PEGAKOTE

### DIRECTION FOR USE

To ensure homogeneity, coating materials should be thoroughly stirred prior to use. Stir the activator thoroughly using an electrical mixer at low speed. Add progressively under stirring to the base. Stir the mixture thoroughly until an even colour and consistency are obtained during min. 3 minutes. Temperature of the mixed materials should be at least 10°C.

### APPLICATION & THINNING

Brush:	If necessary, dilute with water.
Roller:	Dilute 1st coat with max. 10% water. Apply 2nd coat undiluted.
Air-atomised spray:	Not recommended.
Airless spray:	Nozzle: 015 - 017 / Pressure: 220 bars. 1st coat: dilute with 5 - 10% water. 2nd coat: dilute with max. 5% water.
Cleanup:	Water.

### APPLICATION CONDITIONS

Minimum 8°C and maximum 80% R.H.

### REMARKS

1. In order to become a solid gloss finish, please respect the consumption quantities of the second layer, this means that a tin of 4 kg has to be applied on a surface of 10 – 13 m<sup>2</sup>.
2. Always provide good air ventilation; so even when it rains, windows and doors have to be opened wherever possible.
3. The 2 components must be mixed under mechanical agitation.
4. Potlife after mixing component A and B: 2 hours.
5. For use on floors submitted to heavy abrasion, standard and medium colours are recommended. In case of deep and/or bright tones (red, yellow, orange, green, blue etc), it is advised to apply a clear topcoat.

### SAFETY

Consult Safety Data Sheet and Safety Information printed on the can.

### SHELLIFE / STORAGE CONDITIONS

2 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.

**Rust-Oleum Netherlands B.V.**  
Braak 1, 4704 RJ  
P.O. Box 138, 4700 AC  
Roosendaal, The Netherlands  
T +31 (0)165 593 636  
F +31 (0)165 593 600  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)  
[www.rust-oleum.eu](http://www.rust-oleum.eu)

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Halen, Belgium  
T +32 (0)13 460 200  
F +32 (0)13 460 201  
[info.be@ro-m.com](mailto:info.be@ro-m.com)  
[www.ro-m.com](http://www.ro-m.com)

**Rust-Oleum France S.A.S**  
11, Rue Jules Verne, B.P. 60039  
95322 St-Leu-la-Forêt Cedex  
France  
T +33 (0)1 30 40 00 44  
F +33 (0)1 30 40 99 80  
[info.fr@ro-m.com](mailto:info.fr@ro-m.com)  
[www.ro-m.com](http://www.ro-m.com)

**Rust-Oleum UK Ltd.**  
Rotterdam House  
116 Quayside  
Newcastle  
NE1 3DY  
United Kingdom  
T +44 (0)2476 717 329  
F +44 (0)2476 718 930  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)  
[www.rust-oleum.eu](http://www.rust-oleum.eu)