

MULTI LIGHT

GENERAL INFORMATION

Description

Ready mixed light weight multipurpose filler

Intended use

Interior

- Filling small holes and cracks
- Finishing substrate











PRODUCT ADVANTAGES

+ 3 in 1

Fills up to 8 mm

Easy to apply

Easy to sand

+ White



USE

DILUTION APPLICATION

Conditions

- n - t - n n h / - t t - n - n - u - t . u

Do not apply at temperatures of below +8°C or above +35°C, or at a relative humidity of above

70% H.R.

Ready mixed

Equipment Blade, filling knife.

Equipment cleaning With water before

With water before completely dry. Do not throw away into drains, dispose of this material and its container to an approved disposal contractor or taken to municipal collection point. Do not

dispose into the environment.

APPLICATION THICKNESS

8 mm

AVERAGE CONSUMPTION

SUBSTRATES

1,2L/m²/mm thickness

Concrete, cellular concrete, cement, brick,

plaster, plasterboard, gypsum board, glass cloth,

old painted substrates.

Substrates must be hard, cohesive, clean, sound

and dry according to the local standards.

OVERCOAT

Primer, interior conventional paint, light-weight wall coverings.

PRESTONETT



MULTI LIGHT

TECHNICAL DATA

COMPONANTS

Polymer base aqueous phase coat mix,

mineral fillers, additives.

DENSITY

 1.2 ± 0.1

pΗ

9 ± 1

COLOUR

White

WORKING TIME AT

20°C

Unlimited

WAITING TIME

BEFORE

OVERCOATING

Once completely dry

CLASSIFICATION

NFT 36 005 famille III, class 2

V.O.C

< 1 g/l (Ready mixed)

HEALTH AND SAFETY



Use in a well-ventilated place. Avoid direct contact with skin and eyes. Do not breathe

In case of prolonged contact, it is recommended to wear suitable gloves.

Safety data sheet available on

www.beissier.eu or www.quickfds.com

PACKAGING 10 L & 4 L bucket

STORAGE 12 months from date of manufacture, in

> unopened original packaging, protected from frost, heat (max. +30°C), sun and moisture. Close the packaging after each use.

This data sheet supersedes and replaces any prior sheet relating to the same product.

Date of issue: May 2022

The purpose of this data sheet is to inform our customers about our product's properties. The information presented in the sheet is based on the current state of our knowledge. However, this information is no substitute for a description pertaining specifically to the type and condition of the substrate concerned. Since technical progress is continuously being made, it is our customer's responsibility, prior to use, to check with us that updated edition of this sheet has not been issued.

