SAFETY DATA SHEET



1. Identification

Product identifier Extractables Mixture-525

Other means of identification

Item M-EM525B99

Recommended use For Laboratory Use Only

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company nameChem Service, Inc.
Address
660 Tower Lane

West Chester, PA 19380

United States

Telephone Toll Free 800-452-9994

Direct 610-692-3026

Website www.chemservice.com
E-mail info@chemservice.com

Emergency phone number Chemtrec US 800-424-9300

Chemtrec outside US +1 703-527-3887

2. Hazard(s) identification

Physical hazardsFlammable liquidsCategory 2Health hazardsSerious eye damage/eye irritationCategory 2A

Specific target organ toxicity, single exposure Category 3 narcotic effects

Environmental hazards Hazardous to the aquatic environment, acute Category 3

hazard

Hazardous to the aquatic environment,

long-term hazard

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Highly flammable liquid and vapor. Causes serious eye irritation. May cause drowsiness or

dizziness. Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

Precautionary statement

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly

closed. Ground/bond container and receiving equipment. Use explosion-proof

electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist or vapor. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear

Category 3

eye protection/face protection. Wear protective gloves/eye protection/face protection.

Response If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. If eye irritation persists: Get

medical advice/attention. In case of fire: Use appropriate media to extinguish.

Storage Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place.

Keep cool. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Material name: Extractables Mixture-525

Supplemental information

Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

99.88% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 99.88% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Acetone		67-64-1	>99
Pentachlorophenol		87-86-5	0.04
Bis(2-ethylhexyl)adipate		103-23-1	0.01
Bis(2-ethylhexyl)phthalate		117-81-7	0.01
Butyl benzyl phthalate		85-68-7	0.01
Diethyl phthalate		84-66-2	0.01
Dimethyl phthalate		131-11-3	0.01
Di-n-butyl phthalate		84-74-2	0.01
Hexachlorobenzene		118-74-1	0.01
Hexachlorocyclopentadiene		77-47-4	0.01

4. First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin contact

Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical

attention if irritation develops and persists.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Rinse mouth. Get medical attention if symptoms occur.

Most important

symptoms/effects, acute and

delayed

Ingestion

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

General information

Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Alcohol resistant foam. Water fog. Carbon dioxide (CO2). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. This liquid may accumulate static electricity when filling properly grounded containers. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions Specific methods

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Use standard firefighting procedures and consider the hazards of other involved materials.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Prevent product from entering drains. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Environmental precautions

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases. Use appropriate containment to avoid environmental contamination.

7. Handling and storage

Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist or vapor. Avoid contact with eyes. Avoid prolonged exposure. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

For additional information on equipment bonding and grounding, refer to the Canadian Electrical Code in Canada, (CSA C22.1), or the American Petroleum Institute (API) Recommended Practice 2003, "Protection Against Ignitions Arising out of Static, Lightning, and Stray Currents" or National Fire Protection Association (NFPA) 77, "Recommended Practice on Static Electricity" or National Fire Protection Association (NFPA) 70, "National Electrical Code".

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Eliminate sources of ignition. Avoid spark promoters. Ground/bond container and equipment. These alone may be insufficient to remove static electricity. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	
Acetone (CAS 67-64-1)	PEL	2400 mg/m3	
		1000 ppm	
Bis(2-ethylhexyl)phthalate (CAS 117-81-7)	PEL	5 mg/m3	
Dimethyl phthalate (CAS 131-11-3)	PEL	5 mg/m3	

HE OSHA Table 7	1 Limita far	Air Contominanto	(29 CFR 1910.1000)
US. USHA Table Z	1 Limits for	Air Contaminants	(29 CFR 1910.1000)

Components	Тур	e	Val	ue	
Di-n-butyl phthalate (CAS 84-74-2)	PE	-	5 m	ng/m3	
Pentachlorophenol (CAS 87-86-5)	PEI	-	0.5	mg/m3	
US. ACGIH Threshold Lin	nit Values				
Components	Тур	oe e	Val	ue	Form
Acetone (CAS 67-64-1)	STI	ΞL	750) ppm	
	TW	A	500) ppm	
Bis(2-ethylhexyl)phthalate (CAS 117-81-7)	TW	A	5 m	ng/m3	
Diethyl phthalate (CAS 84-66-2)	TW	A	5 m	ng/m3	
Dimethyl phthalate (CAS 131-11-3)	TW	A	5 m	ng/m3	
Di-n-butyl phthalate (CAS 84-74-2)	TW	A	5 m	ng/m3	
Hexachlorobenzene (CAS 118-74-1)	TW	A	0.0	02 mg/m3	
Hexachlorocyclopentadiene (CAS 77-47-4)	e TW	A	0.0	1 ppm	
Pentachlorophenol (CAS	STI	ΞL	1 m	ng/m3	Inhalable fraction and
87-86-5)					vapor.
87-86-5)	TW	A	0.5	mg/m3	•
US. NIOSH: Pocket Guide	e to Chemical Hazards	3		mg/m3	Inhalable fraction and
ŕ		3	0.5 Val	mg/m3	Inhalable fraction and
US. NIOSH: Pocket Guide	e to Chemical Hazards	s oe	Val	mg/m3 ue 0 mg/m3	Inhalable fraction and
US. NIOSH: Pocket Guide Components Acetone (CAS 67-64-1) Bis(2-ethylhexyl)phthalate	e to Chemical Hazards Тур	6 0 e A	Val 590 250	mg/m3	Inhalable fraction and
US. NIOSH: Pocket Guide Components Acetone (CAS 67-64-1)	e to Chemical Hazards Тур TW	s oe A EL	Val 590 250 10	mg/m3 ue) mg/m3) ppm	Inhalable fraction and
US. NIOSH: Pocket Guide Components Acetone (CAS 67-64-1) Bis(2-ethylhexyl)phthalate (CAS 117-81-7) Diethyl phthalate (CAS	e to Chemical Hazards Typ TW STI	A EL	Val 590 250 10	mg/m3 ue) mg/m3) ppm mg/m3	Inhalable fraction and
US. NIOSH: Pocket Guide Components Acetone (CAS 67-64-1) Bis(2-ethylhexyl)phthalate (CAS 117-81-7)	e to Chemical Hazards Typ TW STI	A A A A	Val 590 250 10 5 m	mg/m3 ue) mg/m3) ppm mg/m3 ng/m3	Inhalable fraction and
US. NIOSH: Pocket Guide Components Acetone (CAS 67-64-1) Bis(2-ethylhexyl)phthalate (CAS 117-81-7) Diethyl phthalate (CAS 84-66-2) Dimethyl phthalate (CAS	E to Chemical Hazards Typ TW STI	A A A A	Val 590 250 10 5 m 5 m	mg/m3 ue) mg/m3) ppm mg/m3 ng/m3 ng/m3	Inhalable fraction and
US. NIOSH: Pocket Guide Components Acetone (CAS 67-64-1) Bis(2-ethylhexyl)phthalate (CAS 117-81-7) Diethyl phthalate (CAS 84-66-2) Dimethyl phthalate (CAS 131-11-3) Di-n-butyl phthalate (CAS	TW STI TW TW TW TW TW TW	A EL A A A	Val 590 250 10 5 m 5 m	mg/m3 ue 0 mg/m3 0 ppm mg/m3 ng/m3 ng/m3	Inhalable fraction and
US. NIOSH: Pocket Guide Components Acetone (CAS 67-64-1) Bis(2-ethylhexyl)phthalate (CAS 117-81-7) Diethyl phthalate (CAS 84-66-2) Dimethyl phthalate (CAS 131-11-3) Di-n-butyl phthalate (CAS 84-74-2) Hexachlorocyclopentadiene	TW STI TW TW TW TW TW TW TW TW	A EL A A A	Val 590 250 10 5 m 5 m 5 m 0.1	mg/m3 ue 0 mg/m3 0 ppm mg/m3 ng/m3 ng/m3 ng/m3 ng/m3 ng/m3	Inhalable fraction and
US. NIOSH: Pocket Guide Components Acetone (CAS 67-64-1) Bis(2-ethylhexyl)phthalate (CAS 117-81-7) Diethyl phthalate (CAS 84-66-2) Dimethyl phthalate (CAS 131-11-3) Di-n-butyl phthalate (CAS 84-74-2) Hexachlorocyclopentadiene	TW STI TW TW TW TW TW TW	A EL A A A	Val 590 250 10 5 m 5 m 5 m 0.1	mg/m3 ue 0 mg/m3 0 ppm mg/m3 ng/m3 ng/m3 ng/m3 ng/m3 ng/m3	Inhalable fraction and
US. NIOSH: Pocket Guide Components Acetone (CAS 67-64-1) Bis(2-ethylhexyl)phthalate (CAS 117-81-7) Diethyl phthalate (CAS 84-66-2) Dimethyl phthalate (CAS 131-11-3) Di-n-butyl phthalate (CAS 84-74-2) Hexachlorocyclopentadiene (CAS 77-47-4) Pentachlorophenol (CAS	TW STI TW TW TW TW TW TW TW TW	A EL A A A	Val 590 250 10 5 m 5 m 5 m 0.1	mg/m3 ue 0 mg/m3 0 ppm mg/m3 ng/m3 ng/m3 ng/m3 ng/m3 ng/m3	Inhalable fraction and
US. NIOSH: Pocket Guide Components Acetone (CAS 67-64-1) Bis(2-ethylhexyl)phthalate (CAS 117-81-7) Diethyl phthalate (CAS 84-66-2) Dimethyl phthalate (CAS 131-11-3) Di-n-butyl phthalate (CAS 84-74-2) Hexachlorocyclopentadiene (CAS 77-47-4) Pentachlorophenol (CAS 87-86-5)	TW	A EL A A A	Val 590 250 10 5 m 5 m 5 m 0.1	mg/m3 ue 0 mg/m3 0 ppm mg/m3 ng/m3 ng/m3 ng/m3 ng/m3 ng/m3	Inhalable fraction and

^{* -} For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

Hexachlorobenzene (CAS 118-74-1) Pentachlorophenol (CAS 87-86-5) Can be absorbed through the skin. Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Hexachlorobenzene (CAS 118-74-1)

Skin designation applies.

US - Tennessee OELs: Skin designation

Pentachlorophenol (CAS 87-86-5)

Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

Hexachlorobenzene (CAS 118-74-1) Can be absorbed through the skin. Pentachlorophenol (CAS 87-86-5) Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

Pentachlorophenol (CAS 87-86-5) Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Pentachlorophenol (CAS 87-86-5) Can be absorbed through the skin.

Appropriate engineering

controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station. Eye wash fountain and emergency showers are recommended.

Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove

Individual protection measures, such as personal protective equipment

Eye/face protection

Hand protection

Chemical respirator with organic vapor cartridge and full facepiece.

Skin protection

Other

supplier.

Wear suitable protective clothing. Chemical respirator with organic vapor cartridge and full facepiece. Respiratory protection

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Liquid. **Form** Liquid.

Not available. Color Not available. Odor Not available. Odor threshold Not available. pН

-138.46 °F (-94.7 °C) estimated Melting point/freezing point Initial boiling point and boiling 132.89 °F (56.05 °C) estimated

range

Flash point -4.0 °F (-20.0 °C) estimated

Evaporation rate Not available. Flammability (solid, gas) Not applicable. Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit - upper

(%)

Not available.

Not available. Explosive limit - lower (%) Explosive limit - upper (%) Not available.

308.63 hPa estimated Vapor pressure

Vapor density Not available. Not available. Relative density

Solubility(ies)

Solubility (water) Not available. Not available. Partition coefficient

(n-octanol/water)

Auto-ignition temperature 869 °F (465 °C) estimated

Decomposition temperature Not available. **Viscosity** Not available.

Other information

Density 0.79053 g/cm3 estimated

Explosive properties Not explosive.

Flammability class Flammable IB estimated

Oxidizing properties

Percent volatile

Specific gravity

VOC (Weight %)

Not oxidizing.

99.89 % estimated

0.79 estimated

99.89 % estimated

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

Toxic gas.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be

harmful.

Skin contact No adverse effects due to skin contact are expected.

Eye contact Causes serious eye irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Headache. May cause drowsiness and dizziness. Nausea, vomiting. Severe eye irritation.

Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Information on toxicological effects

Acute toxicity Narcotic effects.

Components	Species	Test Results
Acetone (CAS 67-64-1)		
<u>Acute</u>		
Dermal		
LD50	Guinea pig	> 7426 mg/kg, 24 Hours
		> 9.4 ml/kg, 24 Hours
	Rabbit	> 7426 mg/kg, 24 Hours
		> 9.4 ml/kg, 24 Hours
Inhalation		
Vapor		
LC50	Rat	55700 ppm, 3 Hours
		132 mg/l, 3 Hours
LC50	Rat	76 mg/l, 4 Hours
Vapor		
LC50	Rat	50.1 mg/l
LC50	Rat	50.1 mg/l, 8 Hours
Oral		
LD50	Mouse	5.2 g/kg

Components	Species	Test Results
	Rat	5800 mg/kg
		2.2 ml/kg
Bis(2-ethylhexyl)adipate (C	AS 103-23-1)	•
<u>Acute</u>	,	
Inhalation		
Aerosol		
LC50	Rat	> 5.7 mg/l, 4 Hours
Oral		
LD50	Mouse	15000 mg/kg
	Rat	22500 mg/kg
		5.6 g/kg
Bis(2-ethylhexyl)phthalate	(CAS 117-81-7)	
<u>Acute</u>		
Dermal		
LD50	Guinea pig	10 g/kg
	Rabbit	25 g/kg
		20 ml/kg, 24 Hours
Oral		
LD50	Guinea pig	26.3 g/kg
	Mouse	> 30 g/kg
	Rabbit	33.9 g/kg
	Rat	> 25 g/kg
Butyl benzyl phthalate (CA	S 85-68-7)	
Acute	·	
Dermal		
LD50	Mouse	6700 mg/kg
	Rat	6700 mg/kg
Oral		
LD50	Mouse	4170 mg/kg
	Rat	2330 mg/kg
Diethyl phthalate (CAS 84-	66-2)	
<u>Acute</u>		
Dermal		
LD50	Rat	> 22400 mg/kg
		> 10 ml/kg, 24 Hours
Inhalation		
LC50	Rat	> 4.64 mg/l, 6 Hours
Oral		
LD50	Rat	> 5 ml/kg
		9500 - 31000 mg/kg
Dimethyl phthalate (CAS 1	31-11-3)	
<u>Acute</u>		
Dermal		
LD50	Rabbit	> 12000 mg/kg
	Rat	38000 mg/kg
Oral		
LD50	Guinea pig	2900 mg/kg
	Hen	10200 mg/kg

components	Species	Test Results
	Mouse	8600 mg/kg
	Rabbit	5300 mg/kg
	Rat	8200 mg/kg
i-n-butyl phthalate (CAS 84	-74-2)	
<u>Acute</u>	,	
Dermal		
LD50	Rabbit	4200 mg/kg
		20 ml/kg
Inhalation		
LC50	Mouse	25 mg/l, 2 Hours
Aerosol		
LC50	Rat	>= 15.68 mg/l, 4 Hours
Oral		
LD50	Guinea pig	10000 mg/kg
	Mouse	4840 mg/kg
	Rat	6279 mg/kg
lexachlorobenzene (CAS 1	18-74-1)	
<u>Acute</u>		
Oral	_	
LD50	Cat	1700 mg/kg
	Mouse	4000 mg/kg
	Rabbit	2600 mg/kg
	Rat	3500 mg/kg
exachlorocyclopentadiene	(CAS 77-47-4)	
<u>Acute</u>		
Dermal		
LD50	Rabbit	340 mg/kg
Inhalation		0.0000 # 0.511
LC50	Guinea pig	0.0802 mg/l, 3.5 Hours
	Rat	0.0181 mg/l, 4 Hours
Oral	All	000 000
LD50	Albino rat	300 - 630 mg/kg
entachlorophenol (CAS 87-	-86-5)	
Acute Dormal		
Dermal LD50	Rat	96 mg/kg
	Nat	30 mg/kg
Oral LD50	Rat	146 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

Bis(2-ethylhexyl)adipate (CAS 103-23-1) 3 Not classifiable as to carcinogenicity to humans.

Bis(2-ethylhexyl)phthalate (CAS 117-81-7)

2B Possibly carcinogenic to humans.

Butyl benzyl phthalate (CAS 85-68-7)

3 Not classifiable as to carcinogenicity to humans.

Hexachlorobenzene (CAS 118-74-1)

2B Possibly carcinogenic to humans.
Pentachlorophenol (CAS 87-86-5)

2B Possibly carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens

Bis(2-ethylhexyl)phthalate (CAS 117-81-7)

Reasonably Anticipated to be a Human Carcinogen.

Hexachlorobenzene (CAS 118-74-1)

Reasonably Anticipated to be a Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

May cause drowsiness and dizziness.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

Components		Species	Test Results
Acetone (CAS 67-64-1)		
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	10294 - 17704 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	4740 - 6330 mg/l, 96 hours
Bis(2-ethylhexyl)adipat	te (CAS 103-23-1)		
Aquatic			
Fish	LC50	Bluegill (Lepomis macrochirus)	0.48 - 0.85 mg/l, 96 hours
Bis(2-ethylhexyl)phtha	late (CAS 117-81-7	")	
Aquatic			
Crustacea	EC50	Water flea (Daphnia pulex)	0.133 mg/l, 48 hours
Fish	LC50	Bluegill (Lepomis macrochirus)	> 0.2 mg/l, 96 hours
			> 0.2 mg/l, 96 hours
Butyl benzyl phthalate	(CAS 85-68-7)		
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	> 0.96 mg/l, 48 hours
Fish	LC50	Shiner perch (Cymatogaster aggregata)	0.47 - 0.56 mg/l, 96 hours
Diethyl phthalate (CAS	8 84-66-2)		
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	86 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	12 mg/l, 96 hours
Dimethyl phthalate (CA	AS 131-11-3)		
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	45.9 mg/l, 48 hours
Fish	LC50	Sheepshead minnow (Cyprinodon variegatus)	29 mg/l, 96 hours
Di-n-butyl phthalate (C	AS 84-74-2)		
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	2.99 mg/l, 48 hours
Fish	LC50	Channel catfish (Ictalurus punctatus)	0.4 - 0.53 mg/l, 96 hours

Material name: Extractables Mixture-525

SDS US

Components **Species Test Results**

Hexachlorobenzene (CAS 118-74-1)

Aquatic

Fish LC50 Bluegill (Lepomis macrochirus) > 1 mg/l, 96 hours

Hexachlorocyclopentadiene (CAS 77-47-4)

Aquatic

LC50 Fathead minnow (Pimephales promelas) 0.007 mg/l, 96 hours Fish

Pentachlorophenol (CAS 87-86-5)

Aquatic

Crustacea EC50 Water flea (Daphnia magna) 0.273 - 0.375 mg/l, 48 hours Fish LC50 Atlantic salmon (Salmo salar) 0.042 - 0.083 mg/l, 96 hours

No data is available on the degradability of this product. Persistence and degradability

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Acetone	-0.24
Bis(2-ethylhexyl)phthalate	7.6
Butyl benzyl phthalate	4.91
Diethyl phthalate	2.47
Dimethyl phthalate	1.6
Di-n-butyl phthalate	4.9
Hexachlorobenzene	5.73
Hexachlorocyclopentadiene	3.99
Pentachlorophenol	5.12

No data available. Mobility in soil

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow

this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches

with chemical or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

UN number UN1090

UN proper shipping name

Transport hazard class(es)

Acetone, solution

Class 3 Subsidiary risk _ 3 Label(s) **Packing group** Ш

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions IB2, T4, TP1

150 Packaging exceptions 202 Packaging non bulk Packaging bulk 242

^{*} Estimates for product may be based on additional component data not shown.

IATA

UN1090 **UN number**

UN proper shipping name Acetone solution

Transport hazard class(es)

Class 3 Subsidiary risk П Packing group **Environmental hazards** No. ЗН **ERG Code**

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Allowed.

Allowed. Cargo aircraft only

IMDG

UN1090 **UN** number

UN proper shipping name ACETONE (ACETONE SOLUTIONS)

Not established.

Transport hazard class(es)

3 **Class** Subsidiary risk Ш Packing group **Environmental hazards**

Marine pollutant No. F-E. S-D **EmS**

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

DOT



IATA; IMDG



15. Regulatory information

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication US federal regulations

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

TSCA Chemical Action Plans, Chemicals of Concern

Bis(2-ethylhexyl)phthalate (CAS 117-81-7) Phthalates Action Plan Butyl benzyl phthalate (CAS 85-68-7) Phthalates Action Plan Diethyl phthalate (CAS 84-66-2) Phthalates Action Plan

Dimethyl phthalate (CAS 131-11-3) Phthalates Action Plan Di-n-butyl phthalate (CAS 84-74-2) Phthalates Action Plan

CERCLA Hazardous Substance List (40 CFR 302.4)

Acetone (CAS 67-64-1) Listed. Bis(2-ethylhexyl)phthalate (CAS 117-81-7) Listed. Butyl benzyl phthalate (CAS 85-68-7) Listed. Diethyl phthalate (CAS 84-66-2) Listed. Dimethyl phthalate (CAS 131-11-3) Listed. Di-n-butyl phthalate (CAS 84-74-2) Listed. Hexachlorobenzene (CAS 118-74-1) Listed. Hexachlorocyclopentadiene (CAS 77-47-4) Listed. Pentachlorophenol (CAS 87-86-5) Listed.

SARA 304 Emergency release notification

Hexachlorocyclopentadiene (CAS 77-47-4) **10 LBS** US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Immediate Hazard - Yes **Hazard categories**

Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

CAS number Chemical name Reportable **Threshold** Threshold **Threshold** quantity planning quantity planning quantity, planning quantity, lower value upper value 77-47-4

Hexachlorocyclopenta

10

100 lbs

diene

SARA 311/312 Hazardous No

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Bis(2-ethylhexyl)phthalate (CAS 117-81-7)

Dimethyl phthalate (CAS 131-11-3)

Di-n-butyl phthalate (CAS 84-74-2)

Hexachlorobenzene (CAS 118-74-1)

Hexachlorocyclopentadiene (CAS 77-47-4)

Pentachlorophenol (CAS 87-86-5)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and **Chemical Code Number**

Acetone (CAS 67-64-1) 6532

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

35 %WV Acetone (CAS 67-64-1)

DEA Exempt Chemical Mixtures Code Number

Acetone (CAS 67-64-1) 6532

US state regulations

US - New Jersey RTK - Substances: Listed substance

Acetone (CAS 67-64-1)

Bis(2-ethylhexyl)adipate (CAS 103-23-1)

Bis(2-ethylhexyl)phthalate (CAS 117-81-7)

Butyl benzyl phthalate (CAS 85-68-7)

Diethyl phthalate (CAS 84-66-2)

Dimethyl phthalate (CAS 131-11-3)

Material name: Extractables Mixture-525

Di-n-butyl phthalate (CAS 84-74-2)

Hexachlorobenzene (CAS 118-74-1)

Hexachlorocyclopentadiene (CAS 77-47-4)

Pentachlorophenol (CAS 87-86-5)

US - Pennsylvania RTK - Hazardous Substances: Special hazard

Bis(2-ethylhexyl)phthalate (CAS 117-81-7)

Hexachlorobenzene (CAS 118-74-1)

Pentachlorophenol (CAS 87-86-5)

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

(a))

Acetone (CAS 67-64-1)

Bis(2-ethylhexyl)adipate (CAS 103-23-1)

Bis(2-ethylhexyl)phthalate (CAS 117-81-7)

Butyl benzyl phthalate (CAS 85-68-7)

Diethyl phthalate (CAS 84-66-2)

Dimethyl phthalate (CAS 131-11-3)

Di-n-butyl phthalate (CAS 84-74-2)

US. Massachusetts RTK - Substance List

Acetone (CAS 67-64-1)

Bis(2-ethylhexyl)adipate (CAS 103-23-1)

Bis(2-ethylhexyl)phthalate (CAS 117-81-7)

Butyl benzyl phthalate (CAS 85-68-7)

Diethyl phthalate (CAS 84-66-2)

Dimethyl phthalate (CAS 131-11-3)

Di-n-butyl phthalate (CAS 84-74-2)

Hexachlorobenzene (CAS 118-74-1)

Hexachlorocyclopentadiene (CAS 77-47-4)

Pentachlorophenol (CAS 87-86-5)

US. New Jersey Worker and Community Right-to-Know Act

Bis(2-ethylhexyl)phthalate (CAS 117-81-7)

Butyl benzyl phthalate (CAS 85-68-7)

Diethyl phthalate (CAS 84-66-2)

Dimethyl phthalate (CAS 131-11-3)

Di-n-butyl phthalate (CAS 84-74-2)

Hexachlorobenzene (CAS 118-74-1)

Hexachlorocyclopentadiene (CAS 77-47-4)

Pentachlorophenol (CAS 87-86-5)

US. Pennsylvania RTK - Hazardous Substances

Acetone (CAS 67-64-1)

Bis(2-ethylhexyl)adipate (CAS 103-23-1)

Bis(2-ethylhexyl)phthalate (CAS 117-81-7)

Butyl benzyl phthalate (CAS 85-68-7)

Diethyl phthalate (CAS 84-66-2)

Dimethyl phthalate (CAS 131-11-3)

Di-n-butyl phthalate (CAS 84-74-2)

Hexachlorobenzene (CAS 118-74-1)

Hexachlorocyclopentadiene (CAS 77-47-4)

Pentachlorophenol (CAS 87-86-5)

US. Pennsylvania Worker and Community Right-to-Know Law

Acetone (CAS 67-64-1)

Bis(2-ethylhexyl)adipate (CAS 103-23-1)

Bis(2-ethylhexyl)phthalate (CAS 117-81-7)

Butyl benzyl phthalate (CAS 85-68-7)

Diethyl phthalate (CAS 84-66-2)

Dimethyl phthalate (CAS 131-11-3)

Di-n-butyl phthalate (CAS 84-74-2)

Hexachlorobenzene (CAS 118-74-1)

Hexachlorocyclopentadiene (CAS 77-47-4)

Pentachlorophenol (CAS 87-86-5)

US. Rhode Island RTK

Acetone (CAS 67-64-1)

Bis(2-ethylhexyl)phthalate (CAS 117-81-7) Butyl benzyl phthalate (CAS 85-68-7) Diethyl phthalate (CAS 84-66-2) Dimethyl phthalate (CAS 131-11-3) Di-n-butyl phthalate (CAS 84-74-2)

Hexachlorobenzene (CAS 118-74-1) Hexachlorocyclopentadiene (CAS 77-47-4)

Pentachlorophenol (CAS 87-86-5)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Bis(2-ethylhexyl)phthalate (CAS 117-81-7) Listed: January 1, 1988 Hexachlorobenzene (CAS 118-74-1) Listed: October 1, 1987 Pentachlorophenol (CAS 87-86-5) Listed: January 1, 1990

US - California Proposition 65 - CRT: Listed date/Developmental toxin

Bis(2-ethylhexyl)phthalate (CAS 117-81-7) Listed: October 24, 2003 Butyl benzyl phthalate (CAS 85-68-7) Listed: December 2, 2005 Di-n-butyl phthalate (CAS 84-74-2) Listed: December 2, 2005 Hexachlorobenzene (CAS 118-74-1) Listed: January 1, 1989

US - California Proposition 65 - CRT: Listed date/Female reproductive toxin

Di-n-butyl phthalate (CAS 84-74-2) Listed: December 2, 2005

US - California Proposition 65 - CRT: Listed date/Male reproductive toxin

Bis(2-ethylhexyl)phthalate (CAS 117-81-7) Listed: October 24, 2003 Di-n-butyl phthalate (CAS 84-74-2) Listed: December 2, 2005

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other information, including date of preparation or last revision

Issue date 10-17-2014 09-02-2016 **Revision date**

Version # 02

NFPA ratings Health: 2

Flammability: 3 Instability: 0

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Disclaimer

The above information is believed to be correct on the date it was last revised and must not be considered all inclusive. The information has been obtained only by a search of available literature and is only a guide for handling the chemicals. OSHA regulations require that if other hazards become evident, an upgraded SDS must be made available to the employee within three months. RESPONSIBILITY for updates lies with the employer and not with CHEM SERVICE, Inc.

Persons not specifically and properly trained should not handle this chemical or its container. This product is furnished FOR LABORATORY USE ONLY! Our products may NOT BE USED as drugs, cosmetics, agricultural or pesticide products, food additives or as household chemicals.

This Safety Data Sheet (SDS) is intended only for use with Chem Service, Inc. products and should not be relied on for use with materials from any other supplier even if the chemical name(s) on the product are identical! Whenever using an SDS for a solution or mixture the user should refer to the SDS for every component of the solution or mixture. Chem Service warrants that this SDS is based upon the most current information available to Chem Service at the time it was last revised. THIS WARRANTY IS EXCLUSIVE, AND CHEM SERVICE, INC. MAKES NO OTHER WARRANTY, EXPRESSED OR IMPLIED, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE. This SDS is provided gratis and CHEM SERVICE, INC. SHALL NOT BE LIABLE FOR ANY INCIDENTAL, CONSEQUENTIAL OR CONTINGENT DAMAGES.

Copyright © 2000-2014 Chem Service, Inc. All rights reserved except that this SDS may be printed for the use of a customer or prospective customer of Chem Service, Inc provided the entire SDS is printed. The SDS may not be placed in any database or otherwise stored or distributed in electronic or any other form.

This product is furnished FOR LABORATORY USE ONLY.

Revision Information

This document has undergone significant changes and should be reviewed in its entirety.