HOW TO INSTALL ELITE PVC PANEL KITS

#4 Install
Cap Trim

#3 Install
UpperRail

#2 Install 22" high corners
for 36" high railings
OR
28" high corners
for 42" high railings

#1 Install Lower
Rail assembly

Step 3: Fasten the Upper Rail, be sure to butt up against pre-made corners.

Step 4: Cut and Fasten the Cap Trim.

Step 5: The final finishing touches, fill all gaps with exterior caulking and paint with exterior paint. Preferably alkaloid or oil base paint.

Note: the corners trims are 22" high making the entire paneled section 38 ¼" high to accommodate 36" high Railings. For the optional taller system, the corners trims are 28" high making the entire paneled section 44 ¼" high to accommodate 42" high Railings

Our Universal PVC panel kits can be installed on columns 6 to 10" square. They can be nailed, pined or glued to either a wood, fiberglass or PVC column shaft. Be sure to use the right adhesive to suite the application. All the trims that run horizontally are shipped in 4' lengths. They are to be cut down on site. Important note: Do not assume that your shaft is square, measure each side before cutting.

To start, confirm that you have all the parts shown below.

To start: if installing railings, confirm the overall height that you will need and dry fit all the parts to confirm that all the trims will fit.

Step 1: Start working up from the bottom to the top. Cut width and fasten the upper rail to the shaft.

Step 2: Fasten the 4 pre-glued corner trims.

