

# BIO LUBE AT FG

**Overview:** BioLube AT FG is a readily biodegradable, food grade compressed air line and pneumatic equipment lubricant and is NSF registered as meeting the guidelines of an H1 product for incidental food contact. Its vegetable base oil virtually eliminates petroleum hydrocarbons and VOCs, while its anti-misting, de-gumming and lubricity additives provide maximum performance and equipment protection.

## Specifications, Approvals, Recommendations:

- NSF H1 Food Grade Lubricant
- USDA BioPreferred Program

Physical Properties	AT FG
ISO Grade	22
Specific Gravity, ASTM D1298	.91
Viscosity, ASTM D445 @40°C, cSt	22
Viscosity, ASTM D445 @100°C, cSt	5
Viscosity Index (VI), ASTM D2270	>188
Pour Point, ASTM D97, °F (°C)	0 (-18)
Flash Point, ASTM D92, °F (°C)	>400 (204)
Copper Corrosion, ASTM D4048	1A
Rust Test, ASTM D665, A	PASS
Biodegradability, OECD 301B, %	>85

## Features & Benefits:

- Unique combination of **Biodegradability** certification and **Food Grade** certification
- Primary use is in food processing and food packaging plants
- Natural detergency and de-gumming additives keep systems and tools clean
- Advanced rust and corrosion protection
- Contributes virtually no VOC's to the workplace

