NE-960

Wet Location Two Head Emergency w/Remote

Lamp: 2 x 6W Lamp

PRODUCT DESCRIPTION

Dual adjustable round head emergency light with 120V/277V input. A heavy duty housing completely seals all electrical components and connections from water spary, splash, and corrosive atmosphere. During power outages, the dual incandescent round heads will provides 90 minutes of light on fully charged battery power.

FEATURES

- 120V or 277V dual input
- · 2 x 6 Watt incandescent lamps included
- · Automatically activates during power loss
- · High Impact Injection molded thermoplastic ABS housing

HOUSING

High Impact Injection molded thermoplastic ABS housing.

FACE

Two fully adjustable glare-free round heads for T5 light source

ANGLE ADJUSTMENT

Wall (mounting hardware included)

ELECTRICAL

VOLTAGE

Input: Dual 120V/277V Automatic solid state switching and charging (automatic reset). Quick wire connection - no extra hardware necessary.

LAMPS

2 x 6 Watt DC T5 wedge base lamps (included) Emergency Light Fixtures: Two adjustable glare-free light heads with positive positioning lock Can operate 2 x 10W lamps if no remotes are connected

BATTERY

Replaceable 90-minute, 6V, 4.5Ah lead-calcium (NEB-6V-4.5) maintenance free battery for backup operation during power loss (9-10 months of shelf life). Internal solid state charging circuit

REMOTE

NE-960 may operate 2 x 6W remote heads at a maximum distance of 15 feet.

TESTING

High charge / ready operation indicator light with test button and automatic reset

CIRCUITRY PROTECTION

Short circuit protection (Disconnect for deep discharge).

OPERATING TEMPERATURE

32°F ~ 104°F (10°C ~ 40°C)

OPERATING LIFE EXPECTANCY


4 Years



Wet Location Two Head Emergency w/Remote

Catalog No.

NE-960





CNORALIGHTING.


Туре

Proiect

Catalog No.

Lamp/Wattage

DIMENSIONS



LABELS AND LISTINGS

UL Listed for Wet Location NFC NEMA-4X NFPA State & Municipal

ACCESSORIES

NEB-9V-4.5:

Replacement 6V 4.5Ah 90-minute Battery

