NTH-697 (Line Voltage Track) Line Voltage Gimbal Ring

Lamp: 50W Halogen GU10 MR16

PRODUCT DESCRIPTION

Line voltage die cast aluminum designer cube fixtures with MR16 light source. Yoke provides full adjustment of light source for special aiming and dual tightening knobs assure secure lock on angle position.

FEATURES

- · Die cast aluminum provies superior strength and rigidity.
- · Low profile, aesthetic design.
- · Adjustable yoke for custom aiming.
- · Clear shield included with fixture.
- · High-strength stainless steel electrical contacts.
- One or two circuit track capable.

CONSTRUCTION

Contact Head Assembly

Three .030 stainless steel contacts mounted in high heat rated plastic housing

Gimbal Ring

.030 Baked enamel finished steel ring. High-tension stainless steel spring secures MR16 light source.

"L" Bracket Mount

0.85 Rigid steel yoke connects fixture housing to electrical contact head. Dual plastic angle tightening knobs maintain clean, decorative appearance of the fixture and provides secure angle position.

Lamp Shield

High temperature glass shield included.

ELECTRICAL SYSTEM

Wiring - Teflon coated wire lead connects socket and housing to electrical contact head.

Teflon coating is durable and resists heat degradation from lamp and housing radiation.

Socket

Porcelain socket for GU10 MR16 lamp.

Lamp

One 50W MR16 Halogen Lamp (Included).

One/Two Circuit Conversion

Positive contact (opposite neutral and ground contacts) is preset to "down" position at factory but may be raised to the higher position to install onto the second circuit of Nora Lighting NT- 2300 series two-circuit track.


FINISHES

Black, Silver, and White heat rated baked enamel paint. Custom painting or anodizing for special applications is also available. Custom finishes will require lead times that vary depending on vendor schedule. Please consult factory for quotation, and provide either a Dunn Edwards number or color chip for exact matching.

ENORALIGHTING.

Type
Project
Catalog No.
Lamp/Wattage

DIMENSIONS



Diameter: 2-5/8" Length: 2-1/8" Max. Extension: 4-7/8"

OPTIONAL ACCESSORIES

NM-100/MR16 MR16 Filter (Blue, Clear, Frosted, Green, Linear, Pink, Red, Spread, Yellow)

LABELS AND LISTINGS

UL Listed as track lighting fitting.



Gimbal Ring Line Voltage Track

annous tring and voltage track			
Catalog No.	Min Max. Wattage	Finishes	Style
NTH-697	(Blank) = 50W	$\mathbf{B} = Black$	Blank = H-Style
		S = Silver	J = J-Style
		$\mathbf{W} = \mathbf{W}$ hite	L = L-Style

Create a complete track head number: Example: NTL-697B

