

# NTLE-213 Low Voltage Track

## Versa Wireback w/ Dimmable Integral Electronic Driver/Transformer, LED compatible

Lamp: 3W-50W MR16

### PRODUCT DESCRIPTION

Low voltage die cast aluminum designer MR16 fixtures with round wire mesh face. Compatible with several LED MR16 lamps as well as halogen MR16 lamps, with integral transformer/driver. Single stem conceals wiring and provides full adjustment of light source for special aiming. Dual tightening knobs assure secure lock on vertical angle position! internal friction provides secure lateral lamp position.

### FEATURES

- Compatible with several LED MR16 Lamps or halogen MR16 lamps (not included)
- Die cast aluminum rear body provides superior strength and rigidity.
- Low profile, aesthetic design
- Adjustable stem for custom aiming
- High-strength stainless steel electrical contacts
- One or two circuit track capable

### CONSTRUCTION

#### Housing

Main body consists of .025 wire screen cone terminating at a .025 finishing trim. Small end of cone allows for screw attachment to rear body of fixture. Rear portion of fixture is constructed of .090 die cast aluminum with vented rear providing design feature and heat dissipation and escape.

#### Stem

.065 Die cast aluminum stem connects fixture housing to electrical contact head. Lead wire is completely concealed from view within stem. Dual plastic angle tightening knobs maintain clean, decorative appearance of the fixture and provide secure angle position.

#### Transformer

Solid state LED Driver provide noise-free voltage reduction and operation. If dimming, use electronic low voltage rated only dimming controls.

NTLE-213

Integral Unit - 120V/60Hz Input; 12V Output; 60VA Max. Load

#### Socket

Porcelain socket for GU5.3 12V MR16 lamp.

#### Lamp

MR16 LED compatible

3W- 50W max 12V MR16 Halogen or LED Lamp (Ordered Separately).

*\*MR16 Wireback fixture does not accept clear shield. Please use lamps that are inherently shielded.*

#### Contact Head Assembly

Three .030 stainless steel contacts mounted in high heat rated plastic housing.

# NORALIGHTING.

Type


Project

Catalog No.

Lamp/Wattage

### DIMENSIONS

#### NTLE-213



LED Driver (0W-60W)

Length: 3" Dia.: 2-7/8", Max Ext.: 6"

#### One/Two Circuit Conversion

Positive contact (opposite neutral and ground contacts) is preset to "down" position at factory, but may be raised to the higher position to install onto the second circuit of Nora Lighting NT-2300 series two-circuit track.

#### Compatibility

Nora track fixtures are interchangeable with Halo, Catalina, Hampton Bay, Halo-Edison, or any other brands configured to Halo track system design. Note: fixtures may not be compatible with non-Nora transformers or monopoint adapters.

#### Labels and Listings

cULus Listed



For a list of compatible LED MR16 lamps please refer to "Compatibility" tab under the "Resources" tab of the Nora web site.

### Low Volt Track head

Catalog No.	Finish
NTLE-213	B = Black
	BZ = Bronze
	NM = Natural Metal
	W = White

Create a complete Item number: Example: NTLE-207B

# NORALIGHTING.

6505 Gayhart St., Commerce, CA 90040 • Phone: 800.686.6672 • FAX: 800.500.9955 • [www.noralighting.com](http://www.noralighting.com)  
e-mail: [nora@noralighting.com](mailto:nora@noralighting.com) • Specifications subject to change without notice. © 2011