

NTLE-214 Low Voltage Track

Versa Roundbackw/ Dimmable Integral Electronic Driver/Transformer, LED compatible

Lamp: 3W-50W MR16

NORALIGHTING.

Type _____

Project _____

Catalog No. _____

Lamp/Wattage _____

PRODUCT DESCRIPTION

Low voltage designer round back fixtures with integral transformer/driver. Compatible with several LED MR16 lamps as well as halogen MR16 lamps. Die cast black baffle insert reduces glare and provides finished appearance. Heavy-duty yoke provides low profile support and full aiming for fixture. Dual tightening knobs assure secure lock on vertical angle position; internal friction provides secure lateral lamp position.

FEATURES

- Compatible with several LED MR16 Lamps or halogen MR16 lamps (not included)
- Die cast baffle insert.
- Low profile, aesthetic design.
- Adjustable yoke for custom aiming.
- Clear shield included with fixture.
- High-strength stainless steel electrical contacts.
- One or two circuit track capable.

CONSTRUCTION

Contact Head Assembly

Three .030 stainless steel contacts mounted in high heat rated plastic housing.

Housing

.030 drawn steel construction; cylindrical shape with ventilated rear for enhanced design, heat dissipation, and wire exit. .070 die cast aluminum baffle insert, eliminates side glare from fixture, and hold MR16 lamp source and clear shield.

Yoke

.085 Rigid steel yoke connects fixture housing to electrical contact head. Dual plastic angle tightening knobs maintain clean, decorative appearance of the fixture and provides secure angle position.

Socket

Porcelain socket for GU5.3 12V MR16 lamp.

Lamp

3W-50W Max 12V MR16 Halogen or LED Lamp (Ordered Separately).
MR16 LED compatible

Electrical System

1. **Transformer** – Solid state LED Driver provides noise-free voltage reduction and operation. If dimming, use electronic low voltage rated only dimming controls.


NTLE-214:

Integral Unit - NTL-214: 120V/60Hz Input; 12V Output; 60VA Max. Load

2. **Wiring** - Teflon coated wire lead connects socket and housing to electrical contact head. Teflon coating is durable and resists heat degradation from lamp and housing radiation.

DIMENSIONS

NTLE-214



LED Driver (0W-60W)

Length: 3-3/8" Dia.: 3-5/8", Max Ext.: 5-3/4"

One/Two Circuit Conversion

Positive contact (opposite neutral and ground contacts) is preset to "down" position at factory but may be raised to the higher position to install onto the second circuit of Nora Lighting NT-2300 series two-circuit track.

Optional Accessories

NM-100/MR16 MR16 Filter

(Blue, Clear, Frosted, Green, Linear, Pink, Red, Spread, Yellow)

Labels and Listings

cULus Listed



For a list of compatible LED MR16 lamps please refer to "Compatibility" tab under the "Resources" tab of the Nora web site.

Versa Wireback with Dimmable Ontegral Electronic Driver/Transformer

Catalog No.	Finish
NTLE-214	B = Black
	W = White

Create a complete item number: Example: NTLE-214B

NORALIGHTING.

6505 Gayhart St., Commerce, CA 90040 • Phone: 800.686.6672 • FAX: 800.500.9955 • www.noralighting.com
e-mail: nora@noralighting.com • Specifications subject to change without notice. © 2011