ENORALIGHTING.

Type


Project

Catalog No.

Lamp/Wattage

NTM-513 Air-Tight Baffle Cone with White Flange

DIMENSIONS



OD: 6-1/2" Aperture: 5" Height: 4-3/8"

FEATURES

Trim

Precision spun 0.040 baffle with deep grooves to reduce aperture glare and white flange.

Mounting

Trim includes two "V" torsion springs to mount trim securely to housing. Replacement "V" torsion springs are available (NRA-86). Remove socket from socket plate within housing (if applicable), and mount directly onto trim.

Compatible Housings

Compatible with Line Voltage, Compact Fluorescent, and GU24 housings. See individual specification sheets for more information.

Lamp

Line Voltage

75W BR30/PAR30 (NH-501Q; NHIC-501QAT; NHR-504Q; NHRIC-504QAT)

Note: 50W BR30/PAR30 when used with NTM-513MW

50W PAR30 (NHIC-527QAT; NHRIC-527QAT)

Compact Fluorescent

13W-26W Quad/Triple (NHP-501 Series; NHPIC-5 Series; NHRP-504 Series; NHRPIC-5 Series)

NHRP-504 GU24 Compact Fluorescent

13W-26W GU24 (NHIC-5G24ATFL, NHRIC-5G24ATFL)

Labels and Listings

cULus Listed for Damp Location when used with Compatible Housings

Compatible Housings

NHP-501/13

	LINE VOLTAGE				
Item Number	Installation Type	Lamp	Dimensions		
NH-501Q	Non-IC New Construction	75W BR/PAR30	W: 7-1/4" L: 10-1/2" H: 7-1/2"		
NHIC-501QAT	IC Air-Tight New Construction	75W BR/PAR30	W: 7-1/4" L: 10-1/2" H: 7-1/2"		
NHIC-527QAT	IC AT Shallow New Construct.	50W PAR30	W: 7" L: 10-1/2" H: 5-7/8"		
NHR-504Q	Non-IC Remodel Housing	75W BR/PAR30	W: 5-1/2" L: 13-1/2" H: 7-1/2"		
NHRIC-504QAT	IC Air-Tight Remodel Housing	75W BR/PAR30	W: 5-1/2" L: 13-1/2" H: 7-1/2"		
NHRIC-527QAT	IC Air-Tight Shallow Remodel	50W PAR30	W: 6-3/4" L: 13-1/4" H: 5-1/2"		
COMPACT FLUORESCENT					

	NHP-501/13EL	Non-IC New Construction	13W Quad/Triple	W: 7-3/8" L: 10-1/2" H: 7-1/2
	NHP-501/18EL	Non-IC New Construction	18W Quad/Triple	W: 7-3/8" L: 10-1/2" H: 7-1/2
	NHPIC-501QAT13	IC Air-Tight New Construction	13W 2-Pin Quad	W: 7-3/8" L: 11-1/2" H: 7-1/2
	NHPIC-513ELAT	IC Air-Tight New Construction	13W Quad/Triple	W: 7-3/8" L: 10-1/2" H: 7-1/2
	NHPIC-513ATE2	IC Air-Tight New Construction	13W Quad/Triple	W: 7-3/8" L: 10-1/2" H: 7-1/2
	NHPIC-518ELAT	IC Air-Tight New Construction	18W Quad/Triple	W: 7-3/8" L: 10-1/2" H: 7-1/2
	NHPIC-518ATE2	IC Air-Tight New Construction	18W Quad/Triple	W: 7-3/8" L: 10-1/2" H: 7-1/2
	NHPIC-526ELAT	IC Air-Tight New Construction	26W Quad/Triple	W: 7-3/8" L: 10-1/2" H: 7-1/2
	NHPIC-526ATE2	IC Air-Tight New Construction	26W Quad/Triple	W: 7-3/8" L: 10-1/2" H: 7-1/2
	NHRP-504/13	Non-IC Remodel Housing	13W 2-Pin Quad	W: 6-1/4" L: 13" H: 7-1/2"
	NHRP-504/13EL	Non-IC Remodel Housing	13W Quad/Triple	W: 6-1/4" L: 13" H: 7-1/2"
	NHRP-504/18EL	Non-IC Remodel Housing	18W Quad/Triple	W: 6-1/4" L: 13" H: 7-1/2"
	NHRPIC-504QAT13	IC Air-Tight Remodel Housing	13W 2-Pin Quad	W: 6-1/4" L: 13" H: 7-1/2"
	NHRPIC-513ELAT	IC Air-Tight Remodel Housing	13W Quad/Triple	W: 6-1/4" L: 13" H: 7-1/2"
	NHRPIC-513ATE2	IC Air-Tight Remodel Housing	13W Quad/Triple	W: 6-1/4" L: 13" H: 7-1/2"
	NHRPIC-518ELAT	IC Air-Tight Remodel Housing	18W Quad/Triple	W: 6-1/4" L: 13" H: 7-1/2"
	NHRPIC-518ATE2	IC Air-Tight Remodel Housing	18W Quad/Triple	W: 6-1/4" L: 13" H: 7-1/2"
I	NHRPIC-526ELAT	IC Air-Tight Remodel Housing	26W Quad/Triple	W: 6-1/4" L: 13" H: 7-1/2"
	NHRPIC-526ATE2	IC Air-Tight Remodel Housing	26W Quad/Triple	W: 6-1/4" L: 13" H: 7-1/2"

GU24 COMPACT FLUORESCENT

NHRIC-5G24ATFL | IC Air-Tight Remodel Housing | 13W-26W GU24 | W: 6-1/4" L: 13" H: 7-1/2"

IC Air-Tight New Construction | 13W-26W GU24 | W: 7-1/4" L: 10-1/2" H: 7-1/2"

Air-Tight Baffle Cone with White Flange

NTM-513B: Black Air-Tight Aluminum Baffle Cone with White Flange
NTM-513W: White Air-Tight Aluminum Baffle Cone with White Flange
NTM-513WM: White Air-Tight Metal Baffle Cone with White Flange



NHIC-5G24ATFL