

-1EN

- 2EN

- 3EN

- 4EN

RING

acid and LifePo4 batteries charging or discharging. Do not use any other type of battery.

Do not touch the battery terminals. They may result in injury, death or property damage.

Do not charge a battery if it is damaged, leaking, or of a specific chemistry or voltage, unless specifically approved by the manufacturer.

Do not use a charger if you find the charger is damaged or cracked, or if the battery is damaged or liquid overflow around the battery.

Do not use a charger if there are flames and sparks, do not expose the battery to high-temperature environment, or use the battery while charging, avoid any fire or explosion. It might spark or short-circuit the battery or cause an explosion.

Do not wear jewelry, such as rings, bracelets, necklaces, or watches, while charging.

Do not touch the battery before doing any maintenance or repair. Do not touch the battery until the battery is fully charged. Do not touch the battery while charging.

Battery type	Full of voltage
12V LITHIUM	Max 14.7V/ 12.6V
24V LITHIUM	Max 29.4V/ 25.2V
12V Lead-acid (AGM, GEL, EFB,MF, FLOODED, VRLA, SLA, WET, etc...)	Max 14.7V
24V Lead-acid (AGM, GEL, EFB,MF, FLOODED, VRLA, SLA, WET, etc...)	Max 29.4V
12V LIFEPO4	Max 14.6V
24V LIFEPO4	Max 29.2V

CE FC UK (PSE) RoHS  
Made in China

背面

1 Ladestrom Schalter, 3 Ebenen optional: 10A(12V)/5A(24V)

- 20- 3DE- 4C- 5

Description de l'interface du produit

28

ent end
- 3FB

4F5

Descripción de la interfaz del producto

283FS4F5

Descrizione dell'interfaccia del prodotto

2.30T41

1