



BOTTOM CONNECTED LIQUID FILLED GAUGES

MODEL BR201L

FEATURES:

The Model BR201L from Blue Ribbon Corporation is a high quality line of liquid filled gauges. The glycerine filling helps dampen the effects of vibration, which will extend the life of the gauge. This gauge is typically used on hydraulic and pneumatic systems as well as any commercial or industrial application not corrosive to brass and bronze wetted parts where glycerine filling is suitable for use.



Model BR201L

SPECIFICATIONS:

- Brass Internals and Connection
- Phosphor Bronze Bourdon Tube
- Liquid Filled (Dry Available)
- Accuracy:
 - 1½" and 2" Dial Sizes: 2%
 - 2½" Dial: 1.6%
 - 4" and 6" Dial Sizes: = 1%
- Dual Scale: PSI & BAR (x100=kPa)
- Single Scale (PSI) Available
- Ambient Temperature:
 - Filled: 0 °F to +15 °F
 - Dry: -30 °F to +150 °F
- Enclosure: IP65

FIELD OPTIONS:

- Dial Sizes:
 - 1½", 2", 2½", 4", 6"
- Connection Sizes:
 - 1/8" (M) NPT on 1½" and 2"
 - 1/4" (M) NPT on 2", 2½", and 4"
 - 1/2" (M) NPT on 4" and 6"
- U-Clamp Mount (BR203)
- Front Flange Mount (BR204)

RANGE	CODE	MAJOR INC.	MINOR INC.
30/0" VAC	A	5	0.5
30/0/15	CB	5	0.5
30/0/30	CC	10	1
30/0/60	CD	10	1
30/0/100	CE	20	2
30/0/150	CF	20	2
30/0/300	CH	50	10
0/15	B	2	0.2
0/30	C	5	0.5
0/60	D	10	1
0/100	E	20	2
0/160	F	20	2
0/200	G	40	4
0/300	H	50	5
0/400	I	50	5
0/500	J	100	10
0/600	K	100	10
0/800	L	100	10
0/1000	M	200	20
0/1500	N	200	20
0/2000	O	400	50
0/3000	P	500	50
0/4000	Q	500	50
0/5000	R	1000	100
0/6000	S	2000	200
0/10,000	U	2000	200
0/15,000	V	2000	200