

AUTO SURE LINE

IN-LINE AUTOMATIC FEEDING, LAMINATING AND CUTTING SOLUTION

- Automatic lamination system for offset and digital prints.
- In-line solution with high quality single and double-sided lamination for mass production.
- Equipped internal infrared heater to minimize deformation by heat and maximize adhesion.
- Low-noise vacuum pump as standard option for the better operation environment.



LOW NOISE
VACUUM PUMP



Using household power supply (220 ~ 240V)



SUREFEEDER-5478

- Only 10 minutes required for set-up.
- Automatic feeding system for both offset and digital prints.
- Wide range of substrates (120 ~ 300gsm) can be fed.
- Easy to set up with inching mode.
- Easy to integrate with the existing GMP Surelam Series Laminator (for example, Surelam III-540).
- Ergonomic designed touch panel.

SURELAM II & III-540 SERIES



- Hard surfaced rubber (H85) is applied to hot roller for high gloss effect in both single and double-sided lamination.
- Equipped de-curling device for single side lamination.
- 8-bit microprocessor for pre-program and save job modes for easy and user-friendly operation.
- Equipped photo-eye sensor at feeding area for safety operation.
- Available speed and temperature adjustment for perfect lamination.
- Top and bottom film alignment system (patented).



EASYCUTTER-550

- Compact and space-saving design.
- Various kinds and thickness of substrates that can be cut.
- Easy to operate with a user-friendly designed control panel.
- Equipped scrap paper basket.
- Equipped tray table.

Model Name	SUREFEEDER-5478	SURELAM II & III-540 SERIES	EASYCUTTER-550
Dimensions (WxLxH)	830 x 1060 x 1250mm	780 x 615 x 555mm (1,250mm)	890 x 510 x 1044mm
Operating Speed	Max. 10m/min	Max. 7m/min	Max. 10m/min
Operating Width	Max. 540mm	Max. 540mm	Max. 550mm
Laminating Films	-	25 ~ 250mic	25 ~ 250mic
Thickness of Substrate	120 ~ 350g/m ²	80 ~ 350g/m ²	120 ~ 350g/m ²
Feeder Loading Height	200mm (300g/m ² 700 sheets)	-	-
Power Requirements	AC 220V ~ 240V, 50/60Hz	AC 220V ~ 240V, 50/60Hz	AC 220V ~ 240V, 50/60Hz
Power Consumption	200W / 0.9A	2.8kw / 12.6A	460W / 2A
Max. Temperature	-	150°C	-
Speed Control	SURELAM II & III-540 Series	Key Pad	Jog Dial
Film Core Adaptor	-	19HX / 77(3") BK / Core	-
Cooling System	-	Blower	-
Type of Main Motor	DC Geard Motor	DC W-Geared Motor/OI2	Step Motor

GMP reserves the right to change specifications without prior notice.